

PRODUCT CODES:	ELRX010
NAME:	WB Reducer
DESCRIPTION:	ELRX010 is a reducer designed for use with any Envirolak topcoat or sealer.
USES:	This product is designed to quickly reduce the viscosity of water based coatings. Usage levels relative to water are approximately 2-3 times less, allowing for higher solids applications than with water alone.
PRODUCT PREPARATION:	Ready to use.
RECOMMENDED APPLICATION:	For use in any Envirolak water based coating. Please refer to the technical data sheet for the desired coating for recommended usage levels. We generally recommend ~2% in primers and clear topcoats and 5% in white topcoats.
PHYSICAL PROPERTIES:	Specific Gravity: 0.975 +/-2% Viscosity: NA (water thin) Solids Content: None Pot Life: None Flash Point: >75 C VOC's: 487 g/L, 5.85 lb/gal
GENERAL INFORMATION:	Please follow all recommended addition levels from the associated product you are using ELRX010 in. These products are designed for industrial use only. Please refer to the Safety Data Sheet prior to use.
SHELF LIFE:	24 months in unopened containers
STORAGE:	Store in a tightly closed container at room temperature (18-25°C/64-75°F) and protect from direct sunlight and foreign material.

Disclaimer: Every reasonable precaution is taken in the manufacture of our products to ensure that they comply with our standards. The information given herein is correct to the best of our knowledge. Any suggestions made by us covering the use of our products are based on experience and/or tests believed to be reliable. However, because the use of any product of our manufacture is completely beyond our control, including for example, the method and conditions of application, no guarantee or warranty, expressed or implied, is made. Manufacturer's maximum liability shall be to replace such quantity of product determined by our laboratory to be defective. User shall determine the suitability of the product for his intended use and assumes all risk and liability in connection therewith.