



unit: INCH

<b>L</b> LENGTH TOLERANCE	≤ 3/4	+ 0	- 0.03
	> 3/4" to ≤ 1-1/2"	+ 0	- 0.05
	> 1-1/2"	+ 0	- 0.06

**FULL THREAD**

SCREW SIZE	M PUNCH		Q DRIVE DEPTH	A HEAD DIAM.	H HEAD HEIGHT	D MAJOR DIAM.	d MINOR DIAM.	TEK SIZE	T POINT DIAM.	S POINT LENGTH	THREAD PER INCH	Min. Torsional Strength Lb/Inch
# 6	# 1	Min	0.050	0.238	Ref. 0.083	0.135	0.099	#2	0.108	0.143	20	24
		Max	0.065	0.262		0.139	0.104		0.112	0.155		
# 7	# 1	Min	0.050	0.262	Ref. 0.091	0.150	0.109	#2	0.119	0.178	19	34
		Max	0.065	0.287		0.154	0.115		0.124	0.200		
# 8	# 2	Min	0.060	0.285	Ref. 0.100	0.161	0.116	#2	0.131	0.188	18	42
		Max	0.075	0.312		0.166	0.122		0.136	0.211		
# 10	# 2	Min	0.060	0.333	Ref. 0.116	0.183	0.135	#2	0.149	0.214	16	61
		Max	0.075	0.362		0.189	0.141		0.158	0.235		

**Flat Countersunk Head, Quadrex recess, Self-Drilling Tapping Screw Type BSD 'TEK'  
Zinc plated**

Root= Flat Quadrex Tek Zinc

**Bulk Label Description:**

- English: FLAT HEAD, QUADREX, SELF DRILLING (TEK) SCREW, ZINC
- French: VIS AUTO-PERCEUSE (TEK), TÊTE PLATE, QUADREX, ZINC
- Spanish: TORNILLO AUTOPERFORANTE (TEK), CABEZA PLANA, QUADREX, ZINC

Date: 14 février 2023

Done by: P.B.