

speedbrace™

Patent Pending



TECHNICAL SPECIFICATIONS

The Speedbrace is a heavy duty countertop and shelf support brace without a kicker. They feature a 1.5" x 1.5" notch to enable fast alignment against a wall with a 2x2 cleat installed. Speedbraces also include pass-throughs for cords and chamfered screw holes. Speedbraces support up to 1,000 lbs per pair when installed at 16" on center.

Colors

- White powdercoat
- Black powdercoat
- Gray primer
- Stainless Steel

Sizes

- 21" x 28"
- 21" x 24"
- 15" x 18"
- 8" x 12"
- 5" x 8"



Material

- A-36 Steel plate
- 12 gauge (0.1046" thick)

Load Capacity

- 1,000 lbs. per pair (installed 16" on center)
- *round hole design only

Fasteners

- Designed for installation with conventional bugle-head or drywall screws
- Screw holes chamfered for flush installation
- Screws may be concealed with Fastcaps after installation
- Provision for 3 screws on wall side
- Offset screw holes on shelf side for flexibility

Other Features

- 1.5" x 1.5" notch in corner for installation against 2x2 wall cleat
- 5" x 8" Speedbrace has 1.5" x 0.5" notch for installation with 1x2 wall cleat
- Pass-through holes for cables & cords



Chamfered
Screw Hole



Capped with
9/16" Fastcap