High Pressure Laminate by Wilsonart

Health Product Declaration v2.2

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 21813

CLASSIFICATION: 06 00 00 Wood, Plastics, and Composites

PRODUCT DESCRIPTION: High Pressure Decorative Laminates (HPL) are made from paper, thermoset resins, pigments and various fillers which are consolidated under high pressure and heat into a sheet. HPL is suitable for horizontal and vertical applications including but not limited to countertops, table tops, furniture, case goods, wall panels, interior architectural doors and partitions.

۰	

Product

Section 1: Summary

Basic Method / Product Threshold

CON.	TFNT	INVE	ENTC)RY

Inventory Reporting Format					
Nested Materials Method					
Basic Method					
Threshold Disclosed Per					
C Metavial					

Threshold level					
⊙ 100 ppm					
C 1,000 ppm					

C Per GHS SDS

C Other

3	esi	dua	ls/l	mp	uriti	es
-				٠٣	٠	

Considered

C Partially Considered

Not Considered

Explanation(s) provided for Residuals/Impurities? Yes No

All Substances Above the Threshold Indicated Are:

Characterized	C Yes Ex/SC C Yes C No
% weight and role prov	vided for all substances.

Screened	C Yes Ex/SC © Yes C No
Screened	C Yes Ex/SC © Yes C No

All substances screened using Priority Hazard Lists with results disclosed.

Identified ○ Yes Ex/SC ○ Yes ○ No All substances disclosed by Name (Specific or Generic) and

Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

HIGH PRESSURE LAMINATE [WOOD/CELLULOSE FIBER (KRAFT/DECORATIVE/OVERLAY) NoGS PHENOLIC RESIN LT-P1 | RES

MELAMINE RESIN LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

*Greenguard certificates referenced below, residual emissions < 7 ppb **Full ingredients disclosure withheld to protect proprietary formulation

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: SCS Indoor Advantage Gold VOC emissions: UL/GreenGuard Gold Certified

Other: NSF / ANSI 35

Sustainable forestry: FSC Certification - Chain of Custody (COC)

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1 and Option 2

Third Party Verified?

C Yes No

PREPARER: Self-Prepared

VERIFIER: **VERIFICATION #:** **SCREENING DATE: 2020-08-04** PUBLISHED DATE: 2020-09-23 EXPIRY DATE: 2023-08-04



Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

HIGH PRESSURE LAMINATE

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: UL-E Greenquard testing is recertified annually. For currrent certificate see www.wilsonart.com

OTHER PRODUCT NOTES: High Pressure Decorative Laminates (HPL) are made from paper, thermoset resins, pigments and various fillers which are consolidated under high pressure and heat into a sheet. The monomers and polymers react under these conditions to polymerize into a thermoset hard resin system. The residuals are a very small fraction of the unreacted monomers and are less than 7.3 parts per billion according to the UL 2818 Greenguard test protocol.

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2020-08-04		
%: 40.0000 - 80.0000	GS: NoGS	RC: PostC	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
None found			No	o warnings found on HPD Priority Hazard Lists

PHENOLIC RESIN ID: 9003-35-4

SUBSTANCE NOTES: Post-consumer recycled content varies by product type. For detailed information see www.wilsonart.com

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2020-08-04		
%: 15.0000 - 34.0000	GS: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Polymer species
HAZARD TYPE	AGENCY AND LIST TITLES	WA	RNINGS	
RESPIRATORY	AOEC - Asthmagens		Asthmagen (Rs) - sensitizer-induced	

SUBSTANCE NOTES: Exposure would occur only during paper treating operations in manufacturing.

MELAMINE RESIN ID: 9003-08-1

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCRE	HAZARD SCREENING DATE: 2020-08-04		
%: 2.3000 - 15.0000	GS: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Polymer species	
HAZARD TYPE	AGENCY AND LIST TITLES	WA	ARNINGS		
None found			No w	varnings found on HPD Priority Hazard Lists	

SUBSTANCE NOTES: Exposure would occur only during paper treating operations in manufacturing.



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

SCS Indoor Advantage Gold

CERTIFYING PARTY: Third Party

ISSUE DATE: 2019-

EXPIRY DATE:

CERTIFIER OR LAB: SCS Global

APPLICABLE FACILITIES: Temple, TX and Fletcher, NC

10-01

Services

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: Series: 107, 335, 350, 376 SCS-EC10.3-2014 v4.0

VOC EMISSIONS

UL/GreenGuard Gold Certified

CERTIFYING PARTY: Third Party

ISSUE DATE: 2004-

EXPIRY DATE:

CERTIFIER OR LAB: UL E

APPLICABLE FACILITIES: Temple, TX and Fletcher, NC

07-21

GreenGuard

CERTIFICATE URL:

https://www.wilsonart.com/resources?

category=Laminate&document_type=Sustainability

CERTIFICATION AND COMPLIANCE NOTES: Certification is renewed on an annual basis. The UL-E Greenguard Gold certification program shows compliance in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017. Additional information can be found in Section 5. UL-E Greengold Certificates of Compliance: 1110-420 - Wilsonart Laminate, 1106-420 - Wilsonart High-Wear Laminate, 1830-420 - Wilsonart x You, 62094-420 Virtual Design Library

OTHER

NSF / ANSI 35

CERTIFYING PARTY: Third Party

ISSUE DATE: 2012-

08-07

EXPIRY DATE:

CERTIFIER OR LAB: NSF

APPLICABLE FACILITIES: Temple, TX and Fletcher, NC

CERTIFICATE LIBI :

CERTIFICATION AND COMPLIANCE NOTES: Types: 174, 107, 117, 372, 374, 377, 350, 376, 362, 364, 367, 335, 336. Work contact surfaces acceptable as nonwork surfaces.

06-24

SUSTAINABLE FORESTRY

FSC Certification - Chain of Custody (COC)

CERTIFYING PARTY: Third Party

ISSUE DATE: 2019-

EXPIRY DATE:

CERTIFIER OR LAB: SCS Global

Services

APPLICABLE FACILITIES: Temple, TX and Fletcher, NC CERTIFICATE URL:

https://www.wilsonart.com/resources?

category=Laminate&document_type=Sustainability

CERTIFICATION AND COMPLIANCE NOTES: The Forest Stewardship Council (FSC) is an independent, non-government, notforprofit organization established to promote responsible forest management practices. FSC forest management certification is awarded to forest managers who adopt practices that provide environmental, social and economic benefits. FSC Mixed Certificate for Laminate: SCS-COC-002415 FSC Mix Credit

RECYCLED CONTENT

SCS Recycled Content Certification - Products

CERTIFYING PARTY: Third Party

ISSUE DATE: 2017-

01-01

EXPIRY DATE:

CERTIFIER OR LAB: SCS Global

Services

APPLICABLE FACILITIES: Temple, TX and Fletcher, NC

CERTIFICATE LIBI :

https://www.wilsonart.com/resources?

category=Laminate&document_type=Sustainability

CERTIFICATION AND COMPLIANCE NOTES: Recycle content is typically present in Wilsonart HPL products. The recycle content of the wood/cellulose fiber layers may vary depending on the product type, thickness and other attributes. For certificates covering specific products see: https://www.wilsonart.com/resources? category=Laminate&document_type=Sustainability



Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

WILSONART BRAND ADHESIVES

HPD URL: https://www.wilsonart.com/adhesives-products

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Adhesives are used to bond HPL to various substrates including particleboard, medium density fiberboard and hardwood faced plywood.

WILSONART DECORATIVE EDGE

HPD URL: https://www.wilsonart.com/laminate-edgeoptions

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

Eliminate the flat edges and brown seams traditionally associated with laminate surfaces with Wilsonart Decorative Edges. Available in a range of profiles offering modern look found on more expensive natural stone and engineered quartz.



Section 5: General Notes

Laminates are evaluated under the UL 2818 "GREENUARD Certification Program For Chemical Emissions for Building Materials, Finishes and Furnishings". Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2- 2017 in the office environment; while commercial furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011(R2016) and determined to comply with ANSI/BIFMA X7.1-2011(R2016) and ANSI/BIFMA e3-2014e Credit 7.6.1, 7.6.2, and 7.6.3 in a private office environment.

MANUFACTURER INFORMATION

MANUFACTURER: Wilsonart

ADDRESS: 2501 Wilsonart Drive

P.O. Box 6110

Temple TX 76503-6110, USA

WEBSITE: https://www.wilsonart.com

CONTACT NAME: Richard Conde
TITLE: Technical Services
PHONE: 800-433-3222

EMAIL: smartline@wilsonart.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple

NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or

reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances
 created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this