

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Fil-O-Wood™ Wood Putty

M741 - (color number)

Available in ½ pint and 1 gallon

Product Description: Mohawk Fil-O-Wood™ Wood Putty is water-based putty which can be easily applied to fill corner chips, holes, cracks, screw holes and other defects in wooden surfaces. Fil-O-Wood™ Wood Putty dries fast, is easy to use, and accepts stains, finish or paint.

Advantages:

1. Mild solvent system will not harm the surrounding finish.
2. Dries with minimum shrinkage and sands quickly.
3. Easy water clean-up.
4. Non-toxic, nonflammable.
5. Fil-O-Wood may be colored using Mohawk Blendal Powders.
6. Can be molded, chiseled, sawed, stained and topcoated.

Characteristics:

Weight per gallon: 14.61 lbs/gal*

Solids % (wt): 78.82*

Solids % (vol): 61.40*

Dry time:

VOC's (coating): 0.27 lbs/gal (32.49 g/l)

VOC's (material): 0.17 lbs/gal (20.65 g/l)

VHAP's: 0.0001 lbs VHAP's/lb solids (hap's compliant)

Package Life: 3 years

* Varies, depending on color

HMIS: Health – 2, Flammability – 0, Reactivity – 0, Personal Protection - X

Specifications:

Directions: Mix well before use. Apply with putty knife. Slightly over fill defect and allow to dry before sanding level.

Safety cautions: Warning! Causes eye and skin irritation.

Contains: crystalline silica, napheline syenite, water, mixture 1, propylene glycol, formaldehyde.

Other Hazards: Causes lung, eye, skin, nose and throat irritation. May cause allergic skin reaction. Overexposure may cause lung, kidney damage. Potential cancer hazard; contains formaldehyde which can cause respiratory sensitization. Harmful if swallowed.

Precautions: KEEP OUT OF REACH OF CHILDREN. Wash thoroughly after handling. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Use only with adequate ventilation. Close container after each use. Avoid contact with eyes, skin and clothing. Do not breathe dust, vapors or spray mist.

This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

For industrial and commercial use only

First Aid: If swallowed, do not induce vomiting. Get medical attention immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

See Material Safety Data Sheet (MSDS) for more information.

MSDS: If Material Safety Data Sheet is required, contact:
Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.
P O Box 22000
Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545

Website: www.mohawk-finishing.com