



RICHELIEU SEALANTS LEED Green Building Rating System

This document provides product information so that RICHELIEU sealants can be evaluated for use under the LEED Green Building Rating System.

Table of Applicable LEED Points			
LEED Requirement	Applicable Richelieu Product(s)	LEED Guide Reference	LEED Points
Building materials to be manufactured within 500 miles (800 km) of the project site	941600-11 941600-30	MR Credit 5.1	1
Low-Emitting VOC Materials: Adhesives & Sealants	941501-11 941501-30 941600-11 941600-30	EQ Credit 4.1	1

- **LEED MR Credit 5.1** - Products are manufactured in Ontario facility.
- **LEED EQ Credit 4.1** – Products that have VOC (Volatile Organic Compound) contents that are less than the limit of the State of California’s South Coast Air Quality Management District (SCAQMD) Rule #1168, amended January 19, 2010. The current VOC limit for Architectural Sealants is 250 grams per liter and this category refers to any sealant that can be applied to stationary structures, including mobile homes, and their appurtenances, for example, hand railings, cabinets, bathroom and kitchen fixtures, fences, rain gutters and downspouts, and windows. The current VOC limit for Plastic Foams, Sub-Floor, Drywall and Panel Construction Adhesives is 50 grams per liter.

Prepared by the Technical Services Department
Date: February 12, 2015

Jacques LeBlanc
Product Manager

Richelieu Hardware Ltd.
7900, Henri-Bourassa Boulevard West
Montreal, Quebec, Canada
H4S 1V4

(Canada) 1 800 361-6000
(US) 1 800 619-5446
www.richelieu.com