

Be sure to read and understand all instructions before installation. For best results have installation completed by a qualified technician.

CAUTION: to reduce the risk of fire or electric shock:

Use only insulated staples or plastic ties to secure cords

Route the low voltage wire from the light so that they will not be damaged or pinched when the cabinet is installed (pushed to the wall)

Not intended for recessed ceiling installation or soffits

Low voltage portable cabinet lights maybe installed in furniture or cabinets when:

The power supply is located outside cabinets and is not concealed (this does not apply to the wiring between the light and the power supply)

When the low voltage wire are not concealed or pass through the structure of the building (concealed behind the wall) where it may be inaccessible for examination or where damage to may go unnoticed.

Cords should be visible and examined regularly


Installation instructions:

•For best results, have lighting professionally installed by a qualified licensed Electrician

•Turn power off prior to installation

WARNING: Always connect the LED light to the power supply first and then connect the power supply to the mains, failure to do so may cause damage to the existing diode.


1



Installation I


- 1.adhesive the 3M metal sheet on the magnet
- 2.peel off paper, stick the strip to the mounting surface

2




Installation II

- 1.screw the clip on the wall
- 2.snap the strip in the clips



Link more than 2 fixtures together with either the included direct connector or connecting cable



1. Use correct rated adaptor and components to operate light bar.
2. Plug the DC connector of the desktop adaptor into the light bar and make sure to match the polarity signs on both sides.
3. The total power of light bar in series can not exceed the power of desktop adaptor.

There is no replacement bulb available for this light due to its life span average of 50,000 hours

Richelieu grants no warranty on LED lights if another power supply other than the one specifically prescribed for this product is used.

Do not exceed the maximum wattage by connecting more lights than prescribe damage to the power supply may result.

All unused power supply output plugs must have jumper installed.

Do not cut or splice wiring or the lighting system may be damaged and manufacturer's warranty is voided.

The power supply has a polarized plug (one blade is wider than the other) as a safety feature to reduce the risk of electric shock. This plug will fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified technician. Never use an extension cord unless the plug can be fully inserted. Do not alter the plug.