

Grey Thermoplastic Rubber I Caoutchouc thermoplastique gris I



F24814



F24787



F24723



F24732

FEATURES AND APPLICATIONS

- Non-marking ride, ideal on hard surface floors such as hardwood
- **IMPROVEMENTS:** increased load capacities, wheel material (TPR), and now available with **Full Lock** brake, which locks both the wheel and the swivel
- Thread guards (except for threaded stem casters)
- Fits perfectly indoor – in the kitchen, living room, or in the office

CARACTÉRISTIQUES ET APPLICATIONS

- Bande de roulement qui ne marque pas, idéal pour les planchers de bois franc
- **AMÉLIORATIONS :** capacités de charge augmentées, matériau de roue (CTP), et maintenant disponibles avec frein **Full Lock** qui bloque la roue et le pivot
- Pare-fils de roue (sauf pour les roulettes à tige filetée)
- Idéale à l'intérieur – dans la cuisine, le salon ou le bureau

No.	TYPE	A	B	C	D	E x F	See / Voir : page 36	
				TREAD WIDTH LARGEUR DE BANDE	TOTAL HEIGHT HAUTEUR TOTALE	OFFSET DISTANCE DISTANCE DE DÉPORT	PLATE SIZE DIMENSION DE PLAQUE	WEIGHT POIDS
★ F24784	Swivel / Pivot	2" / 50 mm	110 lb / 50 kg	11/16" / 18 mm	2-13/16" / 71 mm	1" / 25 mm	2-1/8" x 2-1/8" 54 x 54 mm	0.44 lb 0.2 kg
★ F24785	Swivel + brake Pivot + frein	2" / 50 mm	110 lb / 50 kg	11/16" / 18 mm	2-13/16" / 71 mm	1" / 25 mm	2-1/8" x 2-1/8" 54 x 54 mm	0.5 lb 0.23 kg
★ F24814	Rigid / Fixe	2" / 50 mm	110 lb / 50 kg	11/16" / 18 mm	2-3/4" / 70 mm		2-1/8" x 2-1/8" 54 x 54 mm	0.29 lb 0.13 kg
★ F24786	Swivel / Pivot	3" / 75 mm	165 lb / 75 kg	15/16" / 24 mm	3-15/16" / 100 mm	1-11/32" / 34 mm	2-3/8" x 2-3/8" 60 x 60 mm	0.66 lb 0.3 kg
★ F24787	Swivel + brake Pivot + frein	3" / 75 mm	165 lb / 75 kg	15/16" / 24 mm	3-15/16" / 100 mm	1-11/32" / 34 mm	2-3/8" x 2-3/8" 60 x 60 mm	0.78 lb 0.35 kg
★ F24815	Rigid / Fixe	3" / 75 mm	165 lb / 75 kg	15/16" / 24 mm	3-15/16" / 100 mm		2-3/8" x 2-3/8" 60 x 60 mm	0.56 lb 0.26 kg

No.	MOUNTING FIXATION	A	B	C	E x F	See / Voir : page 36		
		BRAKE FREIN ¹			TREAD WIDTH LARGEUR DE BANDE	TOTAL HEIGHT HAUTEUR TOTALE ²	OFFSET DISTANCE DISTANCE DE DÉPORT	WEIGHT POIDS
N F24722	Threaded stem / Tige filetée 3/8"-16 x 1"	✗	2" / 50 mm	110 lb / 50 kg	7/8" / 22 mm	2-17/32" / 64 mm	1-1/16" / 27 mm	0.3 lb 0.13 kg
N F24723	Threaded stem / Tige filetée 3/8"-16 x 1"	✓	2" / 50 mm	110 lb / 50 kg	7/8" / 22 mm	2-17/32" / 64 mm	1-1/16" / 27 mm	0.33 lb 0.15 kg
N F24712	Threaded stem / Tige filetée 3/8"-16 x 1-1/2"	✗	2-1/2" / 63.5 mm	110 lb / 50 kg	15/16" / 24 mm	3-1/4" / 82.5 mm	1-3/16" / 30 mm	0.55 lb 0.25 kg
N F24713	Threaded stem / Tige filetée 3/8"-16 x 1-1/2"	✓	2-1/2" / 63.5 mm	110 lb / 50 kg	15/16" / 24 mm	3-1/4" / 82.5 mm	1-3/16" / 30 mm	0.63 lb 0.29 kg
N F24732	Threaded stem / Tige filetée 3/8"-16 x 1-1/2"	✗	3" / 75 mm	165 lb / 75 kg	29/32" / 23 mm	3-5/8" / 92 mm	1-5/16" / 33 mm	0.61 lb 0.28 kg
N F24733	Threaded stem / Tige filetée 3/8"-16 x 1-1/2"	✓	3" / 75 mm	165 lb / 75 kg	15/16" / 24 mm	3-5/8" / 92 mm	1-5/16" / 33 mm	0.67 lb 0.3 kg

¹ Side friction brake / Frein à serrage latéral

² Stem not included / N'inclus pas la tige