



unit: INCH

<b>L</b> LENGTH TOLERANCE	1-1/4"	+ 0	- 0.05
	> 1-1/4" to ≤ 2-3/4"	+ 0	- 0.06
	> 2-3/4"	+ 0	- 0.09

<b>S</b> THREAD LENGTH	≤ 1-3/4"	Full Thread
	> 1-3/4"	1-3/4" ± 0.05

SCREW SIZE		A ACROSS FLAT	W WASHER DIAM.	H HEAD HEIGHT	U WASHER THICKNESS	E BODY DIAM.	D HI THREAD DIAM.	d1 LOW THREAD DIAM.	d MINOR DIAM.	N SLOT WIDTH	T SLOT DEPTH	THREAD PER INCH	TORK INCH/ POUND
<b>3/16</b>	Min	0.244	0.322	0.096	0.019	0.146	0.205	0.150	0.126	<b>0.045</b>	<b>0.052</b>	16	56
	Max	0.250	0.348	0.110	0.031	0.151	0.215	0.163	0.138	<b>0.054</b>	<b>0.074</b>		
<b>1/4</b>	Min	0.305	0.398	0.139	0.022	0.185	0.244	0.193	0.165	<b>0.056</b>	<b>0.077</b>	14	142
	Max	0.312	0.432	0.155	0.039	0.190	0.255	0.205	0.178	<b>0.067</b>	<b>0.103</b>		

**Indented Slotted Hex Washer head, Hi-Low Thread with 3 cut, BLUE 'Ruspert' ( 1000 hours SST )**

Root= Hex Concrete BBlue

**Bulk Label Description:**

English: HEX/WASHER HEAD, HI-LOW THREAD, CONCRETE SCREW, BLUE 'RUSPERT'

French: VIS À BÉTON, TÊTE HEX/RONDELLE, FILET HI-LOW, 'RUSPERT' BLEU

Spanish: TORNILLO PARA HORMIGÓN, CABEZA HEXAGONAL CON ARANDELA, HI-LOW, 'RUSPERT' AZUL

Date : 5 avril 2019

Done by : P.B