

Airmix® Fluid Tips

Tip Number	Fluid Output				Diameter in Inches	Diameter in mm	Gun Filter		Pump Filter		Spray Angle and Maximum Fan Width at 10" (25cm)													
	500 psi 35 bar		1000 psi 70 bar				Mesh	Filter #	Mesh	Filter #	10°	18°	30°	40°	45°	50°	60°	67°	75°	82°	90°			
	oz/ min	cm ³ / min	oz/ min	cm ³ / min							3.5"	5"	7"	9"	9.5"	10"	12"	13"	15"	18"	22"			
	9 cm	13 cm	18 cm	23 cm			24 cm	25 cm	31 cm	33 cm	38 cm	46 cm	60 cm											
02	1.2	40	3.4	100	0.005	0.127	140 (4)	200 (2)	02-03	02-05														
03	3.4	100	5.1	150	0.007	0.178			03-03	03-05	03-07													
04	5.1	150	6.8	200	0.009	0.229			04-03	04-05	04-07	04-09	04-10	04-11	04-13									
06	6.8	200	11.2	330	0.011	0.279	85 (6)	140 (4)	06-03	06-05	06-07	06-09	06-10	06-11	06-13	06-15								
09	10.1	300	15.2	450	0.013	0.330			09-03	09-05	09-07	09-09	09-10	09-11	09-13	09-15								
12	11.2	350	20.3	600	0.015	0.381	60 (12)	70 (8)	12-03	12-05	12-07	12-09	12-10	12-11	12-13	12-15	12-17							
14	13.5	400	24.4	720	0.016	0.406			14-03	14-05	14-07	14-09	14-10	14-11	14-13	14-15	14-17							
18	15.2	450	28.7	850	0.018	0.457			18-05	18-07	18-09	18-10	18-11	18-13	18-15	18-17								
20	16.9	500	35.8	1060	0.020	0.508	60 (12)	60 (12)			20-07	20-09	20-10	20-11	20-13	20-15	20-17	20-19						
25	22.0	650	45.0	1330	0.022	0.559						25-07	25-09	25-10	25-11	25-13	25-15	25-17	25-19					
30	25.4	750	54.1	1600	0.024	0.610						30-07	30-09	30-10	30-11	30-13	30-15	30-17	30-19					
40	33.3	985	66.6	1970	0.027	0.686							40-09	40-10	40-11	40-13	40-15	40-17	40-19	40-21				
45	38.9	1150	77.8	2300	0.029	0.737								45-10	45-11	45-13	45-15	45-17	45-19	45-21				
60	43.3	1281	86.6	2561	0.031	0.787								60-10	60-11	60-13	60-15	60-17	60-19	60-21				

Standard tips
 - To order a tip, replace the crosses in 134-50x-xx4 with the corresponding number from the chart above. (Example: 134-506-094 for a 06-09 tip) When ordering a 100 tip, use 134-xxx-xx4 (Example: 134-100-134).

Xtra™ tips
 To order a tip, replace the crosses in 134-50x-xx2 with the corresponding number from the chart above. (Example: 134-506-092 for a 06-09 tip) Ideally used for waterborne materials.

Special Order tips
 - These tips require a minimum of 25 tips per order and these tips cannot be ordered in the Xtra™ tip style.

Optimum Fan Adjustment
 - These tips allow for fan adjustment when used with a VX14 air cap.

Xcite™ SPRAY GUNS WITH SWIVEL FITTING

Description	Aircap	Tip	Maximum Fluid Pressure	Seat	Part Number
Xcite™ 120	VX 24 K HVLP	Please specify (see table)	1740 psi (120 bar)	Stainless Steel	668-720-100
Xcite™ 200	VX 24 K HVLP	Please specify (see table)	2900 psi (200 bar)	Carbide	668-720-200