

M.L. Campbell 224 Catherine Street Fort Erie, Ontario L2A 5M9 Canada

Tel: 1(800) 364-1359 Web: www.mlcampbell.com

# **Product Information (PI) Sheet**

**Product: Care Reducer** 

Code(s): C162 1

**Description:** 

Care Lacquer Reducer is a blend of special evaporating solvents. The addition of small amounts will correct most leveling and flow problems. The recommended amounts is 10 to 12 ounces per gallon. Care Lacquer Reducer contains no aromatic or

ketone solvents.

Other To thin lacquer for use under extreme conditions, use C1611 Care Retarder.

**Products:** 

Physical Properties (packaged)		
Weight per Gallon:	7.07 lbs.	
Flash Point (PMCC):	83°F (28.3°C)	
VOC:	907 g/l (7.56 lbs./gal.)	
Photochemically Reactive:	No	

#### **Application Procedure**

For sealer coats, use a minimal amount (2 to 4 ounces per gallon) to solve blushing problems. For topcoat finishes, larger amounts (3 to 12 ounces per gallon) may be added for flow, leveling or blushing problems. The use of reducer will alter the dry time in proportion to the amount added. Excessive use of reducer can increase sheen levels. Do not use in waterborne coatings.

Packaging/Shipping				
Available Units:	Gallons and Pails.			

## Shelf Life and Storage

- Store in cool, dry areas in the original sealed containers.
- Do not store around any source of flames or sparks.
- Spills should be cleaned up with non-sparking tools and inert absorbent material.

DOT Classification					
Flammable Liquid	Re	d Label	UN1263		
B/L Description					
Paint	UN 1263	3	PG II		

### Caution

- THESE PRODUCTS ARE DESIGNED FOR SHOP APPLICATION AND PROFESSIONAL USE ONLY.
- Use only after all safety information is understood.
- Refer to the Material Safety Data Sheet (MSDS) for additional information.

#### **Testing**

Due to the wide variety of substrates, surface preparation methods, application methods, and environments, customers should test the complete system for adhesion and compatibility under their conditions prior to full-scale application.

#### Notes

The information, rating, and options stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application that are not known or under our control, M.L. Campbell cannot make any warranties as to the end result. *Thank you for using M.L. Campbell Wood Finishing products*.