



P.O. BOX 3649 • CROSSVILLE, TN 38557 • (931) 484-9578 • FAX (931) 484-7614

BENCO #B7 INDUSTRIAL PAINT REMOVER

Description

Benco #B7 is a liquid, non-flammable, water rinsable remover capable of stripping most paints and finishes. #B7 will rapidly strip shellacs, varnishes, lacquers, polyurethanes, enamels, latex, acrylics, and precatalyzed lacquers. #B7 is very thin and penetrates rapidly into corners and through finishes. #B7 has a long wet life and contains detergents that enable clean and thorough rinsing with water. #B7 is formulated with the highest quality virgin solvents, surfactants, and additives.

Characteristics

Methylene Chloride Content	75-80% by weight
Specific Gravity	1.195 (10 lbs./gal.)
Percent Volatile	>95%
VOC Content	180 grams/liter (1.5 lbs./gal.)
Boiling Point (Initial)	104 degrees F
Freezing Point	Less than -40 F
Flash Point:	N/A
Shelf Life:	Minimum 1 year, unopened, stored at less than 75 F

Application

Apply Benco #B7 by pouring or flowing over surface or by immersion. Product can be pumped with a Benco electric flow system or diaphragm flow system.

Apply a liberal coat and allow product to strip all coatings prior to removal. Thin coatings and clear finishes will usually strip in 2 – 30 minutes.

For items with multiple coatings, apply repeated liberal coats of stripper until all finishes are removed. Avoid brushing until the base coat is loosened from the surface.

If the product has dried on the surface, reapply a coat of stripper prior to removal of finish for best results.

Stripped finishes can be removed with a brush or squeegee. In a flow system, allow stripped residue to settle in container, and decant stripper for reuse.

For best results, once finishes are removed from the surface, rinse with water. Denatured alcohol can be used as an alternative to water.

For complete stain removal, after rinsing apply a solution of 1 lb. Oxalic acid in 5 gallons of water, let stand for 30 seconds or more, and wash the oxalic solution from the surface. Clean up with water.

Contact Benco at 800-632-3626 for technical assistance.