TECHNICAL DATA SHEET



LAKPRIMER 578

PU white primer

Rev. 4 del 10/04/2024

Product code LBP 578

Hardener 30% LCB178/046/185/195 by weight

50% LCB178/046/185/195 by volume

Thinner LZD 096/083/091 for dilution ratio, see *PREPARATION OF THE PRODUCT*



FIELDS OF APPLICATION

PU white primer suitable for cabinets, furniture and fixtures, furnishing components, frames and various wooden or MDF items. Only for interior use varnishing cycles.

PROPERTIES

Excellent filling power together with white covering. Good verticality, elasticity and sandability.

TECHNICAL DATA

Density (20°C/68°F)		Viscosity (20°C/68°F)	
Density lb/USgal	12.267 ± 0.15	DIN 8	35" ± 3"
Density g/L	1,470 ± 20		
Solids content by weight	71.1% ± 1	Solids content by volume	51.2% ± 1
		According to ISO 2322-3:2015	
VOCs Actual		VOCs Regulatory	
VOCs lb/USgal	3.423 - 3.668	VOCs lb/USgal	3.423 - 3.668
VOCs g/L	410 - 440	VOCs g/L	410 - 440
VOCs %	27.9 - 29.9		
	•		
	LBP578 +50%		330 - 338
Theor. Coverage - 1 dry mil	LCB181 +20% LZD096		ft²/USgal
Pot-life A+B			> 3 h with LCB178

DRYING TIME

Shelf-life

Dust-free 15 min
Dry to touch 50 min
Overcoatable (without sanding) 40 min - 3 h
Thoroughly dry > 8 h
Ready to be sanded 6 h
Top-coat application 8 h

PRODUCT PREPARATION

	by volume		by weight	
LAKPRIMER 578 - LBP578	10 parts	100%	10 parts	100%
Catalyst LCB 178/046/185/195	5 parts	50%	3 parts	30%
Thinner LZD xxx	2 - 3.5 parts	20 - 35%	1 - 2 parts	10 - 20%

SIVAM COATINGS SPA

Via Monviso 10 | 20008 Bareggio (MI) Italy | T +39 02 903041 | F +39 02 9014289

SEDE LEGALE Via Chiosetto 18 | 20122 Milano Italy | T +39 02 903041 | F +39 02 9014289

R.E.A. della C.C.I.A.A. Milano 1186707 | Registro Imprese Milano n. 246901 | Capitale Sociale € 1.600.000 i.v. | P.IVA IT 07867800 158



18 months

TECHNICAL DATA SHEET



LAKPRIMER 578

PU white primer

Rev. 4 del 10/04/2024

APPLICATION

	Spray airmix	Airless spray
First layer quantities wet mils	5 - 6	5 - 6
Following coat wet mils	5 - 6	5 - 6
Maximum amount to apply wet mils	16	16
Dilution	15 - 25%	10 - 20%

SUGGESTED CYCLES

a) Substrate MDF, Tanganika-walnut, various veneers

Basecoat LAKPRIMER 578 - LBP 578 2 layers

Sanding 280 - 320 grain paper

Topcoat LACCASAT - LFP xxx 1 layer

b) Substrate Baseboards, wainscots, frames and turned parts of different essences

Basecoat LAKPRIMER 578 - LBP 578 1 - 3 layers

Sanding 280 - 320 grain paper

Topcoat CHROMOGLOSS - LGP xxx / LACCASAT or CHROMOSAT - LFP xx 1 layer

NOTES

It is possible to shade the **LAKPRIMER 578 - LBP 578** using the pigmented pastes of the range SIVACHROM - LXT 8xx up to a maximum of 5% without changing thecharacteristics of the product.

Catalyst features LCB 178 - standard version

LCB 046 - better elasticity

LCB 185 - faster drying, but less elasticity

LCB 195 - non-yellowing

On very porous substrates we suggest to apply before the primer, one coat of isolator LAKPRIMER 541 - LBP 541 or HIPOSEAL 020 - LDA 020.

To improve adhesion between coats and covering, we suggest to sand in between.

Do not use the product on substrates that have a certain natural movement.

STORAGE

The product, stored in the original well-closed containers, preferably at a temperature between 10 and 30 °C, has a shelf life of 18 months.

It must be stored in a cool and ventilated place, avoiding heat and sunlight.

Shake well before use.

NOTICE

The information contained in this technical data sheet is based on the average results obtained in our laboratories and are to the best of our experiences. However, since the outcome of the painting is influenced by elements that do not depend on our decisions and beyond our control, no responsibility can be assumed by our company regarding the result resulting from the use of our products. The user must ensure that the product corresponds to his needs, that it is suitable for his systems and for his specific conditions of use.

THE DATA REPORTED IN THIS SHEET ARE DETERMINED AT 20°C AND 70% R.H.

SIVAM COATINGS SPA

sivam.it

Via Monviso 10 | 20008 Bareggio (MI) Italy | T +39 02 903041 | F +39 02 9014289
SEDE LEGALE Via Chiosetto 18 | 20122 Milano Italy | T +39 02 903041 | F +39 02 9014289
R.E.A. della C.C.I.A.A. Milano 1186707 | Registro Imprese Milano n. 246901 | Capitale Sociale € 1.600.000 i.v. | P.IVA IT 07867800 158

