TECHNICAL DATA

PRODUCT : **LCB… (CATALYST SERIES)**

DEFINITION : **SECONDS ISOCYANIC COMPONENTS**

MAIN FIELDS OF USE:
Reaction Partner for products PU.

CHEMICAL-PHYSICAL PROPERTIES:

	SPECIFIC WEIGHT	DRY RESIDUE	VISCOSITY
LCB 004	0.910	17±2	40”±2CF2
LCB 047	**0.947**	**27±2**	**44"±2 CF2**
LCB 057	**0.995**	**48±2**	**67” ±2CF2**
LCB 070	**0.995**	**32± 2**	**43"±2 CF2**
LCB 082	**0.940**	**22±2**	**40”±2 CF2**
LCB 089	**0.960**	**26±2**	**44"±3 CF2**
LCB 131	**0.985**	**39 ± 2**	**47"±2 CF2**
LCB 151	**0.990**	**28 ± 2**	**48"±2 CF2**
LCB 178	**0.970**	**27 ± 2**	**42"±2 CF2**
LCB 182	**0,965**	**24 ± 2**	**46”±2 CF2**
LCB 185	**0.940**	**24 ± 2**	**42"±2 CF2**
LCB 189	**0.945**	**26 ± 2**	**44"±2 CF2**
LCB 190	**0.965**	**25± 2**	**43"±2 CF2**
LCB 195	**0.950**	**27±2**	**47”±2 CF2**
LCB205	**0.990**	**30±2**	**56±3 CF2**

T.D.LCB… February 2012 5°

NOTES:he informations contained in this technical data sheet is based on the average results obtained in our laboratories and is the best experience we have gained with the most rigorous, thorough tests and checks possible.
However, as every panel or support, even of the same type, may be different to every other one in terms of the characteristics that influence the outcome of painting operations considerably and as the environment, mixtures and the equipment used also contribute to the final results. The final result is thus the user’s exclusive responsability. The information given herein is based on a temperature of 20% at 70% relative humidity.