

## Safety Data Sheet



### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

Safety Data Sheet dated 10/9/2023, version 2

#### 1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: DILUENTE PU per Lucidi - PU Thinner for Glossy

Other means of identification:

Trade code: LZD083

Recommended use of the chemical and restrictions on use

Recommended use:

IS- Industrial use

PW - Professional use

Thinner for paints and varnishes

Solvent

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

SIVAM Coatings S.p.A - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02 903041

Importer:

Richelieu America Ltd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Distributor:

Richelieu America Ltd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number:

SIVAM Coatings S.p.A - Tel. +39 02- 903041

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

#### 2. HAZARD(S) IDENTIFICATION

Classification of the chemical

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor/... if you feel unwell.  
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO<sub>2</sub>, water spray. Do not use water jet.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	/	1
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		G

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Identification of the substance

Trade code: LZD083

>= 90% n-butyl acetate

REACH No.: 01-2119485493-29, Index number: 607-025-00-1, CAS: 123-86-4, EC: 204-658-1

B.6/3 Flam. Liq. 3 H226

A.8/3 STOT SE 3 H336

Mixtures

N.A.

### 4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

LZD083/2

Page n. 2 of 9

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO<sub>2</sub>, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

---

## 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

Always keep in a well ventilated place.  
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
Avoid accumulating electrostatic charge.  
Keep away from food, drink and feed.  
Incompatible materials:  
None in particular.  
Instructions as regards storage premises:  
Cool and adequately ventilated.  
Safety electric system.  
Storage temperature:  
Store at ambient temperature.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm

DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup>

- Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup>

- Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 11 mg/kg - Worker Professional: 11 mg/kg - Consumer: 6 mg/kg -

Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Intermittent emission - Value: 0.36 mg/l

Target: Freshwater sediments - Value: 0.98 mg/kg

Target: Marine water sediments - Value: 0.098 mg/kg

Target: Microorganisms in sewage treatments - Value: 35.6 mg/l

Target: Soil (agricultural) - Value: 0.09 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour: Liquid, Colourless

Odour: typical

Odour threshold: 7 - 20 ppm

pH: Not Relevant

Melting point / freezing point: - 98 °C

LZD083/2

Page n. 4 of 9

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

Initial boiling point and boiling range:	126 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.5% - 1.2 % Vol.
Vapour density:	4
Flash point:	27 °C
Evaporation rate:	N.D.
Vapour pressure:	15 hPa (20 °C)
Relative density:	0.880
Solubility in water:	5.3 g/l (20°C)
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	2.3
Auto-ignition temperature:	415 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

---

#### 10. STABILITY AND REACTIVITY

##### Reactivity

It may generate dangerous reactions (See subsections below)

##### Chemical stability

It may generate dangerous reactions (See subsections below)

##### Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), and nitrides.

It may catch fire on contact with oxidising mineral acids, powerful oxidising agents, and powerful reducing agents.

##### Conditions to avoid

Avoid accumulating electrostatic charge.

##### Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

##### Hazardous decomposition products

None.

---

#### 11. TOXICOLOGICAL INFORMATION

##### Information on toxicological effects

##### Toxicological information of the substance:

DILUENTE PU per Lucidi - PU Thinner for Glossy

##### a) acute toxicity

Not classified

No data available for the product

##### b) skin corrosion/irritation

Not classified

No data available for the product

##### c) serious eye damage/irritation

Not classified

No data available for the product

##### d) respiratory or skin sensitisation

Not classified

No data available for the product

##### e) germ cell mutagenicity

Not classified

No data available for the product

##### f) carcinogenicity

Not classified

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

- No data available for the product
- g) reproductive toxicity  
Not classified  
No data available for the product
- h) STOT-single exposure  
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure  
Not classified  
No data available for the product
- j) aspiration hazard  
Not classified  
No data available for the product
- n-butyl acetate - CAS: 123-86-4  
The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.  
Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

Substance(s) listed on the NTP report on Carcinogens:

No.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

No.

Substance(s) listed as NIOSH Carcinogen(s):

No.

---

## 12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

DILUENTE PU per Lucidi - PU Thinner for Glossy

Not classified for environmental hazards

No data available for the product

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 200 mg/l - Duration h: 72

Persistence and degradability

n-butyl acetate - CAS: 123-86-4

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

---

## 13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

## 14. TRANSPORT INFORMATION

LZD083/2

Page n. 6 of 9

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy



UN number  
 ADR-UN Number: 1123  
 DOT number: UN1123  
 IATA-UN Number: 1123  
 IMDG-UN Number: 1123

UN proper shipping name  
 ADR-Shipping Name: BUTYL ACETATES  
 DOT-Shipping Name: Butyl acetates  
 IATA-Shipping Name: BUTYL ACETATES  
 IMDG-Shipping Name: BUTYL ACETATES

Transport hazard class(es)  
 ADR-Class: 3  
 DOT Hazard Class: 3  
 ADR - Hazard identification number: 30  
 IATA-Class: 3  
 IATA-Label: 3  
 IMDG-Class: 3  
 IMDG-Class: 3

Packing group  
 ADR-Packing Group: III  
 DOT Packing group: III  
 IATA-Packing group: III  
 IMDG-Packing group: III

Environmental hazards  
 ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
 N.A.

Special precautions  
 Rail (RID): 3  
 DOT Special provisions: B1, IB3, T2, TP1  
 ADR-Subsidiary hazards: -  
 ADR-S.P.: -  
 ADR-Transport category (Tunnel restriction code): 3 (D/E)  
 IATA-Passenger Aircraft: 355  
 IATA-Subsidiary hazards: -  
 IATA-Cargo Aircraft: 366  
 IATA-S.P.: A3  
 IATA-ERG: 3L  
 IMDG-EmS: F-E , S-D  
 IMDG-Subsidiary hazards: -  
 IMDG-Stowage and handling: Category A  
 IMDG-Segregation: -

## 15. REGULATORY INFORMATION

### USA - Federal regulations

#### TSCA - Toxic Substances Control Act

This substance is listed on the TSCA inventory.

TSCA listed substances:

n-butyl acetate is listed in TSCA Section 8b.

#### SARA - Superfund Amendments and Reauthorization Act

## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

Section 302 – Extremely Hazardous Substances: No.

Section 304 – Hazardous substances: Yes.

Section 313 – Toxic chemical list: No.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: n-butyl acetate - Reportable quantity: 5000 pounds.

CAA - Clean Air Act

CAA listed substances:

n-butyl acetate is listed in CAA Section 111 >= 90%.

CWA - Clean Water Act

CWA listed substances:

n-butyl acetate is listed in CWA Section 304, Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Yes.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Yes.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Yes.

Volatile Organic compounds - VOCs = 100.00 %

Volatile Organic compounds - VOCs = 880.00 g/l

Volatile CMR substances = 0.00 %

Organic Carbon - C = 0.62

---

## 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Safety Data Sheet dated 10/9/2023, version 2

Sections modified from the previous revision:

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

9. PHYSICAL AND CHEMICAL PROPERTIES

12. ECOLOGICAL INFORMATION

SECTION 14: Transport information

15. REGULATORY INFORMATION

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical



## Safety Data Sheet

### LZD083 DILUENTE PU per Lucidi - PU Thinner for Glossy

	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average