



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

Safety Data Sheet dated 11/28/2022, version 2

1. IDENTIFICATION Product identifier Mixture identification: Trade name: IDROPRIMER Fondo bianco per interno - White WB primer interior Other means of identification: Trade code: IVT500 Recommended use of the chemical and restrictions on use Recommended use: IS- Industrial use PW - Professional use Water-based paint Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party Company: SIVAM Coatings S.p.A - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02 903041 Importer: Richelieu America Itd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000. Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300 Distributor: Richelieu America Itd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000. Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300 Competent person responsible for the safety data sheet: msds@sivam.it Emergency phone number: SIVAM Coatings S.p.A - Tel. +39 02- 903041 Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

Warning, Skin Sens. 1, May cause an allergic skin reaction.

Label elements Hazard pictograms:



Warning Hazard statements: H317 May cause an allergic skin reaction. Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P321 Specific treatment (see ... On this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

LVT500/2 Page n. 1 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

Special Provisions: None Hazards not otherwise classified identified during the classification process: None Ingredient(s) with unknown acute toxicity: None. Additional classification information NFPA rating:



HMIS rating:



3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A. Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 7% - < 10%	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]	Index number: CAS: EC: REACH No.:	13463-67-7 236-675-5	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
147 ppm	ammonia%	Index number: CAS: EC: REACH No.:	1336-21-6 215-647-6	 A.2/1B Skin Corr. 1B H314 A.8/3 STOT SE 3 H335 US-HAE/A1 Aquatic Acute 1 H400 Specific Concentration Limits: C >= 5%: STOT SE 3 H335
116 ppm	1,2-benzisothiazol-	Index	613-088-00-6	A.1/4/Oral Acute Tox. 4 H302



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

enor				
	3(2H)-one; 1,2- benzisothiazolin-3-one	number: CAS: EC: REACH No.:	2634-33-5 220-120-9 01- 2120761540 -60	 ⁽¹⁾ A.2/2 Skin Irrit. 2 H315 ⁽²⁾ A.3/1 Eye Dam. 1 H318 ⁽²⁾ A.4.2/1 Skin Sens. 1 H317 ⁽³⁾ US-HAE/A1 Aquatic Acute 1 H400 ⁽⁴⁾ US-HAE/C2 Aquatic Chronic 2 H411 Specific Concentration Limits: C >= 0,05%: Skin Sens. 1 H317
55 ppm	Decamethylcyclopentas iloxane (D5)	CAS: EC: REACH No.:	541-02-6 208-764-9 01- 2119511367 -43	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
37 ppm	Dodecamethylcyclohex asiloxane (D6)	CAS: EC: REACH No.:	540-97-6 208-762-8 01- 2119517435 -42	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
31 ppm	octamethylcyclotetrasilo xane (D4)	Index number: CAS: EC: REACH No.:	014-018-00-1 556-67-2 209-136-7 01- 2119529238 -36	 ♦ B.6/3 Flam. Liq. 3 H226 ♦ A.7/2 Repr. 2 H361 US-HAE/C4 Aquatic Chronic 4 H413
17 ppm	2-methyl-2H-isothiazol- 3-one	Index number: CAS: EC: REACH No.:	613-326-00-9 2682-20-4 220-239-6 01- 2120764690 -50	 A.1/2/Inhal Acute Tox. 2 H330 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Oral Acute Tox. 3 H301 A.2/1B Skin Corr. 1B H314 A.4.2/1A Skin Sens. 1A H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 Specific Concentration Limits: C >= 0,0015%: Skin Sens. 1 H317
6 ppm	mixture of: 5-chloro-2- methyl-4-isothiazolin-3- one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: CAS: REACH No.:	613-167-00-5 55965-84-9 01- 2120764691 -48	 A.2/1B Skin Corr. 1B H314 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/2/Inhal Acute Tox. 2 H330 Specific Concentration Limits: C >= 0,6%: Skin Corr. 1B H314 0,06% <= C < 0.6%: Skin Irrit. 2 H315 0,06% <= C < 0.6%: Eye Irrit. 2A

LVT500/2 Page n. 3 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

Skin Sens. 1 H317	H319 C >= 0,0015%: SI				
-------------------	--------------------------	--	--	--	--

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water. Carbon dioxide (CO2). Unsuitable extinguishing media: None in particular. Specific hazards arising from the chemical Do not inhale explosion and combustion gases. Burning produces heavy smoke. Hazardous combustion products: None Explosive properties: N.D. in volume Oxidizing properties: N.D. Special protective equipment and precautions for fire-fighters Use suitable breathing apparatus Collect contaminated fire extinguishing water separately. This must not be discharged into drains Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures Wear personal protection equipment. Remove persons to safety. See protective measures under point 7 and 8. Methods and materials for containment and cleaning up Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling Avoid contact with skin and eyes, inhalation of vapours and mists. Do not use on extensive surface areas in premises where there are occupants. Don't use empty container before they have been cleaned.

LVT500/2 Page n. 4 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contamined clothing should be changed before entering eating areas.
Do not eat or drink while working.
Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7 ACGIH - TWA(8h): 0.2 mg/m3 - Notes: Nanoscale particles; (R); A3 - LRT irr, pneumoconiosis ACGIH - TWA(8h): 2.5 mg/m3 - Notes: Finescale particles; (R); A3 - LRT irr, pneumoconiosis ammonia ...% - CAS: 1336-21-6 ACGIH - TWA: 18 mg/m3, 25 ppm - STEL: 27 mg/m3, 35 ppm Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6 ACGIH - TWA(8h): 10 ppm octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 ACGIH - TWA(8h): 123 mg/m3, 10 ppm mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 TLV TWA - 0,05 mg/m3 TLV STEL - 0,23 mg/m3 **DNEL Exposure Limit Values** titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7 Worker Industry: 3.3 mg/m3 - Worker Professional: 3.3 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects ammonia ...% - CAS: 1336-21-6 Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 36 mg/m3 - Worker Professional: 36 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Industry: 14 mg/m3 - Worker Professional: 14 mg/m3 - Consumer: 2.8 mg/m3 -Exposure: Human Inhalation - Frequency: Long Term, local effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Worker Industry: 24.2 mg/m3 - Worker Professional: 24.2 mg/m3 - Consumer: 4.3 mg/m3

LVT500/2 Page n. 5 of 12



Page n. 6 of 12

LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

- Exposure: Human Inhalation - Frequency: Long Term, local effects Worker Industry: 97.3 mg/m3 - Worker Professional: 97.3 mg/m3 - Consumer: 17.3 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6 Worker Industry: 6.1 mg/m3 - Worker Professional: 6.1 mg/m3 - Consumer: 1.5 mg/m3 -Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Industry: 11 mg/m3 - Worker Professional: 11 mg/m3 - Consumer: 2.7 mg/m3 -Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 1.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Worker Industry: 73 mg/m3 - Worker Professional: 73 mg/m3 - Consumer: 13 mg/m3 -Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg -Exposure: Human Inhalation - Frequency: Long Term, local effects Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects **PNEC Exposure Limit Values** titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7 Target: Fresh Water - Value: 0.184 mg/l Target: Marine water - Value: 0.0184 mg/l Target: Intermittent emission - Value: 0.61 mg/l Target: Freshwater sediments - Value: 1000 mg/kg Target: Marine water sediments - Value: 100 mg/kg Target: Microorganisms in sewage treatments - Value: 100 mg/l Target: Soil (agricultural) - Value: 100 mg/kg Target: Food chain - Value: 1667 mg/kg ammonia ...% - CAS: 1336-21-6 Target: Fresh Water - Value: 0.0011 mg/l Target: Marine water - Value: 0.0011 mg/l Target: Intermittent emission - Value: 0.0068 mg/l Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6 Target: Fresh Water - Value: 0.0012 mg/kg Target: Marine water - Value: 0.00012 mg/kg Target: Freshwater sediments - Value: 11 mg/kg Target: Marine water sediments - Value: 1.1 mg/kg Target: Microorganisms in sewage treatments - Value: 10 mg/l Target: Soil (agricultural) - Value: 2.54 mg/kg Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6 Target: Freshwater sediments - Value: 13 mg/kg Target: Marine water sediments - Value: 1.3 mg/kg Target: Microorganisms in sewage treatments - Value: 1 mg/kg Target: Soil (agricultural) - Value: 3.77 mg/kg octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Target: Fresh Water - Value: 0.0015 mg/l Target: Marine water - Value: 0.00015 mg/l Target: Freshwater sediments - Value: 3 mg/kg Target: Marine water sediments - Value: 0.3 mg/kg Target: Microorganisms in sewage treatments - Value: 10 mg/kg Target: Soil (agricultural) - Value: 0.54 mg/kg Target: Food chain - Value: 41 mg/kg Appropriate engineering controls: None Individual protection measures Eye protection: Eye glasses with side protection. (EN166) LVT500/2



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection: Not needed for normal use.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	White		
Odour:	typical		
Odour threshold:	N.D.		
pH:	8.5		
Melting point / freezing point:	N.D. °C		
Initial boiling point and boiling ra	ange:	> 100 °C	
Solid/gas flammability:	N.A.		
Upper/lower flammability or exp	losive lim	its:	N.D.
Vapour density:	> 1		
Flash point:	N.A. °C		
Evaporation rate:	N.D.		
Vapour pressure:	N.D. (20	°C)	
Relative density:	1.335 - 1	.355	
Solubility in water:	miscible		
Solubility in oil:	partial		
Partition coefficient (n-octanol/v	vater):	N.D.	
Auto-ignition temperature:	N.D. °C		
Decomposition temperature:	N.D. °C		
Viscosity:	N.D.		
Miscibility:	N.D.		
Fat Solubility:	N.D.		
Conductivity:	N.D.		
Substance Groups relevant pro	perties	N.A.	

10. STABILITY AND REACTIVITY

Reactivity Stable under normal conditions Chemical stability Stable under normal conditions Possibility of hazardous reactions Conditions to avoid Stable under normal conditions. Incompatible materials None in particular. Hazardous decomposition products None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects Toxicological information of the product: IDROPRIMER Fondo bianco per interno - White WB primer interior a) acute toxicity Not classified

LVT500/2 Page n. 7 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

No data available for the product
b) skin corrosion/irritation
Not classified
No data available for the product
c) serious eye damage/irritation
Not classified
No data available for the product
d) respiratory or skin sensitisation
The product is classified: Skin Sens. 1 H317
e) germ cell mutagenicity
Not classified
No data available for the product
f) carcinogenicity
Not classified
No data available for the product
g) reproductive toxicity
Not classified
No data available for the product
h) STOT-single exposure
Not classified
No data available for the product
i) STOT-repeated exposure
Not classified
No data available for the product j) aspiration hazard
Not classified
No data available for the product Toxicological information of the main substances found in the product:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter
$<= 10 \ \mu\text{m}$] - CAS: 13463-67-7
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
Test: LC50 - Route: Inhalation Dust - Species: Rat > 3.5 mg/l - Duration: 4h
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
a) acute toxicity: Teat: LD50_ Reute: Orel_ Species: Ret = 670 mg///g
Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg
Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg
octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 36 mg/l - Duration: 4h
Test: LD50 - Route: Skin - Species: Rabbit = 2.5 ml/kg
2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H
-isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS:
55965-84-9
a) acute toxicity:
Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h
Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg
Substance (a) listed on the NTD report on Consinguing
Substance(s) listed on the NTP report on Carcinogens: None.
Substance(s) listed on the IARC Monographs:

LVT500/2 Page n. 8 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μ m] - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μ m].

12. ECOLOGICAL INFORMATION

Ecotoxicity Adopt good working practices, so that the product is not released into the environment. IDROPRIMER Fondo bianco per interno - White WB primer interior Not classified for environmental hazards No data available for the product ammonia ...% - CAS: 1336-21-6 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96 Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48 Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d 2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72 Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96 b) Aquatic chronic toxicity: Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: NOEC - Species: Daphnia = 0.0035 mg/l - Notes: 21d - OECD 211 Endpoint: NOEC - Species: Fish = 0.02 mg/l - Notes: 38d - OECD 210 Persistence and degradability 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD 310 Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 4.47 - Notes: **OECD 310** octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310 LVT500/2

Page n. 9 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

Bioaccumulative potential Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6 Bioaccumulation: Bioaccumulative Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6 Bioaccumulation: Bioaccumulative octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Bioaccumulation: Bioaccumulative Mobility in soil N.A. Other adverse effects None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number Not classified as dangerous in the meaning of transport regulations. UN proper shipping name N.A. Transport hazard class(es) N.A. Packing group N.A. Environmental hazards ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) N.A. Special precautions N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory. TSCA listed substances:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μ m] is listed in TSCA Section 8b

ammonia ...% is listed in TSCA Section 8b

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR

2-methyl-2H-isothiazol-3-one is listed in TSCA Section 12b, Section 8b

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b.

LVT500/2 Page n. 10 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

SARA - Superfund Amendments and Reauthorization Act
Section 302 – Extremely Hazardous Substances: no substances listed.
Section 304 – Hazardous substances: ammonia%.
Section 313 – Toxic chemical list: ammonia%.
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA: ammonia% - Reportable quantity: 1000 pounds. Reportable quantity for mixture: 6802721.088 pounds.
CAA - Clean Air Act
CAA listed substances:
None.
CWA - Clean Water Act
CWA listed substances:
ammonia% is listed in CWA Section 311.
USA - State specific regulations
California Proposition 65
Substance(s) listed under California Proposition 65:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic
diameter <= 10 μm] - Listed as carcinogen. Massachusette Right to know
Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μm]
ammonia%.
New Jersey Right to know Substance(s) listed under New Jersey Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic
diameter <= 10 µm]
ammonia%.
Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic
diameter <= 10 µm]
ammonia%.
/olatile Organic compounds - VOCs = 3.66 %
/olatile Organic compounds - VOCs = 49.55 g/l

Volatile CMR substances = 0.00 %

Organic Carbon - C = 0.02

16. OTHER INFORMATION Full text of phrases referred to in Section 3:

H314 Causes severe skin burns and eye damage.

- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.
- H226 Flammable liquid and vapour.
- H361 Suspected of damaging fertility or the unborn child.
- H413 May cause long lasting harmful effects to aquatic life.
- H330 Fatal if inhaled.
- H311 Toxic in contact with skin.
- H301 Toxic if swallowed.

LVT500/2 Page n. 11 of 12



LVT500 IDROPRIMER Fondo bianco per interno - White WB primer interior

H410 Very toxic to aquatic life with long lasting effects. H319 Causes serious eye irritation.

Safety Data Sheet dated 11/28/2022, version 2 Sections modified from the previous revision:

- 2. HAZARD(S) IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- **15. REGULATORY INFORMATION**

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical
	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport
	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"
	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average

LVT500/2 Page n. 12 of 12