

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Safety Data Sheet dated 11/28/2022, version 2

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Other means of identification:

Trade code: LVT500

Recommended use of the chemical and restrictions on use

Recommended use: IS- Industrial use PW - Professional use Water-based paint

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

SIVAM Coatings S.r.I - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02 903041

Importer:

Richelieu America Ltd., 237 N River Rd Suite 2, Mt. Clemens MI 48043 USA 48043-1920

Tel: 1-800-619-5446

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Distributor:

Richelieu America Ltd., 237 N River Rd Suite 2, Mt. Clemens MI 48043 USA 48043-1920

Tel: 1-800-619-5446

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number:

SIVAM Coatings S.r.I - Tel. +39 02- 903041

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

♦ Warning, Skin Sens. 1, May cause an allergic skin reaction.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see ... On this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

LVT500/2

Page n. 1 of 12



·

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:



3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number		Classification
>= 7% - < 10%	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]	Index number: CAS: EC: REACH No.:	13463-67-7 236-675-5	The product is not classified as hazardous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
147 ppm	ammonia%	Index number: CAS: EC: REACH No.:	1336-21-6 215-647-6	 ♦ A.2/1B Skin Corr. 1B H314 ♦ A.8/3 STOT SE 3 H335 ♦ US-HAE/A1 Aquatic Acute 1 H400 Specific Concentration Limits: C >= 5%: STOT SE 3 H335
116 ppm	1,2-benzisothiazol- 3(2H)-one; 1,2- benzisothiazolin-3-one	Index number: CAS: EC:	613-088-00-6 2634-33-5 220-120-9	 ♠ A.1/4/Oral Acute Tox. 4 H302 ♠ A.2/2 Skin Irrit. 2 H315 ♠ A.3/1 Eye Dam. 1 H318 ♠ A.4.2/1 Skin Sens. 1 H317



•

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

		REACH No.:	01- 2120761540 -60	 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C2 Aquatic Chronic 2 H411 Specific Concentration Limits: C >= 0,05%: Skin Sens. 1 H317
55 ppm	Decamethylcyclopentas iloxane (D5)	CAS: EC: REACH No.:	541-02-6 208-764-9 01- 2119511367 -43	The product is not classified as hazardous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
37 ppm	Dodecamethylcyclohex asiloxane (D6)	CAS: EC: REACH No.:	540-97-6 208-762-8 01- 2119517435 -42	The product is not classified as hazardous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
31 ppm	octamethylcyclotetrasilo xane (D4)	Index number: CAS: EC: REACH No.:	556-67-2 209-136-7	 ♠ B.6/3 Flam. Liq. 3 H226 ♠ A.7/2 Repr. 2 H361 US-HAE/C4 Aquatic Chronic 4 H413
17 ppm	2-methyl-2H-isothiazol- 3-one	Index number: CAS: EC: REACH No.:	2682-20-4 220-239-6	 A.1/2/Inhal Acute Tox. 2 H330 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Oral Acute Tox. 3 H301 A.2/1B Skin Corr. 1B H314 A.4.2/1A Skin Sens. 1A H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 Specific Concentration Limits: C >= 0,0015%: Skin Sens. 1 H317
6 ppm	mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4)	Index number: CAS: REACH No.:	55965-84-9	 A.2/1B Skin Corr. 1B H314 A.3/1 Eye Dam. 1 H318 A.4.2/1 Skin Sens. 1 H317 US-HAE/A1 Aquatic Acute 1 H400 US-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/2/Inhal Acute Tox. 2 H330 Specific Concentration Limits: C >= 0,6%: Skin Corr. 1B H314 0,06% <= C < 0.6%: Skin Irrit. 2 H315 0,06% <= C < 0.6%: Eye Irrit. 2A H319 C >= 0,0015%: Skin Sens. 1 H317



LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into

drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

LVT500/2

Page n. 4 of 12



.

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m] - CAS: 13463-67-7

ACGIH - TWA(8h): 0.2 mg/m3 - Notes: Nanoscale particles; (R); A3 - LRT irr,

pneumoconiosis

ACGIH - TWA(8h): 2.5 mg/m3 - Notes: Finescale particles; (R); A3 - LRT irr,

pneumoconiosis

ammonia ...% - CAS: 1336-21-6

ACGIH - TWA: 18 mg/m3, 25 ppm - STEL: 27 mg/m3, 35 ppm

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

ACGIH - TWA(8h): 10 ppm

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

ACGIH - TWA(8h): 123 mg/m3, 10 ppm

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

TLV TWA - 0,05 mg/m3 TLV STEL - 0,23 mg/m3

DNEL Exposure Limit Values

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m] - CAS: 13463-67-7

Worker Industry: 3.3 mg/m3 - Worker Professional: 3.3 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

ammonia ...% - CAS: 1336-21-6

Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects

Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8

mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 36 mg/m3 - Worker Professional: 36 mg/m3 - Exposure: Human

Inhalation - Frequency: Short Term, local effects
Worker Industry: 14 mg/m3 - Worker Professional: 14 mg/m3 - Consumer: 2.8 mg/m3 -

Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Worker Industry: 24.2 mg/m3 - Worker Professional: 24.2 mg/m3 - Consumer: 4.3 mg/m3

- Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 97.3 mg/m3 - Worker Professional: 97.3 mg/m3 - Consumer: 17.3 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6



·

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Worker Industry: 6.1 mg/m3 - Worker Professional: 6.1 mg/m3 - Consumer: 1.5 mg/m3 -

Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 11 mg/m3 - Worker Professional: 11 mg/m3 - Consumer: 2.7 mg/m3 -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Worker Industry: 73 mg/m3 - Worker Professional: 73 mg/m3 - Consumer: 13 mg/m3 -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg -

Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m] - CAS: 13463-67-7

Target: Fresh Water - Value: 0.184 mg/l Target: Marine water - Value: 0.0184 mg/l Target: Intermittent emission - Value: 0.61 mg/l Target: Freshwater sediments - Value: 1000 mg/kg Target: Marine water sediments - Value: 100 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Soil (agricultural) - Value: 100 mg/kg Target: Food chain - Value: 1667 mg/kg

ammonia ...% - CAS: 1336-21-6

Target: Fresh Water - Value: 0.0011 mg/l Target: Marine water - Value: 0.0011 mg/l

Target: Intermittent emission - Value: 0.0068 mg/l

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Target: Fresh Water - Value: 0.0012 mg/kg Target: Marine water - Value: 0.00012 mg/kg Target: Freshwater sediments - Value: 11 mg/kg Target: Marine water sediments - Value: 1.1 mg/kg

Target: Microorganisms in sewage treatments - Value: 10 mg/l

Target: Soil (agricultural) - Value: 2.54 mg/kg Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

> Target: Freshwater sediments - Value: 13 mg/kg Target: Marine water sediments - Value: 1.3 mg/kg

Target: Microorganisms in sewage treatments - Value: 1 mg/kg

Target: Soil (agricultural) - Value: 3.77 mg/kg octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2 Target: Fresh Water - Value: 0.0015 mg/l

Target: Marine water - Value: 0.00015 mg/l Target: Freshwater sediments - Value: 3 mg/kg Target: Marine water sediments - Value: 0.3 mg/kg

Target: Microorganisms in sewage treatments - Value: 10 mg/kg

Target: Soil (agricultural) - Value: 0.54 mg/kg

Target: Food chain - Value: 41 mg/kg

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

LVT500/2

Page n. 6 of 12



.

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Not needed for normal use.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour: White Odour: typical Odour threshold: N.D. pH: 8.5

Melting point / freezing point: N.D. °C

Initial boiling point and boiling range: > 100 °C

Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.D.

Vapour density: > 1
Flash point: N.A. °C
Evaporation rate: N.D.
Vapour pressure: N.D. (20 °C)
Relative density: 1.335 - 1.355
Solubility in water: miscible
Solubility in oil: partial

Partition coefficient (n-octanol/water): N.D.

Auto-ignition temperature:
Decomposition temperature:
Viscosity:
Miscibility:
Fat Solubility:
Conductivity:

N.D. °C
N.D. °C
N.D.
N.D.
N.D.
N.D.

Substance Groups relevant properties N.A.

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

d) respiratory or skin sensitisation

LVT500/2

Page n. 7 of 12



·

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

The product is classified: Skin Sens. 1 H317

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

h) STOT-single exposure

Not classified

No data available for the product

i) STOT-repeated exposure

Not classified

No data available for the product

i) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m] - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat > 3.5 mg/l - Duration: 4h

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 36 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 ml/kg

2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h

Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None

Substance(s) listed on the IARC Monographs:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μ m] - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m].

12. ECOLOGICAL INFORMATION

LVT500/2

Page n. 8 of 12



·

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

```
Ecotoxicity
```

Adopt good working practices, so that the product is not released into the environment.

IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Not classified for environmental hazards

No data available for the product

ammonia ...% - CAS: 1336-21-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96

Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48 Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d

2-methyl-2H-isothiazol-3-one - CAS: 2682-20-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72 Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: NOEC - Species: Daphnia = 0.0035 mg/l - Notes: 21d - OECD 211

Endpoint. NOEC - Species. Daprina = 0.0033 mg/i - Notes. 210 - OECD 21

Endpoint: NOEC - Species: Fish = 0.02 mg/l - Notes: 38d - OECD 210

Persistence and degradability

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD 310

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 4.47 - Notes: OECD 310

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310

Bioaccumulative potential

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Bioaccumulation: Bioaccumulative

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Bioaccumulation: Bioaccumulative

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Bioaccumulation: Bioaccumulative

Mobility in soil

N.A.

Other adverse effects

None

LVT500/2 Page n. 9 of 12



LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

UN number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

N.A.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \ll 10 μ m] is listed in TSCA Section 8b

ammonia ...% is listed in TSCA Section 8b

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR

2-methyl-2H-isothiazol-3-one is listed in TSCA Section 12b, Section 8b

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: ammonia ...%.

Section 313 – Toxic chemical list: ammonia ...%.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA: ammonia ...% - Reportable quantity: 1000 pounds. Reportable quantity for mixture: 6802721.088 pounds.

CAA - Clean Air Act

CAA listed substances:

None.

CWA - Clean Water Act

CWA listed substances:

LVT500/2 Page n. 10 of 12



.

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

ammonia ...% is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 $\mu m]$

ammonia ...%.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter \ll 10 μ m]

ammonia ...%.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 μ m] ammonia ...%.

Volatile Organic compounds - VOCs = 3.66% Volatile Organic compounds - VOCs = 49.55 g/l Volatile CMR substances = 0.00% Organic Carbon - C = 0.02

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

H226 Flammable liquid and vapour.

H361 Suspected of damaging fertility or the unborn child.

H413 May cause long lasting harmful effects to aquatic life.

H330 Fatal if inhaled.

H311 Toxic in contact with skin.

H301 Toxic if swallowed.

H410 Very toxic to aquatic life with long lasting effects.

H319 Causes serious eye irritation.

Safety Data Sheet dated 11/28/2022, version 2 Sections modified from the previous revision:

- 2. HAZARD(S) IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION

LVT500/2

Page n. 11 of 12



.

LVT500 IDROPRIMER 500 - Fondo bianco1k interni - White 1k primer

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.
GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average