

## Safety Data Sheet



# LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

Safety Data Sheet dated 7/3/2023, version 2

## 1. Identification

GHS Product identifier

Mixture identification:

Trade name: PASTA OPACANTE Universale solvente - Universal Matting paste SB

Other means of identification

Trade code: LXA016

Recommended use and restrictions on use

Recommended use:

IS- Industrial use

PW - Professional use

Paint additive

Supplier's details

Company:

SIVAM Coatings S.p.A - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02 903041

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

SIVAM Coatings S.p.A - Tel. +39 02- 903041

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

## 2. Hazard identification

Classification of the hazardous product

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

GHS label elements, including precautionary statements

Hazard pictograms:



Danger

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

#### Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash ... Thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water/...
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/ doctor/if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see ... On this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use ... to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

#### Special provisions

None

#### Other hazards

None

#### Ingredient(s) with unknown acute toxicity

None.

---

### 3. Composition/Information on ingredients

#### Substances

N.A.

#### Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

Qty	Name	Ident. Number	Classification
>= 15% - < 40%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> <li>⚠ B.6/3 Flam. Liq. 3 H226</li> <li>⚠ CAN-HAE/C3 Aquatic Chronic 3 H412</li> <li>⚠ A.1/4/Dermal Acute Tox. 4 H312</li> <li>⚠ A.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ A.2/2 Skin Irrit. 2 H315</li> <li>⚠ A.8/3 STOT SE 3 H335</li> <li>⚠ A.9/2 STOT RE 2 H373</li> <li>⚠ A.10/1 Asp. Tox. 1 H304</li> </ul>
>= 10% - < 30%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	<ul style="list-style-type: none"> <li>⚠ B.6/2 Flam. Liq. 2 H225</li> <li>⚠ A.8/3 STOT SE 3 H336</li> </ul>
>= 1% - < 5%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	<ul style="list-style-type: none"> <li>⚠ B.6/2 Flam. Liq. 2 H225</li> <li>⚠ A.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ A.9/2 STOT RE 2 H373</li> <li>⚠ A.10/1 Asp. Tox. 1 H304</li> <li>⚠ CAN-HAE/C3 Aquatic Chronic 3 H412</li> </ul>
>= 1% - < 5%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	<ul style="list-style-type: none"> <li>⚠ B.6/3 Flam. Liq. 3 H226</li> <li>⚠ A.8/3 STOT SE 3 H336</li> </ul>
>= 0.5% - < 1.5%	Hydrocarbons, C9, aromatics (CAS 64742-95-6)	EC: 918-668-5 REACH No.: 01-2119455851-35	<ul style="list-style-type: none"> <li>⚠ B.6/3 Flam. Liq. 3 H226</li> <li>⚠ A.10/1 Asp. Tox. 1 H304</li> <li>⚠ CAN-HAE/C2 Aquatic Chronic 2 H411</li> <li>⚠ A.8/3 STOT SE 3 H335</li> <li>⚠ A.8/3 STOT SE 3 H336</li> </ul>
>= 0.1% - < 1%	Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z)	CAS: 147900-93-4 EC: 604-612-4 REACH No.: 01-2119971821-33	<ul style="list-style-type: none"> <li>⚠ A.1/4/Oral Acute Tox. 4 H302</li> <li>⚠ CAN-HAE/C2 Aquatic Chronic 2 H411</li> <li>⚠ A.2/2 Skin Irrit. 2 H315</li> <li>⚠ A.4.2/1A Skin Sens. 1A H317</li> <li>⚠ A.9/2 STOT RE 2 H373</li> </ul>
>= 0.1% - < 1%	Fatty acids, tall-oil, compds. with oleylamine	CAS: 85711-55-3 EC: 288-315-1 REACH No.: 01-2119974148-28	<ul style="list-style-type: none"> <li>⚠ A.2/2 Skin Irrit. 2 H315</li> <li>⚠ A.3/1 Eye Dam. 1 H318</li> <li>⚠ A.4.2/1A Skin Sens. 1A H317</li> <li>⚠ A.9/2 STOT RE 2 H373</li> </ul>

The actual concentration of the components listed above is withheld as a trade secret.

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

The actual concentration of the components listed above is withheld as a trade secret.

---

#### 4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

#### 5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

#### 7. Handling and storage

##### Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Do not use on extensive surface areas in premises where there are occupants.
- Use localized ventilation system.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- See also section 8 for recommended protective equipment.
- Advice on general occupational hygiene:
  - Contaminated clothing should be changed before entering eating areas.
  - Do not eat or drink while working.

##### Conditions for safe storage, including any incompatibilities

- Always keep in a well ventilated place.
- Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
- Avoid accumulating electrostatic charge.
- Keep away from food, drink and feed.
- Incompatible materials:
  - None in particular.
- Instructions as regards storage premises:
  - Cool and adequately ventilated.
  - Safety electric system.
- Storage temperature:
  - Store at ambient temperature.

#### 8. Exposure controls/personal protection

##### Control parameters

- xylylene [4] - CAS: 1330-20-7
  - EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
  - ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair
- isobutyl acetate [2] - CAS: 110-19-0
  - ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
  - EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm
- ethylbenzene - CAS: 100-41-4
  - EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin
  - ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
  - EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin
  - TLV TWA - 275 mg/m<sup>3</sup> - 50 ppm
  - TLV STEL - 550 mg/m<sup>3</sup> - 100 ppm
- Hydrocarbons, C9, aromatics (CAS 64742-95-6)
  - ACGIH - TWA: 100 mg/m<sup>3</sup>, 19 ppm - Notes: total hydrocarbons

##### DNEL Exposure Limit Values

- xylylene [4] - CAS: 1330-20-7
  - Worker Industry: 289 mg/m<sup>3</sup> - Worker Professional: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup>
  - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
  - Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup>
  - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg
  - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- isobutyl acetate [2] - CAS: 110-19-0
  - Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup>

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

- Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 600 mg/m<sup>3</sup> - Worker Professional: 600 mg/m<sup>3</sup> - Consumer: 300 mg/m<sup>3</sup>
- Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg
- Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Consumer: 5 mg/kg
- Exposure: Human Oral - Frequency: Long Term, systemic effects
- ethylbenzene - CAS: 100-41-4  
Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 15 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
Worker Industry: 796 mg/kg - Worker Professional: 796 mg/kg - Consumer: 320 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Worker Industry: 275 mg/m<sup>3</sup> - Worker Professional: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 550 mg/m<sup>3</sup> - Worker Professional: 550 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects  
Consumer: 36 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- Hydrocarbons, C9, aromatics (CAS 64742-95-6)  
Worker Industry: 150 mg/m<sup>3</sup> - Worker Professional: 150 mg/m<sup>3</sup> - Consumer: 32 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
Worker Industry: 25 mg/kg - Worker Professional: 25 mg/kg - Consumer: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
Consumer: 11 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4  
Worker Industry: 0.024 mg/kg - Worker Professional: 0.024 mg/kg - Consumer: 0.012 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
- PNEC Exposure Limit Values**
- xylylene [4] - CAS: 1330-20-7  
Target: Fresh Water - Value: 0.327 mg/l  
Target: Marine water - Value: 0.327 mg/l  
Target: Intermittent emission - Value: 0.327 mg/l  
Target: Freshwater sediments - Value: 12.46 mg/kg  
Target: Marine water sediments - Value: 12.46 mg/kg  
Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  
Target: Soil (agricultural) - Value: 2.31 mg/kg
- isobutyl acetate [2] - CAS: 110-19-0  
Target: Fresh Water - Value: 0.17 mg/l  
Target: Marine water - Value: 0.017 mg/l  
Target: Intermittent emission - Value: 0.34 mg/l  
Target: Microorganisms in sewage treatments - Value: 200 mg/l  
Target: Freshwater sediments - Value: 0.877 mg/kg  
Target: Marine water sediments - Value: 0.0877 mg/kg  
Target: Soil (agricultural) - Value: 0.0755 mg/kg
- ethylbenzene - CAS: 100-41-4  
Target: Fresh Water - Value: 0.1 mg/l  
Target: Marine water - Value: 0.01 mg/l  
Target: Freshwater sediments - Value: 13.7 mg/kg  
Target: Marine water sediments - Value: 1.37 mg/kg  
Target: Intermittent emission - Value: 0.1 mg/l  
Target: Microorganisms in sewage treatments - Value: 9.6 mg/l  
Target: Soil (agricultural) - Value: 2.68 mg/kg
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
Target: Fresh Water - Value: 0.635 mg/l

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

Target: Marine water - Value: 0.0635 mg/l  
 Target: Intermittent emission - Value: 6.35 mg/l  
 Target: Microorganisms in sewage treatments - Value: 100 mg/l  
 Target: Freshwater sediments - Value: 3.29 mg/kg  
 Target: Marine water sediments - Value: 0.329 mg/kg  
 Target: Soil (agricultural) - Value: 0.29 mg/kg  
 Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4  
 Target: Fresh Water - Value: 0.006 mg/l  
 Target: Marine water - Value: 0.0006 mg/l  
 Target: Freshwater sediments - Value: 2.46 mg/kg  
 Target: Marine water sediments - Value: 0.25 mg/kg  
 Target: Soil (agricultural) - Value: 0.28 mg/kg  
 Biological Exposure Index  
 xylene [4] - CAS: 1330-20-7  
 Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine -  
 Sampling Period: End of turn  
 ethylbenzene - CAS: 100-41-4  
 Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and  
 acid fenilgliossalico - Sampling Period: End of turn; End of working week  
 Appropriate engineering controls  
 None  
 Individual protection measures, such as personal protective equipment (PPE)  
 Eye protection:  
 Eye glasses with side protection. (EN166)  
 Protection for skin:  
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or  
 viton.  
 Protection for hands:  
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.  
 (EN374)  
 Respiratory protection:  
 Use respiratory protection where ventilation is insufficient or exposure is prolonged.  
 Use adequate protective respiratory equipment.  
 Thermal Hazards:  
 None

#### 9. Physical and chemical properties

Appearance and colour:	Liquid, White
Odour:	typical
Odour threshold:	N.D.
pH:	Not Relevant
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Flash point:	< 23 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	10.5% - 1.3% Vol. (isobutyl acetate)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	0.980 - 1.000
Solubility in water:	partial
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.



## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

---

#### 10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

---

#### 11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

PASTA OPACANTE Universale solvente - Universal Matting paste SB

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

d) respiratory or skin sensitisation

The product is classified: Skin Sens. 1A H317

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

h) STOT-single exposure

The product is classified: STOT SE 3 H335; STOT SE 3 H336

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 6.7 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 1100 mg/kg

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401

Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403



## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

- Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402  
ethylbenzene - CAS: 100-41-4
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg  
Test: LD50 - Route: Inhalation - Species: Rat = 17.2 mg/l - Duration: 1h
- i) STOT-repeated exposure:  
Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat > 23.5 mg/l - Duration: 4h
- Hydrocarbons, C9, aromatics (CAS 64742-95-6)
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 3492 mg/kg - Source: OCSE 401  
Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m<sup>3</sup> - Duration: 4h - Source: OCSE 403  
Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg - Source: OCSE 402
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 1570 mg/kg
- Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3
- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: OECD 423
- xylene [4] - CAS: 1330-20-7  
Observations on human subjects.  
Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3  
ethylbenzene - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

## 12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

PASTA OPACANTE Universale solvente - Universal Matting paste SB

The product is classified: Aquatic Chronic 3 - H412

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

isobutyl acetate [2] - CAS: 110-19-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 370 mg/l - Duration h: 72 - Notes: OCSE 201

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

- Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202  
 Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203
- b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)
- ethylbenzene - CAS: 100-41-4
- a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96  
 Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96
- b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day  
 Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96 - Notes: OECD 201  
 Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: OECD 203  
 Endpoint: LC50 - Species: Daphnia = 408 mg/l - Duration h: 48
- b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Fish = 47.5 mg/l - Notes: 14d OECD 204  
 Endpoint: NOEC - Species: Daphnia > 100 mg/l - Notes: 21d OECD 211
- Hydrocarbons, C9, aromatics (CAS 64742-95-6)
- a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Daphnia = 3.2 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae = 2.6 mg/l - Duration h: 72  
 Endpoint: LC50 - Species: Fish = 9.2 mg/l - Duration h: 96
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
- a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Algae = 7.89 mg/l - Duration h: 72 - Notes: OECD 201
- Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3
- a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Daphnia = 15.2 mg/l - Duration h: 48 - Notes: OECD TG 202  
 Endpoint: EC50 - Species: Algae = 7.43 mg/l - Duration h: 72 - Notes: OECD TG 201  
 Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: OECD 203
- Persistence and degradability
- xylene [4] - CAS: 1330-20-7  
 Biodegradability: Readily biodegradable
- isobutyl acetate [2] - CAS: 110-19-0  
 Biodegradability: Readily biodegradable
- ethylbenzene - CAS: 100-41-4  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83 - Notes: OECD 301F
- Hydrocarbons, C9, aromatics (CAS 64742-95-6)  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 78
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4  
 Biodegradability: Non-readily biodegradable
- Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3  
 Biodegradability: Readily biodegradable
- Bioaccumulative potential  
 N.A.
- Mobility in soil  
 N.A.
- Other adverse effects  
 None

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

#### 13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

#### 14. Transport information



##### UN number

TDG number: UN1263  
 ADR-UN Number: 1263  
 DOT number: UN1263  
 IATA-UN Number: 1263  
 IMDG-UN Number: 1263

##### UN proper shipping name

TDG-Shipping Name: PAINT RELATED MATERIAL  
 ADR-Shipping Name: PAINT RELATED MATERIAL  
 DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound  
 IATA-Shipping Name: PAINT RELATED MATERIAL  
 IMDG-Shipping Name: PAINT RELATED MATERIAL

##### Transport hazard class(es)

TDG Class: 3  
 ADR-Class: 3  
 DOT Hazard Class: 3  
 ADR - Hazard identification number: 33  
 IATA-Class: 3  
 IATA-Label: 3  
 IMDG-Class: 3

##### Packing group

TDG Packing group: II  
 ADR-Packing Group: II  
 DOT Packing group: II  
 IATA-Packing group: II  
 IMDG-Packing group: II

##### Environmental hazards

ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No

##### Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

##### Special precautions in connection with transport or conveyance

Rail (RID): 3  
 TDG Special provisions: 59, 142  
 DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28  
 ADR-Subsidiary hazards: -  
 ADR-S.P.: 163 367 640D 650  
 ADR-Transport category (Tunnel restriction code): 2 (D/E)  
 IATA-Passenger Aircraft: 353  
 IATA-Subsidiary hazards: -  
 IATA-Cargo Aircraft: 364  
 IATA-S.P.: A3 A72 A192

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

#### 15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

xylene [4] is listed in NPRI Part 5

ethylbenzene is listed in NPRI Part 1, Group A

2-methoxy-1-methylethyl acetate is listed in NPRI Part 5

Hydrocarbons, C9, aromatics (CAS 64742-95-6) is listed in NPRI Part 5.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

xylene [4] is listed in TSCA Section 8b

isobutyl acetate [2] is listed in TSCA Section 8b

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Hydrocarbons, C9, aromatics (CAS 64742-95-6) is listed in TSCA Section 8b, Section 8d HSDR

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) is listed in TSCA Section 8b

Fatty acids, tall-oil, compds. with oleylamine is listed in TSCA Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], isobutyl acetate [2], ethylbenzene.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

ethylbenzene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 254.1296061 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

isobutyl acetate [2] is listed in CWA Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

ethylbenzene - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

xylene [4]

isobutyl acetate [2]

ethylbenzene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

xylene [4]

isobutyl acetate [2]

ethylbenzene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

xylene [4]

isobutyl acetate [2]

ethylbenzene.

Volatile Organic compounds - VOCs = 71.02 %

Volatile Organic compounds - VOCs = 710.15 g/l

Volatile CMR substances = 0.01 %

Organic Carbon - C = 0.56

---

#### 16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Safety Data Sheet dated 7/3/2023, version 2

Sections modified from the previous revision:

2. Hazard identification
3. Composition/Information on ingredients
7. Handling and storage
8. Exposure controls/personal protection
9. Physical and chemical properties
11. Toxicological information
12. Ecological information
14. Transport information
15. Regulatory information

Disclaimer:

LXA016/2

Page n. 13 of 14

## Safety Data Sheet

### LXA016 PASTA OPACANTE Universale solvente - Universal Matting paste SB

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average