



Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Safety Data Sheet dated 9/13/2018, version 2

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: HIPOLPRIMER per legni scuri -Isolator for dark wood

Other means of identification:

Trade code: LDA001

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel: +1-860-529-7704

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel: +1-860-529-7704

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- ⚠ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... Thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor/... if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see ... On this label).
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	B

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

LDA001/2

Page n. 2 of 10

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	butanone; ethyl methyl ketone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH No.: 01-2119457290-43	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.3/2A Eye Irrit. 2A H319</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>
>= 30% - < 40%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.10/1 Asp. Tox. 1 H304</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.7/2 Unst. Expl.</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div>
>= 3% - < 5%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>A.1/4/Dermal Acute Tox. 4 H312</div> </div> <div> <div></div> <div>A.1/4/Inhal Acute Tox. 4 H332</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.3/2A Eye Irrit. 2A H319</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H335</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div> <div> <div></div> <div>A.10/1 Asp. Tox. 1 H304</div> </div>
>= 3% - < 5%	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis[oxirane]	CAS: 25036-25-3	<div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.4.2/1 Skin Sens. 1 H317</div> </div> <div> <div></div> <div>A.3/2A Eye Irrit. 2A H319</div> </div>

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Remove persons to safety.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.
Methods and materials for containment and cleaning up
Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not use on extensive surface areas in premises where there are occupants.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Conditions for safe storage, including any incompatibilities
Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Avoid accumulating electrostatic charge.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters
butanone; ethyl methyl ketone - CAS: 78-93-3
EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm
ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair
toluene - CAS: 108-88-3
EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss
xylene [4] - CAS: 1330-20-7
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
DNEL Exposure Limit Values
butanone; ethyl methyl ketone - CAS: 78-93-3
Worker Industry: 1161 mg/kg - Worker Professional: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human
Dermal - Frequency: Long Term, systemic effects
Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 106 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, systemic effects
Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
toluene - CAS: 108-88-3
Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal
- Frequency: Long Term, systemic effects
Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, systemic effects
Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
xylene [4] - CAS: 1330-20-7
Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human
Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, systemic effects

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal
- Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3

Target: Fresh Water - Value: 55.8 mg/l

Target: Intermittent emission - Value: 55.8 mg/l

Target: Microorganisms in sewage treatments - Value: 709 mg/l

Target: Freshwater sediments - Value: 284.7 mg/kg

Target: Marine water sediments - Value: 284.7 mg/kg

Target: Soil (agricultural) - Value: 22.5 mg/kg

Target: Food chain - Value: 1000 mg/kg

toluene - CAS: 108-88-3

Target: Fresh Water - Value: 0.68 mg/l

Target: Marine water - Value: 0.68 mg/l

Target: Intermittent emission - Value: 0.68 mg/l

Target: Freshwater sediments - Value: 16.39 mg/kg

Target: Marine water sediments - Value: 16.39 mg/kg

Target: Microorganisms in sewage treatments - Value: 13.61 mg/l

Target: Soil (agricultural) - Value: 2.89 mg/kg

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Intermittent emission - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

Biological Exposure Index

xylene [4] - CAS: 1330-20-7

Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	colourless fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 79 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	11.5% - 1.8% Vol. (Butanone)
Vapour density:	> 1
Flash point:	< 0 °C
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	0.870 - 0.890
Solubility in water:	partial
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

LDA001/2

Page n. 5 of 10

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

10. STABILITY AND REACTIVITY

- Reactivity
It may generate dangerous reactions (See subsections below)
- Chemical stability
It may generate dangerous reactions (See subsections below)
- Possibility of hazardous reactions
It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides and powerful reducing agents.
It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.
- Conditions to avoid
Avoid accumulating electrostatic charge.
- Incompatible materials
Avoid contact with combustible materials. The product could catch fire.
- Hazardous decomposition products
None.

11. TOXICOLOGICAL INFORMATION

- Information on toxicological effects
Toxicological information of the product:
HIPOLPRIMER per legni scuri -Isolator for dark wood
- a) acute toxicity
Not classified
No data available for the product
 - b) skin corrosion/irritation
The product is classified: Skin Irrit. 2 H315
 - c) serious eye damage/irritation
The product is classified: Eye Irrit. 2A H319
 - d) respiratory or skin sensitisation
The product is classified: Skin Sens. 1 H317
 - e) germ cell mutagenicity
Not classified
No data available for the product
 - f) carcinogenicity
Not classified
No data available for the product
 - g) reproductive toxicity
The product is classified: Repr. 2 H361
 - h) STOT-single exposure
The product is classified: STOT SE 3 H336
 - i) STOT-repeated exposure
The product is classified: STOT RE 2 H373
 - j) aspiration hazard
The product is classified: Asp. Tox. 1 H304
- Toxicological information of the main substances found in the product:
- butanone; ethyl methyl ketone - CAS: 78-93-3
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 3460 mg/kg - Source: OECD 423
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402
Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h
- toluene - CAS: 108-88-3
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403
 - b) skin corrosion/irritation:
Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h
- xylene [4] - CAS: 1330-20-7
- a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
- butanone; ethyl methyl ketone - CAS: 78-93-3
- High exposure can cause
drowsiness, migraine, narcosis and dizziness.
The extended contact and/or repeated with skin can cause dermatitis.
Environmental concentrations more than 200 ppm result irritating for eyes and respiratory tract.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

toluene - CAS: 108-88-3

Effects following acute exposure:

At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.

At 400 ppm: worsening of symptoms and mental confusion.

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

toluene - Group 3

xylene [4] - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

HIPOLPRIMER per legni scuri -Isolator for dark wood

Not classified for environmental hazards

No data available for the product

butanone; ethyl methyl ketone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 308 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2029 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

Persistence and degradability

butanone; ethyl methyl ketone - CAS: 78-93-3

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 98 - Notes: OECD 301D

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

14. TRANSPORT INFORMATION



UN number	
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263
UN proper shipping name	
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name:	Paint
IATA-Shipping Name:	PAINT
IATA-Technical name:	Paint
IMDG-Shipping Name:	PAINT
IMDG-Shipping name:	Paint
Transport hazard class(es)	
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
IMDG-Class:	3
Packing group	
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	N.A.
Special precautions	
Rail (RID):	3
DOT Special provisions:	149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

butanone; ethyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

xylene [4] is listed in TSCA Section 8b

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with

2,2'-[1-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Section 304 – Hazardous substances: butanone; ethyl methyl ketone, toluene, xylene [4].

Section 313 – Toxic chemical list: toluene, xylene [4].

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: butanone; ethyl methyl ketone - Reportable quantity: 5000 pounds

toluene - Reportable quantity: 1000 pounds

xylene [4] - Reportable quantity: 100 pounds.

Reportable quantity for mixture: 2857.142857 pounds.

CAA - Clean Air Act

CAA listed substances:

butanone; ethyl methyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

xylene [4] is listed in CWA Section 304, Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

butanone; ethyl methyl ketone

toluene

xylene [4].

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

butanone; ethyl methyl ketone

toluene

xylene [4].

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

butanone; ethyl methyl ketone

toluene

xylene [4].

Volatile Organic compounds - VOCs = 84.40 %

Volatile Organic compounds - VOCs = 751.20 g/l

Volatile CMR substances = 0.00 %

Organic Carbon - C = 0.66

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

Safety Data Sheet dated 9/13/2018, version 2

Sections modified from the previous revision:

3. COMPOSITION/INFORMATION ON INGREDIENTS

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

15. REGULATORY INFORMATION

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average