

Safety Data Sheet



LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Safety Data Sheet dated 9/13/2018, version 2

1. Identification

GHS Product identifier
Mixture identification:
Trade name: HIPOLPRIMER per legni scuri -Isolator for dark wood
Other means of identification
Trade code: LDA001

Recommended use and restrictions on use
Recommended use:
Industrial and professional uses (SU3 - SU22)
Varnish for wood

Supplier's details
Company:
NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1
Importer:
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-514-832-4010
Emergency phone number for Canada: Canutec (613) 996-6666
Distributor:
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.
7900 Henri-Bourassa Blvd. W.
Montreal, Quebec, Canada, H4S 1V4
Tel :+1-514-832-4010
Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:
msds@sivam.it

Emergency phone number
NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)
Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- ⚠ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

GHS label elements, including precautionary statements
Hazard pictograms:



Danger

Hazard statements:
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... Thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P302+P352 IF ON SKIN: Wash with plenty of water/...
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/ doctor/ if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see ... On this label).
P331 Do NOT induce vomiting.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	butanone; ethyl methyl ketone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH No.: 01-2119457290-43	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>
>= 30% - < 40%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.10/1 Asp. Tox. 1 H304</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.7/2 Unst. Expl.</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div>
>= 3% - < 5%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>A.1/4/Dermal Acute Tox. 4 H312</div> </div> <div> <div></div> <div>A.1/4/Inhal Acute Tox. 4 H332</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H335</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div> <div> <div></div> <div>A.10/1 Asp. Tox. 1 H304</div> </div>
>= 3% - < 5%	Phenol, 4,4'-(1-methylethylidene)bis-,	CAS: 25036-25-3	<div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div>

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

	polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]		A.4.2/1 Skin Sens. 1 H317
--	--	--	---------------------------

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an

ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

See also section 8 for recommended protective equipment.
 Conditions for safe storage, including any incompatibilities
 Always keep in a well ventilated place.
 Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Safety electric system.
 Storage temperature:
 Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

butanone; ethyl methyl ketone - CAS: 78-93-3
 EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm
 ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair
 toluene - CAS: 108-88-3
 EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss
 xylene [4] - CAS: 1330-20-7
 EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

DNEL Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3
 Worker Industry: 1161 mg/kg - Worker Professional: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human
 Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 106 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
 Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 toluene - CAS: 108-88-3
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal
 - Frequency: Long Term, systemic effects
 Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 xylene [4] - CAS: 1330-20-7
 Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human
 Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal
 - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

butanone; ethyl methyl ketone - CAS: 78-93-3
 Target: Fresh Water - Value: 55.8 mg/l
 Target: Intermittent emission - Value: 55.8 mg/l
 Target: Microorganisms in sewage treatments - Value: 709 mg/l
 Target: Freshwater sediments - Value: 284.7 mg/kg
 Target: Marine water sediments - Value: 284.7 mg/kg
 Target: Soil (agricultural) - Value: 22.5 mg/kg
 Target: Food chain - Value: 1000 mg/kg
 toluene - CAS: 108-88-3
 Target: Fresh Water - Value: 0.68 mg/l
 Target: Marine water - Value: 0.68 mg/l
 Target: Intermittent emission - Value: 0.68 mg/l
 Target: Freshwater sediments - Value: 16.39 mg/kg
 Target: Marine water sediments - Value: 16.39 mg/kg
 Target: Microorganisms in sewage treatments - Value: 13.61 mg/l
 Target: Soil (agricultural) - Value: 2.89 mg/kg
 xylene [4] - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.327 mg/l
 Target: Marine water - Value: 0.327 mg/l
 Target: Intermittent emission - Value: 0.327 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg
 Target: Marine water sediments - Value: 12.46 mg/kg

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

Biological Exposure Index

xylene [4] - CAS: 1330-20-7

Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour:	colourless fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 79 °C
Flash point:	< 0 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	11.5% - 1.8% Vol. (Butanone)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	0.870 - 0.890
Solubility in water:	partial
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

HIPOLPRIMER per legni scuri -Isolator for dark wood

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

d) respiratory or skin sensitisation
The product is classified: Skin Sens. 1 H317

e) germ cell mutagenicity
Not classified
No data available for the product

f) carcinogenicity
Not classified
No data available for the product

g) reproductive toxicity
The product is classified: Repr. 2 H361

h) STOT-single exposure
The product is classified: STOT SE 3 H336

i) STOT-repeated exposure
The product is classified: STOT RE 2 H373

j) aspiration hazard
The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

butanone; ethyl methyl ketone - CAS: 78-93-3

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 3460 mg/kg - Source: OECD 423
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402
Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h

toluene - CAS: 108-88-3

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403

b) skin corrosion/irritation:
Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

xylene [4] - CAS: 1330-20-7

a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

butanone; ethyl methyl ketone - CAS: 78-93-3

High exposure can cause
drowsiness, migraine, narcosis and dizziness.
The extended contact and/or repeated with skin can cause dermatitis.
Environmental concentrations more than 200 ppm result irritating for eyes and respiratory tract.

toluene - CAS: 108-88-3

Effects following acute exposure:
At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.
At 400 ppm: worsening of symptoms and mental confusion.

xylene [4] - CAS: 1330-20-7

Observations on human subjects.
Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

Substance(s) listed on the NTP report on Carcinogens:
None.

Substance(s) listed on the IARC Monographs:
toluene - Group 3
xylene [4] - Group 3.

Substance(s) listed as OSHA Carcinogen(s):
None.

Substance(s) listed as NIOSH Carcinogen(s):
None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

HIPOLPRIMER per legni scuri -Isolator for dark wood

Not classified for environmental hazards

No data available for the product

butanone; ethyl methyl ketone - CAS: 78-93-3

a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Daphnia = 308 mg/l - Duration h: 48

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

Endpoint: EC50 - Species: Algae = 2029 mg/l - Duration h: 96
 Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3
 Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48
 Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72
 Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d
 Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72
 Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d
 Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

Persistence and degradability

butanone; ethyl methyl ketone - CAS: 78-93-3
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 98 - Notes: OECD 301D

toluene - CAS: 108-88-3
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

xylene [4] - CAS: 1330-20-7
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

Bioaccumulative potential
 N.A.

Mobility in soil
 N.A.

Other adverse effects
 None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information



UN number

TDG number:	UN1263
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263

UN proper shipping name

TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name:	Paint
IATA-Shipping Name:	PAINT
IATA-Technical name:	Paint
IMDG-Shipping Name:	PAINT
IMDG-Shipping name:	Paint

Transport hazard class(es)

TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

IATA-Label:	3
IMDG-Class:	3
Packing group	
TDG Packing group:	II
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
N.A.	
Special precautions in connection with transport or conveyance	
Rail (RID):	3
TDG Special provisions:	59,142
DOT Special provisions:	149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. Regulatory information

Safety, health and environmental regulations specific for the product in question
 This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory
 Substance(s) listed under NPRI:
 None.

DSL inventory - Domestic substances list
 no substances listed

NDSL inventory - Not Domestic substances list
 no substances listed

TSCA inventory
 All the components are listed on the TSCA inventory.

TSCA listed substances:
 butanone; ethyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR
 toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR
 xylene [4] is listed in TSCA Section 8b
 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with
 2,2'-[1-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] is listed in TSCA Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act
 Section 302 – Extremely Hazardous Substances: no substances listed.
 Section 304 – Hazardous substances: butanone; ethyl methyl ketone, toluene, xylene [4].
 Section 313 – Toxic chemical list: toluene, xylene [4].

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 Substance(s) listed under CERCLA: butanone; ethyl methyl ketone - Reportable quantity: 5000 pounds
 toluene - Reportable quantity: 1000 pounds
 xylene [4] - Reportable quantity: 100 pounds.
 Reportable quantity for mixture: 2857.142857 pounds.

CAA - Clean Air Act
 CAA listed substances:
 butanone; ethyl methyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
 toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
 xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act
 CWA listed substances:
 toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants
 xylene [4] is listed in CWA Section 304, Section 311.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:
toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:
butanone; ethyl methyl ketone
toluene
xylene [4].

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:
butanone; ethyl methyl ketone
toluene
xylene [4].

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:
butanone; ethyl methyl ketone
toluene
xylene [4].

Volatile Organic compounds - VOCs = 84.40 %

Volatile Organic compounds - VOCs = 751.20 g/l

Volatile CMR substances = 0.00 %

Organic Carbon - C = 0.66

16. Other information

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H317 May cause an allergic skin reaction.

Safety Data Sheet dated 9/13/2018, version 2

Sections modified from the previous revision:

3. Composition/Information on ingredients

8. Exposure controls/personal protection

9. Physical and chemical properties

10. Stability and reactivity

11. Toxicological information

12. Ecological information

15. Regulatory information

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.

Safety Data Sheet

LDA001 HIPOLPRIMER per legni scuri -Isolator for dark wood

KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average