

## Safety Data Sheet



### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Safety Data Sheet dated 9/16/2022, version 2

#### 1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Other means of identification:

Trade code: LGE040

Recommended use of the chemical and restrictions on use

Recommended use:

IS- Industrial use

PW - Professional use

Varnish for wood

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

SIVAM Coatings S.p.A - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02 903041

Importer:

Richelieu America Ltd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Distributor:

Richelieu America Ltd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number:

SIVAM Coatings S.p.A - Tel. +39 02- 903041

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

#### 2. HAZARD(S) IDENTIFICATION

Classification of the chemical

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor/... if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P321 Specific treatment (see ... On this label).  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO2, water spray. Do not use water jet.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	/	2
FLAMMABILITY		3
PHYSICAL HAZARD		1
PERSONAL PROTECTION		G

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

LGE040/2

Page n. 2 of 16

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

N.A.






Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number	Classification
>= 40% - < 50%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	<div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>
>= 5% - < 7%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	<div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>
>= 3% - < 5%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>
>= 3% - < 5%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<div> <div></div> <div>B.6/3 Flam. Liq. 3 H226</div> </div> <div> <div></div> <div>US-HAE/C3 Aquatic Chronic 3 H412</div> </div> <div> <div></div> <div>A.1/4/Dermal Acute Tox. 4 H312</div> </div> <div> <div></div> <div>A.1/4/Inhal Acute Tox. 4 H332</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.3/2A Eye Irrit. 2A H319</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H335</div> </div> <div> <div></div> <div>A.9/2 STOT RE 2 H373</div> </div> <div> <div></div> <div>A.10/1 Asp. Tox. 1 H304</div> </div>
>= 1% - < 2.5%	butanone; ethyl methyl ketone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH No.: 01-2119457290-43	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.3/2A Eye Irrit. 2A H319</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H336</div> </div>
>= 0.5% - < 1%	methyl methacrylate; methyl 2-methylprop-2-enoate	Index number: 607-035-00-6 CAS: 80-62-6 EC: 201-297-1 REACH No.: 01-2119452498-28	<div> <div></div> <div>B.6/2 Flam. Liq. 2 H225</div> </div> <div> <div></div> <div>A.8/3 STOT SE 3 H335</div> </div> <div> <div></div> <div>A.2/2 Skin Irrit. 2 H315</div> </div> <div> <div></div> <div>A.4.2/1 Skin Sens. 1 H317</div> </div>

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

>= 0.1% - < 0.25%	2-hydroxyethyl methacrylate	Index number: CAS: EC: REACH No.:	607-124-00-X 868-77-9 212-782-2 01-2119490169-29	 A.3/2A Eye Irrit. 2A H319  A.2/2 Skin Irrit. 2 H315  A.4.2/1 Skin Sens. 1 H317
14 ppm	octamethylcyclotetrasiloxane (D4)	Index number: CAS: EC: REACH No.:	014-018-00-1 556-67-2 209-136-7 01-2119529238-36	 B.6/3 Flam. Liq. 3 H226  A.7/2 Repr. 2 H361 US-HAE/C4 Aquatic Chronic 4 H413
10 ppm	Decamethylcyclopentasiloxane (D5)	CAS: EC: REACH No.:	541-02-6 208-764-9 01-2119511367-43	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### 4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO<sub>2</sub>, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

---

#### 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

---

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

EU - TWA(8h): 275 mg/m<sup>3</sup>, 50 ppm - STEL: 550 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

TLV TWA - 275 mg/m<sup>3</sup> - 50 ppm

TLV STEL - 550 mg/m<sup>3</sup> - 100 ppm

isobutyl acetate [2] - CAS: 110-19-0

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m<sup>3</sup>, 50 ppm - STEL: 723 mg/m<sup>3</sup>, 150 ppm

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

butanone; ethyl methyl ketone - CAS: 78-93-3

EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 EU - TWA(8h): 50 ppm - STEL: 100 ppm  
 ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: DSEN, A4 - URT and eye irr, body weight eff, pulm edema

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 ACGIH - TWA(8h): 123 mg/m<sup>3</sup>, 10 ppm

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6  
 ACGIH - TWA(8h): 10 ppm

**DNEL Exposure Limit Values**

n-butyl acetate - CAS: 123-86-4  
 Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Long Term, local effects  
 Worker Industry: 11 mg/kg - Worker Professional: 11 mg/kg - Consumer: 6 mg/kg -  
 Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 Worker Industry: 796 mg/kg - Worker Professional: 796 mg/kg - Consumer: 320 mg/kg -  
 Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 275 mg/m<sup>3</sup> - Worker Professional: 275 mg/m<sup>3</sup> - Consumer: 33 mg/m<sup>3</sup> -  
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 550 mg/m<sup>3</sup> - Worker Professional: 550 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, local effects  
 Consumer: 36 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

isobutyl acetate [2] - CAS: 110-19-0  
 Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 600 mg/m<sup>3</sup> - Worker Professional: 600 mg/m<sup>3</sup> - Consumer: 300 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg -  
 Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7  
 Worker Industry: 289 mg/m<sup>3</sup> - Worker Professional: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> -  
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg -  
 Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

butanone; ethyl methyl ketone - CAS: 78-93-3  
 Worker Industry: 1161 mg/kg - Worker Professional: 1161 mg/kg - Consumer: 412 mg/kg  
 - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 600 mg/m<sup>3</sup> - Worker Professional: 600 mg/m<sup>3</sup> - Consumer: 106 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 Worker Industry: 13.67 mg/kg - Worker Professional: 13.67 mg/kg - Consumer: 8.2 mg/kg  
 - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 208 mg/m<sup>3</sup> - Worker Professional: 208 mg/m<sup>3</sup> - Consumer: 74.3 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

2-hydroxyethyl methacrylate - CAS: 868-77-9  
 Worker Industry: 1.3 mg/kg - Worker Professional: 1.3 mg/kg - Consumer: 0.83 -

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 4.9 mg/m<sup>3</sup> - Worker Professional: 4.9 mg/m<sup>3</sup> - Consumer: 2.9 -  
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Worker Industry: 73 mg/m<sup>3</sup> - Worker Professional: 73 mg/m<sup>3</sup> - Consumer: 13 mg/m<sup>3</sup> -  
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg -  
 Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects  
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects  
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6  
 Worker Industry: 24.2 mg/m<sup>3</sup> - Worker Professional: 24.2 mg/m<sup>3</sup> - Consumer: 4.3 mg/m<sup>3</sup>  
 - Exposure: Human Inhalation - Frequency: Long Term, local effects  
 Worker Industry: 97.3 mg/m<sup>3</sup> - Worker Professional: 97.3 mg/m<sup>3</sup> - Consumer: 17.3  
 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects  
**PNEC Exposure Limit Values**  
 n-butyl acetate - CAS: 123-86-4  
 Target: Fresh Water - Value: 0.18 mg/l  
 Target: Marine water - Value: 0.018 mg/l  
 Target: Intermittent emission - Value: 0.36 mg/l  
 Target: Freshwater sediments - Value: 0.98 mg/kg  
 Target: Marine water sediments - Value: 0.098 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 35.6 mg/l  
 Target: Soil (agricultural) - Value: 0.09 mg/kg  
 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 Target: Fresh Water - Value: 0.635 mg/l  
 Target: Marine water - Value: 0.0635 mg/l  
 Target: Intermittent emission - Value: 6.35 mg/l  
 Target: Microorganisms in sewage treatments - Value: 100 mg/l  
 Target: Freshwater sediments - Value: 3.29 mg/kg  
 Target: Marine water sediments - Value: 0.329 mg/kg  
 Target: Soil (agricultural) - Value: 0.29 mg/kg  
 isobutyl acetate [2] - CAS: 110-19-0  
 Target: Fresh Water - Value: 0.17 mg/l  
 Target: Marine water - Value: 0.017 mg/l  
 Target: Intermittent emission - Value: 0.34 mg/l  
 Target: Microorganisms in sewage treatments - Value: 200 mg/l  
 Target: Freshwater sediments - Value: 0.877 mg/kg  
 Target: Marine water sediments - Value: 0.0877 mg/kg  
 Target: Soil (agricultural) - Value: 0.0755 mg/kg  
 xylene [4] - CAS: 1330-20-7  
 Target: Fresh Water - Value: 0.327 mg/l  
 Target: Marine water - Value: 0.327 mg/l  
 Target: Intermittent emission - Value: 0.327 mg/l  
 Target: Freshwater sediments - Value: 12.46 mg/kg  
 Target: Marine water sediments - Value: 12.46 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  
 Target: Soil (agricultural) - Value: 2.31 mg/kg  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 Target: Fresh Water - Value: 55.8 mg/l  
 Target: Marine water - Value: 55.8 mg/l  
 Target: Freshwater sediments - Value: 284.7 mg/kg  
 Target: Marine water sediments - Value: 284.7 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 709 mg/l  
 Target: Soil (agricultural) - Value: 22.5 mg/kg



## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Target: Food chain - Value: 1000 mg/kg  
 methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 Target: Fresh Water - Value: 0.94 mg/l  
 Target: Marine water - Value: 0.094 mg/l  
 Target: Freshwater sediments - Value: 5.74 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 10 mg/l  
 Target: Soil (agricultural) - Value: 1.47 mg/kg  
 2-hydroxyethyl methacrylate - CAS: 868-77-9  
 Target: Fresh Water - Value: 0.482 mg/l  
 Target: Marine water - Value: 0.482 mg/l  
 Target: Freshwater sediments - Value: 3.79 mg/kg  
 Target: Marine water sediments - Value: 3.79 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 10 mg/l  
 Target: Soil (agricultural) - Value: 0.476 mg/kg  
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Target: Fresh Water - Value: 0.00044 mg/l  
 Target: Marine water - Value: 0.00044 mg/l  
 Target: Freshwater sediments - Value: 0.128 mg/kg  
 Target: Marine water sediments - Value: 0.013 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 10 mg/kg  
 Target: Soil (agricultural) - Value: 0.136 mg/kg  
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6  
 Target: Fresh Water - Value: 0.0012 mg/kg  
 Target: Marine water - Value: 0.00012 mg/kg  
 Target: Freshwater sediments - Value: 11 mg/kg  
 Target: Marine water sediments - Value: 1.1 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 10 mg/l  
 Target: Soil (agricultural) - Value: 2.54 mg/kg  
 Biological Exposure Index  
 xylene [4] - CAS: 1330-20-7  
 Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine -  
 Sampling Period: End of turn  
 Appropriate engineering controls:  
 None  
 Individual protection measures  
 Eye protection:  
 Eye glasses with side protection. (EN166)  
 Protection for skin:  
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.  
 Protection for hands:  
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)  
 Respiratory protection:  
 Use adequate protective respiratory equipment.  
 Thermal Hazards:  
 None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	Liquid, colourless
Odour:	typical
Odour threshold:	N.D.
pH:	Not Relevant
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Solid/gas flammability:	N.A.



## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Upper/lower flammability or explosive limits:	7.5% - 1.6% Vol. (n-butyl acetate)
Vapour density:	> 1
Flash point:	< 23 °C
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	0.950 - 0.970
Solubility in water:	N.D.
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

---

#### 10. STABILITY AND REACTIVITY

##### Reactivity

It may generate dangerous reactions (See subsections below)

##### Chemical stability

It may generate dangerous reactions (See subsections below)

##### Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), and nitrides.

It may catch fire on contact with oxidising mineral acids, powerful oxidising agents, and powerful reducing agents.

##### Conditions to avoid

Avoid accumulating electrostatic charge.

##### Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

##### Hazardous decomposition products

None.

---

#### 11. TOXICOLOGICAL INFORMATION

##### Information on toxicological effects

##### Toxicological information of the product:

SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

##### a) acute toxicity

Not classified

No data available for the product

##### b) skin corrosion/irritation

Not classified

No data available for the product

##### c) serious eye damage/irritation

Not classified

No data available for the product

##### d) respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

##### e) germ cell mutagenicity

Not classified

No data available for the product

##### f) carcinogenicity

Not classified

No data available for the product

##### g) reproductive toxicity

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Not classified

No data available for the product

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 10760 mg/kg - Source: OECD 423

Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h - Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.5 mg/l - Duration: 4h

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401

Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403

Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 6.7 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 1100 mg/kg

butanone; ethyl methyl ketone - CAS: 78-93-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2054 mg/kg - Source: OECD 423

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h

methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 7900 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 29.8 mg/l - Duration: 4h

2-hydroxyethyl methacrylate - CAS: 868-77-9

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5050 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3000 mg/kg

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.  
 xylene [4] - CAS: 1330-20-7  
 Observations on human subjects.  
 Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 High exposure can cause  
 drowsiness, migraine, narcosis and dizziness.  
 The extended contact and/or repeated with skin can cause dermatitis.  
 Environmental concentrations more than 200 ppm result irritating for eyes and respiratory tract.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3

methyl methacrylate; methyl 2-methylprop-2-enoate - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

## 12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

Not classified for environmental hazards

No data available for the product

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 200 mg/l - Duration h: 72

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96 - Notes: OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: LC50 - Species: Daphnia = 408 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Notes: 14d OECD 204

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Notes: 21d OECD 211

isobutyl acetate [2] - CAS: 110-19-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 370 mg/l - Duration h: 72 - Notes: OCSE 201

Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202

Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d  
 Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Daphnia = 308 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae = 2029 mg/l - Duration h: 96  
 Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96  
 methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 a) Aquatic acute toxicity:  
 Endpoint: LC50 - Species: Fish > 79 mg/l - Duration h: 96  
 Endpoint: EC50 - Species: Daphnia = 69 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae = 170 mg/l - Duration h: 96  
 Persistence and degradability  
 n-butyl acetate - CAS: 123-86-4  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83  
 2-methoxy-1-methylethyl acetate - CAS: 108-65-6  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83 - Notes: OECD 301F  
 isobutyl acetate [2] - CAS: 110-19-0  
 Biodegradability: Readily biodegradable  
 xylene [4] - CAS: 1330-20-7  
 Biodegradability: Readily biodegradable  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 98 - Notes: OECD 301D  
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310  
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6  
 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD 310  
 Bioaccumulative potential  
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2  
 Bioaccumulation: Bioaccumulative  
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6  
 Bioaccumulation: Bioaccumulative  
 Mobility in soil  
 N.A.  
 Other adverse effects  
 None

### 13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods  
 Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

### 14. TRANSPORT INFORMATION



UN number  
 ADR-UN Number: 1263

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

DOT number: UN1263  
 IATA-UN Number: 1263  
 IMDG-UN Number: 1263  
 UN proper shipping name  
 ADR-Shipping Name: PAINT  
 DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound  
 IATA-Shipping Name: PAINT  
 IMDG-Shipping Name: PAINT  
 Transport hazard class(es)  
 ADR-Class: 3  
 DOT Hazard Class: 3  
 ADR - Hazard identification number: 33  
 IATA-Class: 3  
 IATA-Label: 3  
 IMDG-Class: 3  
 IMDG-Class: 3  
 Packing group  
 ADR-Packing Group: II  
 DOT Packing group: II  
 IATA-Packing group: II  
 IMDG-Packing group: II  
 Environmental hazards  
 ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No  
 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
 N.A.  
 Special precautions  
 Rail (RID): 3  
 DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28  
 ADR-Subsidiary hazards: -  
 ADR-S.P.: 163 367 640D 650  
 ADR-Transport category (Tunnel restriction code): 2 (D/E)  
 IATA-Passenger Aircraft: 353  
 IATA-Subsidiary hazards: -  
 IATA-Cargo Aircraft: 364  
 IATA-S.P.: A3 A72 A192  
 IATA-ERG: 3L  
 IMDG-EmS: F-E , S-E  
 IMDG-Subsidiary hazards: -  
 IMDG-Stowage and handling: Category A  
 IMDG-Segregation: -

## 15. REGULATORY INFORMATION

### USA - Federal regulations

#### TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

n-butyl acetate is listed in TSCA Section 8b

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

isobutyl acetate [2] is listed in TSCA Section 8b

xylene [4] is listed in TSCA Section 8b

butanone; ethyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in TSCA Section 8b, Section

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

8d HSDR

2-hydroxyethyl methacrylate is listed in TSCA Section 8b

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: n-butyl acetate, isobutyl acetate [2], xylene [4], butanone; ethyl methyl ketone, methyl methacrylate; methyl 2-methylprop-2-enoate.

Section 313 – Toxic chemical list: xylene [4], methyl methacrylate; methyl 2-methylprop-2-enoate.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: n-butyl acetate - Reportable quantity: 5000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

xylene [4] - Reportable quantity: 100 pounds

butanone; ethyl methyl ketone - Reportable quantity: 5000 pounds

methyl methacrylate; methyl 2-methylprop-2-enoate - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 2946.375958 pounds.

CAA - Clean Air Act

CAA listed substances:

n-butyl acetate is listed in CAA Section 111  $\geq 40\%$  -  $< 50\%$

isobutyl acetate [2] is listed in CAA Section 111  $\geq 3\%$  -  $< 5\%$

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON  $\geq 3\%$  -  $< 5\%$

butanone; ethyl methyl ketone is listed in CAA Section 111, Section 112(b) - HON  $\geq 1\%$  -  $< 2.5\%$

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON  $\geq 0.5\%$  -  $< 1\%$ .

CWA - Clean Water Act

CWA listed substances:

n-butyl acetate is listed in CWA Section 304, Section 311

isobutyl acetate [2] is listed in CWA Section 311

xylene [4] is listed in CWA Section 304, Section 311

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

n-butyl acetate

isobutyl acetate [2]

xylene [4]

butanone; ethyl methyl ketone

methyl methacrylate; methyl 2-methylprop-2-enoate.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

n-butyl acetate

isobutyl acetate [2]

xylene [4]

butanone; ethyl methyl ketone

methyl methacrylate; methyl 2-methylprop-2-enoate.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

n-butyl acetate  
isobutyl acetate [2]  
xylene [4]  
butanone; ethyl methyl ketone  
methyl methacrylate; methyl 2-methylprop-2-enoate.

Volatile Organic compounds - VOCs = 58.65 %  
Volatile Organic compounds - VOCs = 568.90 g/l  
Volatile CMR substances = 0.01 %  
Organic Carbon - C = 0.37

#### 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H225 Highly flammable liquid and vapour.  
H412 Harmful to aquatic life with long lasting effects.  
H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.  
H317 May cause an allergic skin reaction.  
H361 Suspected of damaging fertility or the unborn child.  
H413 May cause long lasting harmful effects to aquatic life.

Safety Data Sheet dated 9/16/2022, version 2  
Sections modified from the previous revision:

2. HAZARD(S) IDENTIFICATION  
3. COMPOSITION/INFORMATION ON INGREDIENTS  
4. FIRST-AID MEASURES  
6. ACCIDENTAL RELEASE MEASURES  
7. HANDLING AND STORAGE  
8. EXPOSURE CONTROLS/PERSONAL PROTECTION  
9. PHYSICAL AND CHEMICAL PROPERTIES  
11. TOXICOLOGICAL INFORMATION  
12. ECOLOGICAL INFORMATION  
SECTION 14: Transport information  
15. REGULATORY INFORMATION

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ATE: Acute Toxicity Estimate  
ATEmix: Acute toxicity Estimate (Mixtures)  
CAS: Chemical Abstracts Service (division of the American Chemical Society).



## Safety Data Sheet

### LGE040 SIVOGLOSS Lucido Acrilico trasparente - Clear Acrylic glossy finish

CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average