

## Safety Data Sheet



# LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Safety Data Sheet dated 3/15/2018, version 1

## 1. Identification

### GHS Product identifier

Mixture identification:

Trade name:

SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Other means of identification

Trade code:

LFE607

### Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

### Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

## 2. Hazard identification

### Classification of the hazardous product

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Danger, Eye Dam. 1, Causes serious eye damage.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

GHS label elements, including precautionary statements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash ... Thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water/...  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P310 Immediately call a POISON CENTER/doctor/...  
P312 Call a POISON CENTER/ doctor/if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P321 Specific treatment (see ... On this label).  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO<sub>2</sub>, water spray. Do not use water jet.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

### 3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 30% - < 40%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 15% - < 20%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.10/1 Asp. Tox. 1 H304 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.7/2 Unst. Expl. ⚠ A.8/3 STOT SE 3 H336 ⚠ A.9/2 STOT RE 2 H373
>= 5% - < 7%	2-methylpropan-1-ol; iso-butanol	Index number: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 REACH No.: 01-2119484609-23	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ A.8/3 STOT SE 3 H336
>= 5% - < 7%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-	⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.2/2 Skin Irrit. 2 H315

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

		32	<p>⚠ A.8/3 STOT SE 3 H335</p> <p>⚠ A.9/2 STOT RE 2 H373</p> <p>⚠ A.10/1 Asp. Tox. 1 H304</p>
>= 5% - < 7%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	<p>⚠ B.6/2 Flam. Liq. 2 H225</p> <p>⚠ A.8/3 STOT SE 3 H336</p>
>= 3% - < 5%	butanone; ethyl methyl ketone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH No.: 01-2119457290-43	<p>⚠ B.6/2 Flam. Liq. 2 H225</p> <p>⚠ A.8/3 STOT SE 3 H336</p>
>= 3% - < 5%	4-methylpentan-2-one; isobutyl methyl ketone	Index number: 606-004-00-4 CAS: 108-10-1 EC: 203-550-1 REACH No.: 01-2119473980-30	<p>⚠ B.6/2 Flam. Liq. 2 H225</p> <p>⚠ A.8/3 STOT SE 3 H335</p> <p>⚠ A.1/4/Inhal Acute Tox. 4 H332</p>
>= 1% - < 3%	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	Index number: 603-016-00-1 CAS: 123-42-2 EC: 204-626-7 REACH No.: 01-2119473975-21	<p>⚠ B.6/3 Flam. Liq. 3 H226</p> <p>⚠ A.8/3 STOT SE 3 H335</p>
>= 1% - < 3%	ethyl acetate	Index number: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH No.: 01-2119475103-46	<p>⚠ B.6/2 Flam. Liq. 2 H225</p> <p>⚠ A.3/2A Eye Irrit. 2A H319</p> <p>⚠ A.8/3 STOT SE 3 H336</p>
>= 0.1% - < 0.3%	methyl methacrylate; methyl 2-methylprop-2-enoate	Index number: 607-035-00-6 CAS: 80-62-6 EC: 201-297-1 REACH No.: 01-2119452498-28	<p>⚠ A.4.2/1 Skin Sens. 1 H317</p> <p>⚠ B.6/2 Flam. Liq. 2 H225</p> <p>⚠ A.8/3 STOT SE 3 H335</p> <p>⚠ A.2/2 Skin Irrit. 2 H315</p>

#### 4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### 5. Fire-fighting measures

Suitable and unsuitable extinguishing media

LFE607/1

Page n. 3 of 14

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO<sub>2</sub>, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

---

#### 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

---

#### 8. Exposure controls/personal protection

Control parameters

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

toluene - CAS: 108-88-3

EU - TWA(8h): 192 mg/m<sup>3</sup>, 50 ppm - STEL: 384 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

ACGIH - TWA(8h): 50 ppm - Notes: Skin and eye irr

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

isobutyl acetate [2] - CAS: 110-19-0

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

butanone; ethyl methyl ketone - CAS: 78-93-3  
 EU - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm  
 ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 EU - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm  
 ACGIH - TWA(8h): 20 ppm - STEL: 75 ppm - Notes: A3, BEI - URT irr, dizziness, headache

4-hydroxy-4-methylpentan-2-one; diacetone alcohol - CAS: 123-42-2  
 ACGIH - TWA(8h): 50 ppm - Notes: URT and eye irr

ethyl acetate - CAS: 141-78-6  
 ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr  
 EU - TWA(8h): 734 mg/m<sup>3</sup>, 200 ppm - STEL: 1468 mg/m<sup>3</sup>, 400 ppm

methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 EU - TWA(8h): 50 ppm - STEL: 100 ppm  
 ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: DSEN, A4 - URT and eye irr, body weight eff, pulm edema

**DNEL Exposure Limit Values**

n-butyl acetate - CAS: 123-86-4  
 Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, local effects  
 Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, local effects

toluene - CAS: 108-88-3  
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal  
 - Frequency: Long Term, systemic effects  
 Worker Industry: 192 mg/m<sup>3</sup> - Worker Professional: 192 mg/m<sup>3</sup> - Consumer: 56.5 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1  
 Worker Industry: 310 mg/m<sup>3</sup> - Worker Professional: 310 mg/m<sup>3</sup> - Consumer: 55 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, local effects

xylene [4] - CAS: 1330-20-7  
 Worker Industry: 289 mg/m<sup>3</sup> - Worker Professional: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal  
 - Frequency: Long Term, systemic effects  
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

isobutyl acetate [2] - CAS: 110-19-0  
 Worker Industry: 300 mg/m<sup>3</sup> - Worker Professional: 300 mg/m<sup>3</sup> - Consumer: 35.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 600 mg/m<sup>3</sup> - Worker Professional: 600 mg/m<sup>3</sup> - Consumer: 300 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg - Exposure: Human Dermal -  
 Frequency: Long Term, systemic effects  
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

butanone; ethyl methyl ketone - CAS: 78-93-3  
 Worker Industry: 1161 mg/kg - Worker Professional: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human  
 Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 600 mg/m<sup>3</sup> - Worker Professional: 600 mg/m<sup>3</sup> - Consumer: 106 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Worker Industry: 83 mg/m<sup>3</sup> - Worker Professional: 83 mg/m<sup>3</sup> - Consumer: 14.7 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 208 mg/m<sup>3</sup> - Worker Professional: 208 mg/m<sup>3</sup> - Consumer: 115.2 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 83 mg/m<sup>3</sup> - Worker Professional: 83 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long  
 Term, local effects  
 Worker Industry: 208 mg/m<sup>3</sup> - Worker Professional: 208 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short  
 Term, local effects  
 Worker Industry: 11.8 mg/kg - Worker Professional: 11.8 mg/kg - Consumer: 4.2 mg/kg - Exposure: Human Dermal  
 - Frequency: Long Term, systemic effects

4-hydroxy-4-methylpentan-2-one; diacetone alcohol - CAS: 123-42-2  
 Worker Industry: 9.4 mg/kg - Worker Professional: 9.4 mg/kg - Consumer: 3.4 mg/kg - Exposure: Human Dermal -

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Frequency: Long Term, systemic effects  
 Worker Industry: 66.4 mg/m<sup>3</sup> - Worker Professional: 66.4 mg/m<sup>3</sup> - Consumer: 11.8 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 3.4 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethyl acetate - CAS: 141-78-6  
 Worker Industry: 1468 mg/m<sup>3</sup> - Worker Professional: 1468 mg/m<sup>3</sup> - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 1468 mg/m<sup>3</sup> - Worker Professional: 1468 mg/m<sup>3</sup> - Consumer: 734 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Short Term, local effects  
 Worker Industry: 63 mg/kg - Worker Professional: 63 mg/kg - Consumer: 37 mg/kg - Exposure: Human Dermal -  
 Frequency: Long Term, systemic effects  
 Worker Industry: 734 mg/m<sup>3</sup> - Worker Professional: 734 mg/m<sup>3</sup> - Consumer: 367 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 734 mg/m<sup>3</sup> - Worker Professional: 734 mg/m<sup>3</sup> - Consumer: 367 mg/m<sup>3</sup> - Exposure: Human  
 Inhalation - Frequency: Long Term, local effects  
 Consumer: 4.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4  
 Target: Fresh Water - Value: 0.18 mg/l  
 Target: Marine water - Value: 0.018 mg/l  
 Target: Intermittent emission - Value: 0.36 mg/l  
 Target: Freshwater sediments - Value: 0.98 mg/kg  
 Target: Marine water sediments - Value: 0.098 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 35.6 mg/l  
 Target: Soil (agricultural) - Value: 0.09 mg/kg

toluene - CAS: 108-88-3  
 Target: Fresh Water - Value: 0.68 mg/l  
 Target: Marine water - Value: 0.68 mg/l  
 Target: Intermittent emission - Value: 0.68 mg/l  
 Target: Freshwater sediments - Value: 16.39 mg/kg  
 Target: Marine water sediments - Value: 16.39 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 13.61 mg/l  
 Target: Soil (agricultural) - Value: 2.89 mg/kg

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1  
 Target: Fresh Water - Value: 0.4 mg/l  
 Target: Marine water - Value: 0.04 mg/l  
 Target: Freshwater sediments - Value: 1.52 mg/kg  
 Target: Marine water sediments - Value: 0.152 mg/kg  
 Target: Intermittent emission - Value: 11 mg/l  
 Target: Microorganisms in sewage treatments - Value: 10 mg/l  
 Target: Soil (agricultural) - Value: 0.06 mg/kg

xylene [4] - CAS: 1330-20-7  
 Target: Fresh Water - Value: 0.32 mg/l  
 Target: Marine water - Value: 0.32 mg/l  
 Target: Intermittent emission - Value: 0.32 mg/l  
 Target: Freshwater sediments - Value: 12.46 mg/kg  
 Target: Marine water sediments - Value: 12.46 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l  
 Target: Soil (agricultural) - Value: 2.31 mg/kg

isobutyl acetate [2] - CAS: 110-19-0  
 Target: Fresh Water - Value: 0.17 mg/l  
 Target: Marine water - Value: 0.017 mg/l  
 Target: Intermittent emission - Value: 0.34 mg/l  
 Target: Microorganisms in sewage treatments - Value: 200 mg/l  
 Target: Freshwater sediments - Value: 0.877 mg/kg  
 Target: Marine water sediments - Value: 0.0877 mg/kg  
 Target: Soil (agricultural) - Value: 0.0755 mg/kg

butanone; ethyl methyl ketone - CAS: 78-93-3  
 Target: Fresh Water - Value: 55.8 mg/l  
 Target: Intermittent emission - Value: 55.8 mg/l  
 Target: Microorganisms in sewage treatments - Value: 709 mg/l  
 Target: Freshwater sediments - Value: 284.7 mg/kg  
 Target: Marine water sediments - Value: 284.7 mg/kg  
 Target: Soil (agricultural) - Value: 22.5 mg/kg  
 Target: Food chain - Value: 1000 mg/kg

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Target: Fresh Water - Value: 0.6 mg/l  
 Target: Freshwater sediments - Value: 0.27 mg/kg



## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Target: Microorganisms in sewage treatments - Value: 27.5 mg/l  
 Target: Soil (agricultural) - Value: 1.3 mg/kg  
 4-hydroxy-4-methylpentan-2-one; diacetone alcohol - CAS: 123-42-2  
 Target: Fresh Water - Value: 2 mg/l  
 Target: Marine water - Value: 0.2 mg/l  
 Target: Freshwater sediments - Value: 9.06 mg/kg  
 Target: Marine water sediments - Value: 0.91 mg/kg  
 Target: Intermittent emission - Value: 1 mg/l  
 Target: Microorganisms in sewage treatments - Value: 82 mg/l  
 Target: Soil (agricultural) - Value: 0.63 mg/kg  
 ethyl acetate - CAS: 141-78-6  
 Target: Fresh Water - Value: 0.24 mg/l  
 Target: Marine water - Value: 0.024 mg/l  
 Target: Intermittent emission - Value: 1.65 mg/l  
 Target: Microorganisms in sewage treatments - Value: 650 mg/l  
 Target: Freshwater sediments - Value: 1.15 mg/kg  
 Target: Marine water sediments - Value: 0.115 mg/kg  
 Target: Soil (agricultural) - Value: 0.148 mg/kg  
 Target: Food chain - Value: 200 mg/kg  
 Appropriate engineering controls  
 None  
 Individual protection measures, such as personal protective equipment (PPE)  
 Eye protection:  
 Eye glasses with side protection. (EN166)  
 Protection for skin:  
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.  
 Protection for hands:  
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)  
 Respiratory protection:  
 Use adequate protective respiratory equipment.  
 Thermal Hazards:  
 None

## 9. Physical and chemical properties

Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Flash point:	> 4 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.5% - 1.6% Vol. (n-butyl acetate)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	0.910 - 0.930
Solubility in water:	N.D.
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

## 10. Stability and reactivity

Reactivity  
 It may generate dangerous reactions (See subsections below)  
 Chemical stability  
 It may generate dangerous reactions (See subsections below)  
 Possibility of hazardous reactions  
 It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.  
 Conditions to avoid  
 Avoid accumulating electrostatic charge.  
 Incompatible materials  
 Avoid contact with combustible materials. The product could catch fire.  
 Hazardous decomposition products

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

None.

#### 11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

- a) acute toxicity  
Not classified  
No data available for the product
- b) skin corrosion/irritation  
The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation  
The product is classified: Eye Dam. 1 H318
- d) respiratory or skin sensitisation  
The product is classified: Skin Sens. 1 H317
- e) germ cell mutagenicity  
Not classified  
No data available for the product
- f) carcinogenicity  
Not classified  
No data available for the product
- g) reproductive toxicity  
The product is classified: Repr. 2 H361
- h) STOT-single exposure  
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure  
The product is classified: STOT RE 2 H373
- j) aspiration hazard  
Not classified  
No data available for the product

Toxicological information of the main substances found in the product:

n-butyl acetate - CAS: 123-86-4

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 10760 mg/kg - Source: OECD 423  
Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OECD 403  
Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

toluene - CAS: 108-88-3

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit = 12124 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403
- b) skin corrosion/irritation:  
Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 2830 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat > 24.6 mg/l - Duration: 4h

xylene [4] - CAS: 1330-20-7

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg  
Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h  
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

isobutyl acetate [2] - CAS: 110-19-0

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401  
Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg  
Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403  
Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

butanone; ethyl methyl ketone - CAS: 78-93-3

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat > 2193 mg/kg - Source: OECD 423  
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402  
Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

- a) acute toxicity:



## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Test: LC50 - Route: Inhalation - Species: Rat > 2000 Ppm - Duration: 4h - Source: OCSE 403  
 Test: LD50 - Route: Oral - Species: Rat = 2080 mg/kg - Source: OCSE 401  
 Test: LD50 - Route: Skin - Species: Rabbit > 20 ml/kg - Source: OCSE 402  
 4-hydroxy-4-methylpentan-2-one; diacetone alcohol - CAS: 123-42-2  
 a) acute toxicity:  
 Test: LD50 - Route: Oral - Species: Rat = 3002 mg/kg  
 Test: LD50 - Route: Skin - Species: Rat > 1875 mg/kg  
 ethyl acetate - CAS: 141-78-6  
 a) acute toxicity:  
 Test: LD50 - Route: Oral - Species: Rat = 4934 mg/kg - Source: OCSE 401  
 Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg  
 methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 a) acute toxicity:  
 Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg  
 Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg  
 Test: LC50 - Route: Inhalation - Species: Rat > 29.8 mg/l - Duration: 4h  
 n-butyl acetate - CAS: 123-86-4  
 The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.  
 Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.  
 toluene - CAS: 108-88-3  
 Effects following acute exposure:  
 At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.  
 At 400 ppm: worsening of symptoms and mental confusion.  
 xylene [4] - CAS: 1330-20-7  
 Observations on human subjects.  
 Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 High exposure can cause drowsiness, migraine, narcosis and dizziness.  
 The extended contact and/or repeated with skin can cause dermatitis.  
 Environmental concentrations more than 200 ppm result irritating for eyes and respiratory tract.  
 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Product is harmful if inhaled.  
 Repeated exposure can cause irritation to respiratory tract, skin dryness, cough, cephalic nausea, dizziness and vomiting. Symptoms of chronic exposure are neurological, gastro-intestinal and respiratory.  
 4-hydroxy-4-methylpentan-2-one; diacetone alcohol - CAS: 123-42-2  
 The product is irritating for eyes and for the superior respiratory tract.  
 The acute toxicity shows itself to environmental concentrations of 100 ppm with irritation to eyes, nose end throat end with pulmonary troubles at 400 ppm.  
 ethyl acetate - CAS: 141-78-6  
 The product is extremely volatile and provokes for inhalation, irritation to respiratory tracts. Acute exposition can cause depression of central nervous system with effects such as drowsiness, reflex loss, narcosis.

Substance(s) listed on the NTP report on Carcinogens:  
 None.

Substance(s) listed on the IARC Monographs:  
 toluene - Group 3  
 xylene [4] - Group 3  
 4-methylpentan-2-one; isobutyl methyl ketone - Group 2B  
 methyl methacrylate; methyl 2-methylprop-2-enoate - Group 3.

Substance(s) listed as OSHA Carcinogen(s):  
 None.

Substance(s) listed as NIOSH Carcinogen(s):  
 None.

## 12. Ecological information

### Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Not classified for environmental hazards

No data available for the product

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72  
 toluene - CAS: 108-88-3  
 a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3  
 Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48  
 Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96  
 b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72  
 Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d  
 Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d  
 xylene [4] - CAS: 1330-20-7  
 a) Aquatic acute toxicity:  
 Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96  
 Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72  
 Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24  
 b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d  
 Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d  
 isobutyl acetate [2] - CAS: 110-19-0  
 a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Algae = 397 mg/l - Duration h: 72 - Notes: OCSE 201  
 Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202  
 Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203  
 b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Daphnia = 308 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae = 2029 mg/l - Duration h: 96  
 Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96  
 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 a) Aquatic acute toxicity:  
 Endpoint: EC50 - Species: Daphnia > 200 mg/l - Duration h: 48  
 Endpoint: LC50 - Species: Fish > 179 mg/l - Duration h: 96 - Notes: OCSE 203  
 b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Algae > 146 mg/l - Notes: 7 days  
 Endpoint: NOEC - Species: Daphnia = 30 mg/l - Notes: 21 days  
 ethyl acetate - CAS: 141-78-6  
 a) Aquatic acute toxicity:  
 Endpoint: LC50 - Species: Algae > 100 mg/l - Duration h: 72  
 Endpoint: EC50 - Species: Daphnia = 165 mg/l - Duration h: 48  
 Endpoint: LC50 - Species: Fish = 230 mg/l - Duration h: 96  
 b) Aquatic chronic toxicity:  
 Endpoint: NOEC - Species: Daphnia = 2.4 mg/l - Notes: 21d  
 methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6  
 a) Aquatic acute toxicity:  
 Endpoint: LC50 - Species: Fish = 191 mg/l - Duration h: 96  
 Endpoint: EC50 - Species: Daphnia = 69 mg/l - Duration h: 48  
 Endpoint: EC50 - Species: Algae > 110 mg/l - Duration h: 72  
 Persistence and degradability  
 n-butyl acetate - CAS: 123-86-4  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 toluene - CAS: 108-88-3  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 xylene [4] - CAS: 1330-20-7  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 isobutyl acetate [2] - CAS: 110-19-0  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 butanone; ethyl methyl ketone - CAS: 78-93-3  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.  
 4-hydroxy-4-methylpentan-2-one; diacetone alcohol - CAS: 123-42-2  
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 98.51 - Notes: OECD 301 A  
 Bioaccumulative potential

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

N.A.  
Mobility in soil  
N.A.  
Other adverse effects  
None

#### 13. Disposal considerations

Safe handling and methods for disposal  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

#### 14. Transport information



UN number	
TDG number:	UN1263
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263
UN proper shipping name	
TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name:	Paint
IATA-Shipping Name:	PAINT
IATA-Technical name:	Paint
IMDG-Shipping Name:	PAINT
IMDG-Shipping name:	Paint
Transport hazard class(es)	
TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
TDG Packing group:	II
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
N.A.	
Special precautions in connection with transport or conveyance	
Rail (RID):	3
TDG Special provisions:	59,142
DOT Special provisions:	149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

#### 15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

None.

DSL inventory - Domestic substances list

no substances listed

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

n-butyl acetate is listed in TSCA Section 8b

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

2-methylpropan-1-ol; iso-butanol is listed in TSCA Section 8b, Section 8d HSDR

xylene [4] is listed in TSCA Section 8b

isobutyl acetate [2] is listed in TSCA Section 8b

butanone; ethyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR

4-methylpentan-2-one; isobutyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR

4-hydroxy-4-methylpentan-2-one; diacetone alcohol is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

ethyl acetate is listed in TSCA Section 8b

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in TSCA Section 8b, Section 8d HSDR.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 - Hazardous substances: n-butyl acetate, toluene, 2-methylpropan-1-ol; iso-butanol, xylene [4], isobutyl acetate [2], butanone; ethyl methyl ketone, 4-methylpentan-2-one; isobutyl methyl ketone, ethyl acetate, methyl methacrylate; methyl 2-methylprop-2-enoate.

Section 313 - Toxic chemical list: toluene, xylene [4], 4-methylpentan-2-one; isobutyl methyl ketone, methyl methacrylate; methyl 2-methylprop-2-enoate.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: n-butyl acetate - Reportable quantity: 5000 pounds

toluene - Reportable quantity: 1000 pounds

2-methylpropan-1-ol; iso-butanol - Reportable quantity: 5000 pounds

xylene [4] - Reportable quantity: 100 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

butanone; ethyl methyl ketone - Reportable quantity: 5000 pounds

4-methylpentan-2-one; isobutyl methyl ketone - Reportable quantity: 5000 pounds

ethyl acetate - Reportable quantity: 5000 pounds

methyl methacrylate; methyl 2-methylprop-2-enoate - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 1852.023335 pounds.

CAA - Clean Air Act

CAA listed substances:

n-butyl acetate is listed in CAA Section 111

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

2-methylpropan-1-ol; iso-butanol is listed in CAA Section 111

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

butanone; ethyl methyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

4-methylpentan-2-one; isobutyl methyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

4-hydroxy-4-methylpentan-2-one; diacetone alcohol is listed in CAA Section 111

ethyl acetate is listed in CAA Section 111

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

n-butyl acetate is listed in CWA Section 304, Section 311

toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

xylene [4] is listed in CWA Section 304, Section 311  
isobutyl acetate [2] is listed in CWA Section 311  
4-methylpentan-2-one; isobutyl methyl ketone is listed in CWA Section 304  
ethyl acetate is listed in CWA Section 304  
methyl methacrylate; methyl 2-methylprop-2-enoate is listed in CWA Section 311.

#### USA - State specific regulations

##### California Proposition 65

Substance(s) listed under California Proposition 65:  
toluene - Listed as reproductive toxicant  
4-methylpentan-2-one; isobutyl methyl ketone - Listed as carcinogen and reproductive toxicant.

##### Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:  
n-butyl acetate  
toluene  
2-methylpropan-1-ol; iso-butanol  
xylene [4]  
isobutyl acetate [2]  
butanone; ethyl methyl ketone  
4-methylpentan-2-one; isobutyl methyl ketone  
4-hydroxy-4-methylpentan-2-one; diacetone alcohol  
ethyl acetate  
methyl methacrylate; methyl 2-methylprop-2-enoate.

##### New Jersey Right to know

Substance(s) listed under New Jersey Right to know:  
n-butyl acetate  
toluene  
2-methylpropan-1-ol; iso-butanol  
xylene [4]  
isobutyl acetate [2]  
butanone; ethyl methyl ketone  
4-methylpentan-2-one; isobutyl methyl ketone  
4-hydroxy-4-methylpentan-2-one; diacetone alcohol  
ethyl acetate  
methyl methacrylate; methyl 2-methylprop-2-enoate.

##### Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:  
n-butyl acetate  
toluene  
2-methylpropan-1-ol; iso-butanol  
xylene [4]  
isobutyl acetate [2]  
butanone; ethyl methyl ketone  
4-methylpentan-2-one; isobutyl methyl ketone  
4-hydroxy-4-methylpentan-2-one; diacetone alcohol  
ethyl acetate  
methyl methacrylate; methyl 2-methylprop-2-enoate.

Volatile Organic compounds - VOCs = 80.93 %  
Volatile Organic compounds - VOCs = 752.62 g/l  
Volatile CMR substances = 0.00 %  
Organic Carbon - C = 0.57

---

## 16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H335 May cause respiratory irritation.  
H318 Causes serious eye damage.  
H312 Harmful in contact with skin.  
H332 Harmful if inhaled.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.

## Safety Data Sheet

### LFE607 SIVOSAT Finitura ACR effetto naturale - Clear Acrylic natural effect

Safety Data Sheet dated 3/15/2018, version 1

**Disclaimer:**

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average