

Safety Data Sheet



LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Safety Data Sheet dated 9/16/2022, version 2

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Other means of identification:

Trade code: LFP7080

Recommended use of the chemical and restrictions on use

Recommended use:

IS- Industrial use

PW - Professional use

Varnish

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02-903041

Importer:

Richelieu America Ltd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Distributor:

Richelieu America Ltd, 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: +1-800-361-6000.

Emergency phone number for U.S.A.: Chemtrec +1-800-424-9300

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number:

NUOVA S.I.V.A.M. SpA - Tel. +39 02- 903041 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

- ⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.
- Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash ... Thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor/... if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see ... On this label).
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:

HMIS rating:

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number	Classification
>= 25% - < 30%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 US-HAE/C3 Aquatic Chronic 3 H412 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/2A Eye Irrit. 2A H319 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304
>= 12.5% - < 15%	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]	Index number: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 REACH No.: 01-2119489379-17	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
>= 3% - < 5%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304 US-HAE/C3 Aquatic Chronic 3 H412
>= 1% - < 2.5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 0.1% - < 0.25%	Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z)	CAS: 147900-93-4 REACH No.: 01-2119971821-33	<ul style="list-style-type: none"> ⚠ A.1/4/Oral Acute Tox. 4 H302 ⚠ US-HAE/C2 Aquatic Chronic 2 H411 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ A.9/2 STOT RE 2 H373
>= 0.1% - < 0.25%	Propylidynetrimehanol	CAS: 77-99-6 EC: 201-074-9 REACH No.: 01-2119486799-10	<ul style="list-style-type: none"> ⚠ A.7/2 Repr. 2 H361

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

955 ppm	Fatty acids, tall-oil, compds. with oleylamine	CAS: 85711-55-3 EC: 288-315-1 REACH No.: 01-2119974148-28	<ul style="list-style-type: none"> ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ A.9/2 STOT RE 2 H373
49 ppm	Decamethylcyclopentasiloxane (D5)	CAS: 541-02-6 EC: 208-764-9 REACH No.: 01-2119511367-43	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
9 ppm	Dodecamethylcyclohexasiloxane (D6)	CAS: 540-97-6 EC: 208-762-8 REACH No.: 01-2119517435-42	The product is not classified as dangerous according to OSHA Hazard Communication Standard (29 CFR 1910.1200).
9 ppm	octamethylcyclotetrasiloxane (D4)	Index number: 014-018-00-1 CAS: 556-67-2 EC: 209-136-7 REACH No.: 01-2119529238-36	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.7/2 Repr. 2 H361 US-HAE/C4 Aquatic Chronic 4 H413

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

ACGIH - TWA(8h): 10 mg/m³ - Notes: A4 - LRT irr
 ethylbenzene - CAS: 100-41-4
 EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy),
 cochlear impair
 n-butyl acetate - CAS: 123-86-4
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
 EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 ACGIH - TWA(8h): 10 ppm
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 ACGIH - TWA(8h): 123 mg/m³, 10 ppm
 DNEL Exposure Limit Values
 xylene [4] - CAS: 1330-20-7
 Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³
 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter
 <= 10 µm] - CAS: 13463-67-7
 Worker Industry: 3.3 mg/m³ - Worker Professional: 3.3 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
 ethylbenzene - CAS: 100-41-4
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human
 Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
 n-butyl acetate - CAS: 123-86-4
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³
 - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 11 mg/kg - Worker Professional: 11 mg/kg - Consumer: 6 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 Worker Industry: 0.024 mg/kg - Worker Professional: 0.024 mg/kg - Consumer: 0.012
 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Propylidynetrimethanol - CAS: 77-99-6
 Worker Industry: 3.3 mg/m³ - Worker Professional: 3.3 mg/m³ - Consumer: 0.58 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 0.94 mg/kg - Worker Professional: 0.94 mg/kg - Consumer: 0.34 mg/kg
 - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 0.34 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic
 effects
 Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 Worker Industry: 24.2 mg/m³ - Worker Professional: 24.2 mg/m³ - Consumer: 4.3 mg/m³
 - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 97.3 mg/m³ - Worker Professional: 97.3 mg/m³ - Consumer: 17.3
 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Worker Industry: 6.1 mg/m³ - Worker Professional: 6.1 mg/m³ - Consumer: 1.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 11 mg/m³ - Worker Professional: 11 mg/m³ - Consumer: 2.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Worker Industry: 73 mg/m³ - Worker Professional: 73 mg/m³ - Consumer: 13 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Intermittent emission - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

Target: Fresh Water - Value: 0.184 mg/l

Target: Marine water - Value: 0.0184 mg/l

Target: Intermittent emission - Value: 0.61 mg/l

Target: Freshwater sediments - Value: 1000 mg/kg

Target: Marine water sediments - Value: 100 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Soil (agricultural) - Value: 100 mg/kg

Target: Food chain - Value: 1667 mg/kg

ethylbenzene - CAS: 100-41-4

Target: Fresh Water - Value: 0.1 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Freshwater sediments - Value: 13.7 mg/kg

Target: Marine water sediments - Value: 1.37 mg/kg

Target: Intermittent emission - Value: 0.1 mg/l

Target: Microorganisms in sewage treatments - Value: 9.6 mg/l

Target: Soil (agricultural) - Value: 2.68 mg/kg

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Intermittent emission - Value: 0.36 mg/l

Target: Freshwater sediments - Value: 0.98 mg/kg

Target: Marine water sediments - Value: 0.098 mg/kg

Target: Microorganisms in sewage treatments - Value: 35.6 mg/l

Target: Soil (agricultural) - Value: 0.09 mg/kg

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

Target: Fresh Water - Value: 0.006 mg/l

Target: Marine water - Value: 0.0006 mg/l

Target: Freshwater sediments - Value: 2.46 mg/kg

Target: Marine water sediments - Value: 0.25 mg/kg

Target: Soil (agricultural) - Value: 0.28 mg/kg

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Target: Fresh Water - Value: 0.0012 mg/kg

Target: Marine water - Value: 0.00012 mg/kg

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Target: Freshwater sediments - Value: 11 mg/kg
 Target: Marine water sediments - Value: 1.1 mg/kg
 Target: Microorganisms in sewage treatments - Value: 10 mg/l
 Target: Soil (agricultural) - Value: 2.54 mg/kg
 Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6
 Target: Freshwater sediments - Value: 13 mg/kg
 Target: Marine water sediments - Value: 1.3 mg/kg
 Target: Microorganisms in sewage treatments - Value: 1 mg/kg
 Target: Soil (agricultural) - Value: 3.77 mg/kg
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Target: Fresh Water - Value: 0.00044 mg/l
 Target: Marine water - Value: 0.000044 mg/l
 Target: Freshwater sediments - Value: 0.128 mg/kg
 Target: Marine water sediments - Value: 0.013 mg/kg
 Target: Microorganisms in sewage treatments - Value: 10 mg/kg
 Target: Soil (agricultural) - Value: 0.136 mg/kg

Biological Exposure Index
 xylene [4] - CAS: 1330-20-7
 Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine -
 Sampling Period: End of turn
 ethylbenzene - CAS: 100-41-4
 Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and
 acid fenilgliossalico - Sampling Period: End of turn; End of working week

Appropriate engineering controls:
 None

Individual protection measures
Eye protection:
 Eye glasses with side protection. (EN166)

Protection for skin:
 Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or
 viton.

Protection for hands:
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
 (EN374)

Respiratory protection:
 Use respiratory protection where ventilation is insufficient or exposure is prolonged.
 Use adequate protective respiratory equipment.

Thermal Hazards:
 None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	Liquid, white
Odour:	typical
Odour threshold:	N.D.
pH:	Not Relevant
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.0% - 0.9% Vol. (Xylene)
Vapour density:	> 1
Flash point:	> 23 °C
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	1.340 - 1.360
Solubility in water:	N.D.
Solubility in oil:	partial

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

LACCASAT 30 Bianco polivalente EX - PU White self-seal external

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

d) respiratory or skin sensitisation

The product is classified: Skin Sens. 1A H317

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

The product is classified: Repr. 2 H361

h) STOT-single exposure

The product is classified: STOT SE 3 H335

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 6.7 mg/l - Duration: 4h

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Test: LD50 - Route: Skin - Species: Rabbit = 1100 mg/kg
 titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat > 3.5 mg/l - Duration: 4h

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat = 17.2 mg/l - Duration: 1h

i) STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 10760 mg/kg - Source: OECD 423

Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h - Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 1570 mg/kg

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: OECD 423

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

xylene [4] - Group 3

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - Group 2B

ethylbenzene - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm].

12. ECOLOGICAL INFORMATION

Ecotoxicity

LFP7080/2

Page n. 10 of 15

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Adopt good working practices, so that the product is not released into the environment.

LACCASAT 30 Bianco polivalente EX - PU White self-seal external

The product is classified: Aquatic Chronic 3 - H412

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day

Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 200 mg/l - Duration h: 72

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 7.89 mg/l - Duration h: 72 - Notes: OECD 201

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 15.2 mg/l - Duration h: 48 - Notes: OECD TG 202

Endpoint: EC50 - Species: Algae = 7.43 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: OECD 203

Persistence and degradability

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable

ethylbenzene - CAS: 100-41-4

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80

n-butyl acetate - CAS: 123-86-4

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

Biodegradability: Non-readily biodegradable

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

Biodegradability: Readily biodegradable

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD 310

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 4.47 - Notes: OECD 310

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310

Bioaccumulative potential

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

Bioaccumulation: Bioaccumulative
 Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6
 Bioaccumulation: Bioaccumulative
 octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Bioaccumulation: Bioaccumulative

Mobility in soil

N.A.

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number

ADR-UN Number: 1263

DOT number: UN1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

UN proper shipping name

ADR-Shipping Name: PAINT

DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound

IATA-Shipping Name: PAINT

IMDG-Shipping Name: PAINT

Transport hazard class(es)

ADR-Class: 3

DOT Hazard Class: 3

ADR - Hazard identification number: 30

IATA-Class: 3

IATA-Label: 3

IMDG-Class: 3

IMDG-Class: 3

Packing group

ADR-Packing Group: III

DOT Packing group: III

IATA-Packing group: III

IMDG-Packing group: III

Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions

Rail (RID): 3

DOT Special provisions: 367, B1, B52, B131, IB3, T2, TP1, TP29

ADR-Subsidiary hazards: -

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

ADR-S.P.:	163 367 640E 650
ADR-Transport category (Tunnel restriction code):	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

xylene [4] is listed in TSCA Section 8b

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is listed in TSCA Section 8b

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR

n-butyl acetate is listed in TSCA Section 8b

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) is listed in TSCA Section 8b

Propylidynetrimethanol is listed in TSCA Section 8b

Fatty acids, tall-oil, compds. with oleylamine is listed in TSCA Section 8b

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], ethylbenzene, n-butyl acetate.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds

n-butyl acetate - Reportable quantity: 5000 pounds.

Reportable quantity for mixture: 357.642279 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON $\geq 25\%$ - $< 30\%$

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON $\geq 3\%$ - $< 5\%$

n-butyl acetate is listed in CAA Section 111 $\geq 1\%$ - $< 2.5\%$

Propylidynetrimethanol is listed in CAA Section 112(b) - HON $\geq 0.1\%$ - $< 0.25\%$.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

n-butyl acetate is listed in CWA Section 304, Section 311.

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - Listed as carcinogen
ethylbenzene - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

xylene [4]

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
ethylbenzene
n-butyl acetate.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

xylene [4]

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
ethylbenzene
n-butyl acetate.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

xylene [4]

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
ethylbenzene
n-butyl acetate.

Volatile Organic compounds - VOCs = 33.81 %

Volatile Organic compounds - VOCs = 459.88 g/l

Volatile CMR substances = 0.00 %

Organic Carbon - C = 0.30

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H302 Harmful if swallowed.

H411 Toxic to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H318 Causes serious eye damage.

H413 May cause long lasting harmful effects to aquatic life.

Safety Data Sheet dated 9/16/2022, version 2

Sections modified from the previous revision:

Safety Data Sheet

LFP7080 LACCASAT 30 Bianco polivalente EX - PU White self-seal external

1. IDENTIFICATION
2. HAZARD(S) IDENTIFICATION
3. COMPOSITION/INFORMATION ON INGREDIENTS
6. ACCIDENTAL RELEASE MEASURES
7. HANDLING AND STORAGE
8. EXPOSURE CONTROLS/PERSONAL PROTECTION
9. PHYSICAL AND CHEMICAL PROPERTIES
11. TOXICOLOGICAL INFORMATION
12. ECOLOGICAL INFORMATION
- SECTION 14: Transport information
15. REGULATORY INFORMATION

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average