

TECHNICAL DATA

PRODUCT : **LWY100 – TRANSPARENT TIX SEALER FOR EXTERIOR**

DEFINITION : **Waterborne transparent sealer for exterior**

MAIN FIELDS OF USE:

As intermediate sealer on items previously treated with solvent base or waterbase impregnating

PROPERTIES:

It is a waterbased product completely odourless, studied for the coating for articles for exterior, as fixtures,shutters and doors.

Good transparency, drying rapidity, and good sanding.

Easy to apply, and very good verticality. It does not contain biocide.

CHEMICAL-PHYSICAL PROPERTIES:

SPECIFIC WEIGHT :	1.000
DRY RESIDUE :	38% ± 2
VISCOSITY :	20.000 cps
YIELD:	6-8 sqmt./kg.
STABILITY	12 months

APPLICATION: by spray with airless or air mix. In winter periods, with low room temperature it is suggested the use of a preheater set between 35° and 45°C.

QUANTITY: Apply 128-180 micron of humid thickness. We suggest not to apply higher quantity as the sanding might be jeopardised.

SUPPORT PREPARATION:

Apply on completely dried support.

DRYING:

- Dust free: 40 minutes
- Dry to touch: 1 hour and 30 minutes
- Sanding/over coating: 12 hours

Sand with Stearate Paper grain 220-240

These data can be influenced by the temperature, or by unfavourable weather or ambient conditions.

REMARKS.:

Keep away from frost. Do not store or work at temperature lower than 5°C.

T.D. LWY100 – March 2013 1^

IMPORTANT: The information contained in this technical data sheet is based on the average results obtained in our laboratories and is the best experience we have gained with the most rigorous, thorough tests and checks possible.

However, as every panel or support, even of the same type, may be different to every other one in terms of the characteristics that influence the outcome of painting operations considerably and as the environment, mixtures and the equipment used also contribute to the final results. The final result is thus the user's exclusive responsibility The information given herein is based on a temperature of 20° at 70% relative humidity.