

TECHNICAL DATA

PRODUCT	LWW 7xx – LASUR serie
DEFINITION	WATERBASED PROTECTIVE WAX
DILUTING AGENT	(if necessary) WATER

---

**MAIN FIELD OF USE:**

Impregnating LASUR products are developed for application of artifacts in unstable wood type, such beading, roofing, balconies and gates destined outside.

---

**PROPERTIES:**

These water-based products with outstanding quality and with high solid content have been developed for the protection and decoration of wood, to preserve it for a long time from weather and UV rays.

The special water-repellent and hygro-regulator features conferred by LASUR, allows the natural transpiration wood.

The product does not chalk, does not flake and does not crack.

---

**CHEMICAL-PHYSICAL PROPERTIES:**

SPECIFIC WEIGHT	1.000 ± 10 g/l
SOLID CONTENT	27% ± 2
VISCOSITY (DIN cup Ø 4)	50" ± 2"
YIELD	8÷10 sqm/l
SHELF LIFE	12 months
DRYING-TIME at room temperature:	
Dust-free	15÷20 mins.
Dry to touch	about 45 mins.
Overcoatable	about 6 hrs.

These values may be affected by temperature and weather condition, or by unfavorable environmental conditions.

In any case, it is not advisable to apply the product at temperatures below 5°C.

Follow TDs LWW7xx SERIE

---

**APPLICATION:** by brush.

**AMOUNT TO APPLY:**

The product usually allows an application of 60-80 g/sqm

**SUGGESTED CYCLES/SUBSTRATE PREPARATION:**

- **New wood:** apply a first coat of LASUR series on the raw wood, uniformly distributing the product on the surface. - Respect the recommended drying time. - After reaching the full drying (about 6 hours), you can proceed to a slight superficial abrasion with the purpose of eliminating some imperfections due to the rise of the wood fibers. You can then proceed to the application of the second and final coat of LASUR.

- **Old wood:** if the substrate only needs to be refreshed and the surface of this is still intact, it is advisable to apply one or two coats of colored LASUR in lighter shades, in order not to alter the final color of article.

If the substrate has evident signs of wear of time, we recommend cleaning the surface with a brass brush to remove the damaged layers of paint, and then proceed as before.

LWW7xx SERIE can be pigmented with the pastes of LXW10x SERIE to get different shades.

---

**REMARK:**

KEEP AWAY FROM FROST.

DO NOT STORE THE PRODUCT AT TEMPERATURES BELOW 5°C.

---

TDs LWW 7xx – 2016, May – revision 2

**IMPORTANT:** The information contained in this technical data sheet is based on the average results obtained in our laboratories and is the best experience we have gained with the most rigorous, thorough tests and checks possible. However, as every panel or support, even of the same type, may be different to every other one in terms of the characteristics that influence the outcome of painting operations considerably and as the environment, mixtures and the equipment used also contribute to the results. The result is thus the user's exclusive responsibility. The information given herein is based on a temperature of 20° at 70% relative humidity.