

TECHNICAL DATA

PRODUCT :	LXW10x - PASTES FOR IDROSIV
DEFINITION :	Pigmented pastes for Idrosiv
DILUTING AGENT :	WATER

MAIN FIELDS OF USE:

Fixtures, fences. For the protection of wood articles for exterior.

PROPERTIES:

Put in the converter (LWW300 or LWW100) they enable to obtain all the range of shades of the colour cards and to and to prepare dyes on samples

CHEMICAL-PHYSICAL PROPERTIES:

LXW102	IDROSIV BLACK
LXW103	IDROSIV YELLOW
LXW105	IDROSIV RED

USE: To be added, during mixing, up to a maximum of 5/6% (for the darker shades) to the converter of the range LWW100 and LWW300 in order to obtain the wished shades.

REMARKS:

On particularly resinous and reach of tannine veneers (iroko, merants, etc.) it is necessary a special treatment before proceeding with the normal varnishing cycle.

T.D. LXW10x April 2011 1°

NOTES:

The informations contained in this technical data sheet is based on the average results obtained in our laboratories and is the best experience we have gained with the most rigorous, thorough tests and checks possible.

However, as every panel or support, even of the same type, may be different to every other one in terms of the characteristics that influence the outcome of painting operations considerably and as the environment, mixtures and the equipment used also contribute to the final results. The final result is thus the user's exclusive responsibility. The information given herein is based on a temperature of 20° at 70% relative humidity.