

Safety Data Sheet



LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

Safety Data Sheet dated 7/2/2018, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: LAKPRIMER Fondo PU bianco EC - PU white primer EC

Other means of identification:

Trade code: LBP625

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-860-529-7704

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-860-529-7704

Competent person responsible for the safety data sheet:

msds@sivam.it






Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

-  Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, Eye Irrit. 2A, Causes serious eye irritation.
-  Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
-  Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash ... Thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see ... On this label).
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	/ 2
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	B

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Qty	Name	Ident. Number	Classification
>= 12.5% - < 15%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/2A Eye Irrit. 2A H319 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304
>= 7% - < 10%	Titanium Dioxide	CAS: 13463-67-7	The product is not classified as dangerous according to OSHA Hazard Communication

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

		EC: REACH No.:	236-675-5 01-2119489379-17	Standard (29 CFR 1910.1200).
>= 7% - < 10%	toluene	Index number: CAS: EC: REACH No.:	601-021-00-3 108-88-3 203-625-9 01-2119471310-51	⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.10/1 Asp. Tox. 1 H304 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.7/2 Unst. Expl. ⚠ A.8/3 STOT SE 3 H336 ⚠ A.9/2 STOT RE 2 H373
>= 1% - < 3%	ethylbenzene	Index number: CAS: EC: REACH No.:	601-023-00-4 100-41-4 202-849-4 01-2119489370-35	⚠ B.6/2 Flam. Liq. 2 H225 US-HAE/C3 Aquatic Chronic 3 H412 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.
Remove contaminated clothing immediately and dispose off safely.
After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.
Remove all sources of ignition.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Provide adequate ventilation.
Remove persons to safety.
Use appropriate respiratory protection.
See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
 Exercise the greatest care when handling or opening the container.
 Do not use on extensive surface areas in premises where there are occupants.
 Don't use empty container before they have been cleaned.
 Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 Contaminated clothing should be changed before entering eating areas.
 Do not eat or drink while working.
 See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
 Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Safety electric system.
 Storage temperature:
 Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

xylene [4] - CAS: 1330-20-7
 EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair
 Titanium Dioxide - CAS: 13463-67-7
 ACGIH - TWA(8h): 10 mg/m³ - Notes: A4 - LRT irr
 toluene - CAS: 108-88-3
 EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss
 ethylbenzene - CAS: 100-41-4
 EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

DNEL Exposure Limit Values

xylene [4] - CAS: 1330-20-7
 Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human
 Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal
 - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Titanium Dioxide - CAS: 13463-67-7
 Worker Industry: 10 mg/m³ - Worker Professional: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long
 Term, local effects
 Consumer: 700 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 toluene - CAS: 108-88-3
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal
 - Frequency: Long Term, systemic effects
 Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 ethylbenzene - CAS: 100-41-4
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term,
 systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation
 - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

xylene [4] - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.32 mg/l
 Target: Marine water - Value: 0.32 mg/l
 Target: Intermittent emission - Value: 0.32 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Soil (agricultural) - Value: 2.31 mg/kg
 Titanium Dioxide - CAS: 13463-67-7
 Target: Fresh Water - Value: 0.127 mg/l
 Target: Marine water - Value: 1 mg/l
 Target: Intermittent emission - Value: 0.61 mg/l
 Target: Freshwater sediments - Value: 1000 mg/kg
 Target: Marine water sediments - Value: 100 mg/kg
 Target: Microorganisms in sewage treatments - Value: 100 mg/l
 Target: Soil (agricultural) - Value: 100 mg/kg
 Target: Food chain - Value: 1667 mg/kg
 toluene - CAS: 108-88-3
 Target: Fresh Water - Value: 0.68 mg/l
 Target: Marine water - Value: 0.68 mg/l
 Target: Intermittent emission - Value: 0.68 mg/l
 Target: Freshwater sediments - Value: 16.39 mg/kg
 Target: Marine water sediments - Value: 16.39 mg/kg
 Target: Microorganisms in sewage treatments - Value: 13.61 mg/l
 Target: Soil (agricultural) - Value: 2.89 mg/kg
 ethylbenzene - CAS: 100-41-4
 Target: Fresh Water - Value: 0.1 mg/l
 Target: Marine water - Value: 0.01 mg/l
 Target: Freshwater sediments - Value: 13.7 mg/kg
 Target: Soil (agricultural) - Value: 2.68 mg/kg
 Target: Intermittent emission - Value: 0.1 mg/l
 Target: Microorganisms in sewage treatments - Value: 9.6 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	white fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.0% - 0.9% Vol. (Xylene)
Vapour density:	> 1
Flash point:	> 4 °C
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	1.500 - 1.520
Solubility in water:	N.D.
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

10. STABILITY AND REACTIVITY

Reactivity

LBP625/1

Page n. 5 of 10

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

- It may generate dangerous reactions (See subsections below)
- Chemical stability
 - It may generate dangerous reactions (See subsections below)
- Possibility of hazardous reactions
 - It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.
- Conditions to avoid
 - Avoid accumulating electrostatic charge.
- Incompatible materials
 - Avoid contact with combustible materials. The product could catch fire.
- Hazardous decomposition products
 - None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

LAKPRIMER Fondo PU bianco EC - PU white primer EC

- a) acute toxicity
 - Not classified
 - No data available for the product
- b) skin corrosion/irritation
 - The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation
 - The product is classified: Eye Irrit. 2A H319
- d) respiratory or skin sensitisation
 - Not classified
 - No data available for the product
- e) germ cell mutagenicity
 - Not classified
 - No data available for the product
- f) carcinogenicity
 - Not classified
 - No data available for the product
- g) reproductive toxicity
 - The product is classified: Repr. 2 H361
- h) STOT-single exposure
 - Not classified
 - No data available for the product
- i) STOT-repeated exposure
 - The product is classified: STOT RE 2 H373
- j) aspiration hazard
 - Not classified
 - No data available for the product

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

- a) acute toxicity:
 - Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
 - Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg
 - Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h
 - Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Titanium Dioxide - CAS: 13463-67-7

- a) acute toxicity:
 - Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425
 - Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
 - Test: LC50 - Route: Inhalation - Species: Rat > 6.8 mg/l - Duration: 4h

toluene - CAS: 108-88-3

- a) acute toxicity:
 - Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg
 - Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
 - Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403
- b) skin corrosion/irritation:
 - Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

toluene - CAS: 108-88-3

Effects following acute exposure:

At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

At 400 ppm: worsening of symptoms and mental confusion.

Substance(s) listed on the NTP report on Carcinogens:
None.

Substance(s) listed on the IARC Monographs:
xylene [4] - Group 3
Titanium Dioxide - Group 2B
toluene - Group 3
ethylbenzene - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):
None.

Substance(s) listed as NIOSH Carcinogen(s):
Titanium Dioxide.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

LAKPRIMER Fondo PU bianco EC - PU white primer EC

Not classified for environmental hazards

No data available for the product

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 2.4 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 4.6 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Duration h: 168

Persistence and degradability

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.

ethylbenzene - CAS: 100-41-4

Biodegradability: Readily biodegradable - Test: N.A. - Duration h: 28 days - %: 70-80 - Notes: N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC



UN number	
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263
UN proper shipping name	
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name:	Paint
IATA-Shipping Name:	PAINT
IATA-Technical name:	Paint
IMDG-Shipping Name:	PAINT
IMDG-Shipping name:	Paint
Transport hazard class(es)	
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
IMDG-Class:	3
Packing group	
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
N.A.	
Special precautions	
Rail (RID):	3
DOT Special provisions:	149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

xylene [4] is listed in TSCA Section 8b

Titanium Dioxide is listed in TSCA Section 8b

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], toluene, ethylbenzene.

Section 313 – Toxic chemical list: xylene [4], toluene, ethylbenzene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

toluene - Reportable quantity: 1000 pounds
ethylbenzene - Reportable quantity: 1000 pounds.
Reportable quantity for mixture: 710.2272727 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON
ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311
toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants
ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:
Titanium Dioxide - Listed as carcinogen
toluene - Listed as reproductive toxicant
ethylbenzene - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:
xylene [4]
Titanium Dioxide
toluene
ethylbenzene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:
xylene [4]
Titanium Dioxide
toluene
ethylbenzene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:
xylene [4]
Titanium Dioxide
toluene
ethylbenzene.

Volatile Organic compounds - VOCs = 25.70 %
Volatile Organic compounds - VOCs = 390.64 g/l
Volatile CMR substances = 0.01 %
Organic Carbon - C = 0.22

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Safety Data Sheet dated 7/2/2018, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.
This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.

Safety Data Sheet

LBP625 LAKPRIMER Fondo PU bianco EC - PU white primer EC

EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average