







LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

Safety Data Sheet dated 2/18/2019, version 1

1. Identification

GHS Product identifier

Mixture identification:

Trade name:

DILUENTE Universale prodotti acqua - Universal Thinner for WB

Other means of identification

Trade code:

Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Thinner for paints and varnishes

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

- Warning, Flam. Liq. 3, Flammable liquid and vapour.
 Danger, Repr. 1B, May damage fertility or the unborn child.
 Warning, STOT SE 3, May cause drowsiness or dizziness.

GHS label elements, including precautionary statements

Hazard pictograms:







Danger

H226 Flammable liquid and vapour.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/ doctor/if you feel unwell.

LZD786/1

Page n. 1 of 7



LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

P370+P378 In case of fire: Use ... to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number		Classification
>= 30%- < 60%	1-methoxy-2-propanol; monopropylene glycol methyl ether	Index number: CAS: EC: REACH No.:	603-064-00-3 107-98-2 203-539-1 01-2119457435- 35	♦ B.6/3 Flam. Liq. 3 H226♦ A.8/3 STOT SE 3 H336
>= 0.1% - < 1%	2-methoxypropanol	Index number: CAS: EC:	603-106-00-0 1589-47-5 216-455-5	 ♦ B.6/3 Flam. Liq. 3 H226 ♦ A.7/1B Repr. 1B H360 ♦ A.8/3 STOT SE 3 H335 ♦ A.2/2 Skin Irrit. 2 H315 ♦ A.3/1 Eye Dam. 1 H318

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke. Hazardous combustion products:

None

Explosive properties:

N.D. in volume

LZD786/1

Page n. 2 of 7



LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

EU - TWA(8h): 375 mg/m3, 100 ppm - STEL: 563 mg/m3, 150 ppm - Notes: Skin

ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr

DNEL Exposure Limit Values

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Worker Industry: 553.5 mg/m3 - Worker Professional: 553.5 mg/m3 - Exposure: Human Inhalation - Frequency:

Short Term, local effects

Worker Industry: 369 mg/m3 - Worker Professional: 369 mg/m3 - Consumer: 43.9 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 183 mg/kg - Worker Professional: 183 mg/kg - Consumer: 78 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Consumer: 33 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Target: Fresh Water - Value: 10 mg/l

Target: Marine water - Value: 1 mg/l

Target: Intermittent emission - Value: 100 mg/l Target: Freshwater sediments - Value: 52.3 mg/kg Target: Marine water sediments - Value: 5.2 mg/kg

Target: Soil (agricultural) - Value: 4.59 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

LZD786/1

Page n. 3 of 7



LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour: colourless fluid

Odour: typical Odour threshold: Ñ.D. pH: N.A. N.D. °C Melting point / freezing point: Initial boiling point and boiling range: > 100 °C > 30 °C Flash point: Evaporation rate: N.D. Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.D. N.D. (20 °C) Vapour pressure: Vapour density: > 1 0.960 - 0.970 Relative density: Solubility in water: soluble Solubility in oil: partial Partition coefficient (n-octanol/water): N.D. > 270 °C Auto-ignition temperature: N.D. °C Decomposition temperature: Viscosity: N.D.

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

DILUENTE Universale prodotti acqua - Universal Thinner for WB

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

d) respiratory or skin sensitisation

Not classified

No data available for the product

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

LZD786/1

Page n. 4 of 7



LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

No data available for the product

g) reproductive toxicity

The product is classified: Repr. 1B H360

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

No data available for the product

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 54.6 mg/l - Duration: 4h

Substance(s) listed on the NTP report on Carcinogens:

None

Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment. DILUENTE Universale prodotti acqua - Universal Thinner for WB

Not classified for environmental hazards

No data available for the product

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity: Endpoint: LC50 - Species: Daphnia > 21100 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish > 4600 mg/l - Duration h: 96 Endpoint: EC50 - Species: Algae > 1000 mg/l - Notes: 7 d

Persistence and degradability

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 96 - Notes: OECD 301E

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information



UN number

TDG number: UN1263 ADR-UN Number: 1263 DOT number: UN1263 IATA-UN Number: 1263 IMDG-UN Number: 1263

LZD786/1

Page n. 5 of 7



LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

UN proper shipping name TDG-Shipping Name:

TDG-Shipping Name: PAINT RELATED MATERIAL ADR-Shipping Name: PAINT RELATED MATERIAL

DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid

lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound

IATA-Shipping Name: PAINT RELATED MATERIAL IATA-Technical name: al IMDG-Shipping Name: PAINT RELATED MATERIAL

Transport hazard class(es)

TDG Class: 3
ADR-Class: 3
DOT Hazard Class: 3

ADR - Hazard identification number: 30
IATA-Class: 3
IATA-Label: 3
IMDG-Class: 3
Packing group

TDG Packing group:

ADR-Packing Group:

DOT Packing group:

III

IATA-Packing group:

III

IMDG-Packing group:

III

IMDG-Packing group:

III

Environmental hazards

ADR-Environmental Pollutant:

IMDG-Marine pollutant:

No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

Rail (RID):

TDG Special provisions: 59,142

DOT Special provisions: 367, B1, B52, B131, IB3, T2, TP1, TP29

ADR-Subsidiary risks: ADR-S.P.:

163 367 640E 650

ADR-Transport category (Tunnel restriction code): 3 (D/E)

 IATA-Passenger Aircraft:
 355

 IATA-Subsidiary risks:

 IATA-Cargo Aircraft:
 366

 IATA-S.P.:
 A3 A72 A192

 IATA-ERG:
 3L

 IMDG-EmS:
 F-E , S-E

 IMDG-Subsidiary risks:

IMDG-Subsidiary risks: IMDG-Stowage and handling: Category A

IMDG-Segregation: -

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

None.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

1-methoxy-2-propanol; monopropylene glycol methyl ether is listed in TSCA Section 8b, Section 8d HSDR 2-methoxypropanol is listed in TSCA Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: no substances listed.

Section 313 – Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

LZD786/1

Page n. 6 of 7



LZD786 DILUENTE Universale prodotti acqua - Universal Thinner for WB

1-methoxy-2-propanol; monopropylene glycol methyl ether is listed in CAA Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

None

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know: 1-methoxy-2-propanol; monopropylene glycol methyl ether.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know: 1-methoxy-2-propanol; monopropylene glycol methyl ether.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know: 1-methoxy-2-propanol; monopropylene glycol methyl ether.

Volatile Organic compounds - VOCs = 50.00 % Volatile Organic compounds - VOCs = 485.00 g/l

Volatile CMR substances = 0.10 % Organic Carbon - C = 0.27

16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H335 May cause respiratory irritation.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Safety Data Sheet dated 2/18/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances. GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients. KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population. LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

National Toxicology Program NTP:

Occupational Safety and Health Administration. OSHA: PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. TLV: Threshold Limiting Value. TWA: Time-weighted average

LZD786/1

Page n. 7 of 7