

Safety Data Sheet



LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Safety Data Sheet dated 6/6/2022, version 2

1. Identification

GHS Product identifier

Mixture identification:

Trade name: CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Other means of identification

Trade code: LGP501

Recommended use and restrictions on use

Recommended use:

IS- Industrial use

PW - Professional use

Varnish for wood

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02-903041

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02- 903041 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.

⚠ Warning, Skin Irrit. 2, Causes skin irritation.

⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.

⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

GHS label elements, including precautionary statements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash ... Thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water/...
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see ... On this label).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use ... to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 15% - < 40%	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]	Index number: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5 REACH No.: 01-2119489379-17	The product is not classified as dangerous according to WHMIS 2015.
>= 10% - < 30%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 CAN-HAE/C3 Aquatic Chronic 3 H412 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

			2119488216 -32	<ul style="list-style-type: none"> ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304
>= 1% - < 5%	ethylbenzene	Index number: CAS: EC: REACH No.:	601-023-00-4 100-41-4 202-849-4 01-2119489370 -35	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304 CAN-HAE/C3 Aquatic Chronic 3 H412
>= 1% - < 5%	isobutyl acetate [2]	Index number: CAS: EC: REACH No.:	607-026-00-7 110-19-0 203-745-1 01-2119488971 -22	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.8/3 STOT SE 3 H336
>= 1% - < 5%	n-butyl acetate	Index number: CAS: EC: REACH No.:	607-025-00-1 123-86-4 204-658-1 01-2119485493 -29	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 1% - < 5%	2-methoxy-1-methylethyl acetate	Index number: CAS: EC: REACH No.:	607-195-00-7 108-65-6 203-603-9 01-2119475791 -29	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 0.1% - < 1%	Propylidynetrimethanol	CAS: EC: REACH No.:	77-99-6 201-074-9 01-2119486799 -10	<ul style="list-style-type: none"> ⚠ A.7/2 Repr. 2 H361
180 ppm	Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z)	CAS: REACH No.:	147900-93-4 01-2119971821 -33	<ul style="list-style-type: none"> ⚠ A.1/4/Oral Acute Tox. 4 H302 ⚠ CAN-HAE/C2 Aquatic Chronic 2 H411 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ A.9/2 STOT RE 2 H373
120 ppm	Fatty acids, tall-oil, compds. with oleylamine	CAS: EC: REACH No.:	85711-55-3 288-315-1 01-2119974148 -28	<ul style="list-style-type: none"> ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ A.4.2/1A Skin Sens. 1A H317 ⚠ A.9/2 STOT RE 2 H373
55 ppm	Decamethylcyclopentasiloxane (D5)	CAS:	541-02-6	The product is not classified as dangerous according to WHMIS

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

		EC: 208-764-9 REACH No.: 01-2119511367-43	2015.
15 ppm	octamethylcyclotetrasiloxane (D4)	Index number: 014-018-00-1 CAS: 556-67-2 EC: 209-136-7 REACH No.: 01-2119529238-36	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.7/2 Repr. 2 H361 CAN-HAE/C4 Aquatic Chronic 4 H413
9 ppm	Dodecamethylcyclohexasiloxane (D6)	CAS: 540-97-6 EC: 208-762-8 REACH No.: 01-2119517435-42	The product is not classified as dangerous according to WHMIS 2015.
60 ppb	formaldehyde ...%	Index number: 605-001-00-5 CAS: 50-00-0 EC: 200-001-8 REACH No.: 01-2119488953-20	<ul style="list-style-type: none"> ⚠ A.6/1B Carc. 1B H350 ⚠ A.5/2 Muta. 2 H341 ⚠ A.1/3/Oral Acute Tox. 3 H301 ⚠ A.1/3/Dermal Acute Tox. 3 H311 ⚠ A.1/3/Inhal Acute Tox. 3 H331 ⚠ A.2/1B Skin Corr. 1B H314 ⚠ A.4.2/1 Skin Sens. 1 H317 Specific Concentration Limits: C >= 25%: Skin Corr. 1B H314 5% <= C < 25%: Skin Irrit. 2 H315 C >= 0,2%: Skin Sens. 1 H317 C >= 5%: STOT SE 3 H335
60 ppb	acetaldehyde; ethanal	Index number: 605-003-00-6 CAS: 75-07-0 EC: 200-836-8	<ul style="list-style-type: none"> ⚠ B.6/1 Flam. Liq. 1 H224 ⚠ A.6/2 Carc. 2 H351 ⚠ A.8/3 STOT SE 3 H335
60 ppb	1,4-dioxane	Index number: 603-024-00-5 CAS: 123-91-1 EC: 204-661-8	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.6/2 Carc. 2 H351 ⚠ A.8/3 STOT SE 3 H335

The actual concentration of the components listed above is withheld as a trade secret.

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

ACGIH - TWA(8h): 10 mg/m³ - Notes: A4 - LRT irr

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

isobutyl acetate [2] - CAS: 110-19-0

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: Skin

TLV TWA - 275 mg/m³ - 50 ppm

TLV STEL - 550 mg/m³ - 100 ppm

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

ACGIH - TWA(8h): 10 ppm

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

ACGIH - TWA(8h): 123 mg/m³, 10 ppm

formaldehyde ...% - CAS: 50-00-0

ACGIH - TWA(8h): 0.1 ppm - STEL: 0.3 ppm - Notes: DSEN, RSEN, A1 - URT and eye irr, URT cancer

EU - TWA(8h): 0,37 mg/m³, 0,3 ppm - STEL: 0,74 mg/m³, 0,6 ppm - Notes: Dermal sensitisation

acetaldehyde; ethanal - CAS: 75-07-0

ACGIH - STEL: Ceiling 25 ppm - Notes: A2 - Eye and URT irr

1,4-dioxane - CAS: 123-91-1

EU - TWA(8h): 73 mg/m³, 20 ppm

ACGIH - TWA(8h): 20 ppm - Notes: Skin, A3 - Liver dam

DNEL Exposure Limit Values

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

Worker Industry: 3.3 mg/m³ - Worker Professional: 3.3 mg/m³ - Exposure: Human

Inhalation - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ -

Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg -

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

isobutyl acetate [2] - CAS: 110-19-0
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 300 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 11 mg/kg - Worker Professional: 11 mg/kg - Consumer: 6 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 2 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 Worker Industry: 796 mg/kg - Worker Professional: 796 mg/kg - Consumer: 320 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 275 mg/m³ - Worker Professional: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 550 mg/m³ - Worker Professional: 550 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Consumer: 36 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Propylidynetrimechanol - CAS: 77-99-6
 Worker Industry: 3.3 mg/m³ - Worker Professional: 3.3 mg/m³ - Consumer: 0.58 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 0.94 mg/kg - Worker Professional: 0.94 mg/kg - Consumer: 0.34 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 0.34 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 Worker Industry: 0.024 mg/kg - Worker Professional: 0.024 mg/kg - Consumer: 0.012 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 Worker Industry: 24.2 mg/m³ - Worker Professional: 24.2 mg/m³ - Consumer: 4.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 97.3 mg/m³ - Worker Professional: 97.3 mg/m³ - Consumer: 17.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 Worker Industry: 73 mg/m³ - Worker Professional: 73 mg/m³ - Consumer: 13 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6
 Worker Industry: 6.1 mg/m³ - Worker Professional: 6.1 mg/m³ - Consumer: 1.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Worker Industry: 11 mg/m³ - Worker Professional: 11 mg/m³ - Consumer: 2.7 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
 formaldehyde ...% - CAS: 50-00-0
 Worker Industry: 9 mg/m³ - Worker Professional: 9 mg/m³ - Consumer: 3.2 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 0.5 mg/m³ - Worker Professional: 0.5 mg/m³ - Consumer: 0.1 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, local effects
 Worker Industry: 1 mg/m³ - Worker Professional: 1 mg/m³ - Exposure: Human Inhalation
 - Frequency: Short Term, systemic effects
 Worker Industry: 240 mg/kg - Worker Professional: 240 mg/kg - Consumer: 102 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 4.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter
 <= 10 µm] - CAS: 13463-67-7
 Target: Fresh Water - Value: 0.184 mg/l
 Target: Marine water - Value: 0.0184 mg/l
 Target: Intermittent emission - Value: 0.61 mg/l
 Target: Freshwater sediments - Value: 1000 mg/kg
 Target: Marine water sediments - Value: 100 mg/kg
 Target: Microorganisms in sewage treatments - Value: 100 mg/l
 Target: Soil (agricultural) - Value: 100 mg/kg
 Target: Food chain - Value: 1667 mg/kg

xylene [4] - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.327 mg/l
 Target: Marine water - Value: 0.327 mg/l
 Target: Intermittent emission - Value: 0.327 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg
 Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Soil (agricultural) - Value: 2.31 mg/kg

ethylbenzene - CAS: 100-41-4
 Target: Fresh Water - Value: 0.1 mg/l
 Target: Marine water - Value: 0.01 mg/l
 Target: Freshwater sediments - Value: 13.7 mg/kg
 Target: Marine water sediments - Value: 1.37 mg/kg
 Target: Intermittent emission - Value: 0.1 mg/l
 Target: Microorganisms in sewage treatments - Value: 9.6 mg/l
 Target: Soil (agricultural) - Value: 2.68 mg/kg

isobutyl acetate [2] - CAS: 110-19-0
 Target: Fresh Water - Value: 0.17 mg/l
 Target: Marine water - Value: 0.017 mg/l
 Target: Intermittent emission - Value: 0.34 mg/l
 Target: Microorganisms in sewage treatments - Value: 200 mg/l
 Target: Freshwater sediments - Value: 0.877 mg/kg
 Target: Marine water sediments - Value: 0.0877 mg/kg
 Target: Soil (agricultural) - Value: 0.0755 mg/kg

n-butyl acetate - CAS: 123-86-4
 Target: Fresh Water - Value: 0.18 mg/l
 Target: Marine water - Value: 0.018 mg/l
 Target: Intermittent emission - Value: 0.36 mg/l
 Target: Freshwater sediments - Value: 0.98 mg/kg
 Target: Marine water sediments - Value: 0.098 mg/kg
 Target: Microorganisms in sewage treatments - Value: 35.6 mg/l
 Target: Soil (agricultural) - Value: 0.09 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 Target: Fresh Water - Value: 0.635 mg/l

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

- Target: Marine water - Value: 0.0635 mg/l
- Target: Intermittent emission - Value: 6.35 mg/l
- Target: Microorganisms in sewage treatments - Value: 100 mg/l
- Target: Freshwater sediments - Value: 3.29 mg/kg
- Target: Marine water sediments - Value: 0.329 mg/kg
- Target: Soil (agricultural) - Value: 0.29 mg/kg
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 - Target: Fresh Water - Value: 0.006 mg/l
 - Target: Marine water - Value: 0.0006 mg/l
 - Target: Freshwater sediments - Value: 2.46 mg/kg
 - Target: Marine water sediments - Value: 0.25 mg/kg
 - Target: Soil (agricultural) - Value: 0.28 mg/kg
- Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 - Target: Fresh Water - Value: 0.0012 mg/kg
 - Target: Marine water - Value: 0.00012 mg/kg
 - Target: Freshwater sediments - Value: 11 mg/kg
 - Target: Marine water sediments - Value: 1.1 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 10 mg/l
 - Target: Soil (agricultural) - Value: 2.54 mg/kg
- octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 - Target: Fresh Water - Value: 0.00044 mg/l
 - Target: Marine water - Value: 0.000044 mg/l
 - Target: Freshwater sediments - Value: 0.128 mg/kg
 - Target: Marine water sediments - Value: 0.013 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 10 mg/kg
 - Target: Soil (agricultural) - Value: 0.136 mg/kg
- Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6
 - Target: Freshwater sediments - Value: 13 mg/kg
 - Target: Marine water sediments - Value: 1.3 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 1 mg/kg
 - Target: Soil (agricultural) - Value: 3.77 mg/kg
- formaldehyde ...% - CAS: 50-00-0
 - Target: Fresh Water - Value: 0.47 mg/l
 - Target: Marine water - Value: 0.47 mg/l
 - Target: Freshwater sediments - Value: 2.44 mg/kg
 - Target: Marine water sediments - Value: 2.44 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 0.19 mg/l
 - Target: Soil (agricultural) - Value: 0.21 mg/kg
- Biological Exposure Index
 - xylene [4] - CAS: 1330-20-7
 - Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn
 - ethylbenzene - CAS: 100-41-4
 - Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and acid fenilgliossalico - Sampling Period: End of turn; End of working week
- Appropriate engineering controls
 - None
- Individual protection measures, such as personal protective equipment (PPE)
 - Eye protection:
 - Eye glasses with side protection. (EN166)
 - Protection for skin:
 - Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
 - Protection for hands:
 - Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)
 - Respiratory protection:
 - Use adequate protective respiratory equipment.

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Thermal Hazards:
None

9. Physical and chemical properties

Appearance and colour: white fluid
Odour: typical
Odour threshold: N.D.
pH: Not Relevant
Melting point / freezing point: N.D. °C
Initial boiling point and boiling range: > 110 °C
Flash point: < 23 °C
Evaporation rate: N.D.
Solid/gas flammability: N.A.
Upper/lower flammability or explosive limits: 7.0% - 0.9% Vol. (Xylene)
Vapour pressure: N.D. (20 °C)
Vapour density: > 1
Relative density: 1.320 - 1.350
Solubility in water: N.D.
Solubility in oil: partial
Partition coefficient (n-octanol/water): N.D.
Auto-ignition temperature: > 300 °C
Decomposition temperature: N.D. °C
Viscosity: N.D.

10. Stability and reactivity

Reactivity
It may generate dangerous reactions (See subsections below)
Chemical stability
It may generate dangerous reactions (See subsections below)
Possibility of hazardous reactions
It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.
Conditions to avoid
Avoid accumulating electrostatic charge.
Incompatible materials
Avoid contact with combustible materials. The product could catch fire.
Hazardous decomposition products
None.

11. Toxicological information

Information on toxicological effects
Toxicological information of the product:
CHROMOGLOSS Lucido PU bianco - PU White glossy finish
a) acute toxicity
Not classified
No data available for the product
b) skin corrosion/irritation
The product is classified: Skin Irrit. 2 H315
c) serious eye damage/irritation
The product is classified: Eye Irrit. 2A H319
d) respiratory or skin sensitisation
Not classified
No data available for the product
e) germ cell mutagenicity
Not classified
No data available for the product
f) carcinogenicity

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Not classified

No data available for the product

g) reproductive toxicity

The product is classified: Repr. 2 H361

h) STOT-single exposure

Not classified

No data available for the product

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat > 3.5 mg/l - Duration: 4h

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 6.7 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 1100 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat = 17.2 mg/l - Duration: 1h

i) STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401

Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403

Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 10760 mg/kg - Source: OECD 423

Test: LC50 - Route: Inhalation - Species: Rat > 21 mg/l - Duration: 4h - Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.5 mg/l - Duration: 4h

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 1570 mg/kg

Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: OECD 423

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 12.17 mg/l - Duration: 4h

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 mg/kg
formaldehide ...% - CAS: 50-00-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 100 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 588 mg/m³ - Duration: 4h

Test: LC50 - Route: Skin - Species: Rabbit = 270 mg/l

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

Substance(s) listed on the NTP report on Carcinogens:

formaldehide ...%

acetaldehyde; ethanal

1,4-dioxane.

Substance(s) listed on the IARC Monographs:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - Group 2B

xylene [4] - Group 3

ethylbenzene - Group 2B

formaldehide ...% - Group 1

acetaldehyde; ethanal - Group 2B

1,4-dioxane - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):

formaldehide ...%.

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]

formaldehide ...%

acetaldehyde; ethanal

1,4-dioxane.

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Not classified for environmental hazards

No data available for the product

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day
 Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96
- isobutyl acetate [2] - CAS: 110-19-0
- a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Algae = 370 mg/l - Duration h: 72 - Notes: OCSE 201
 Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202
 Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)
- n-butyl acetate - CAS: 123-86-4
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203
 Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Algae = 200 mg/l - Duration h: 72
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96 - Notes: OECD 201
 Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: OECD 203
 Endpoint: LC50 - Species: Daphnia = 408 mg/l - Duration h: 48
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Fish = 47.5 mg/l - Notes: 14d OECD 204
 Endpoint: NOEC - Species: Daphnia > 100 mg/l - Notes: 21d OECD 211
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
- a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Algae = 7.89 mg/l - Duration h: 72 - Notes: OECD 201
- Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3
- a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Daphnia = 15.2 mg/l - Duration h: 48 - Notes: OECD TG 202
 Endpoint: EC50 - Species: Algae = 7.43 mg/l - Duration h: 72 - Notes: OECD TG 201
 Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: OECD 203
- formaldehyde ...% - CAS: 50-00-0
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 6.7 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Daphnia = 5.8 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae > 3.48 mg/l - Duration h: 72
- Persistence and degradability
- xylene [4] - CAS: 1330-20-7
 Biodegradability: Readily biodegradable
- ethylbenzene - CAS: 100-41-4
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80
- isobutyl acetate [2] - CAS: 110-19-0
 Biodegradability: Readily biodegradable
- n-butyl acetate - CAS: 123-86-4
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83 - Notes: OECD 301F
- Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) - CAS: 147900-93-4
 Biodegradability: Non-readily biodegradable
- Fatty acids, tall-oil, compds. with oleylamine - CAS: 85711-55-3
 Biodegradability: Readily biodegradable
- Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD 310
- octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310

Dodecamethylcyclotetrasiloxane (D6) - CAS: 540-97-6
Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 4.47 - Notes: OECD 310

Bioaccumulative potential

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
Bioaccumulation: Bioaccumulative

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
Bioaccumulation: Bioaccumulative

Dodecamethylcyclotetrasiloxane (D6) - CAS: 540-97-6
Bioaccumulation: Bioaccumulative

Mobility in soil
N.A.

Other adverse effects
None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information



UN number

TDG number:	UN1263
ADR-UN Number:	1263
DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263

UN proper shipping name

TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
IATA-Shipping Name:	PAINT
IMDG-Shipping Name:	PAINT

Transport hazard class(es)

TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	33
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3

Packing group

TDG Packing group:	II
ADR-Packing Group:	II
DOT Packing group:	II
IATA-Packing group:	II
IMDG-Packing group:	II

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

Rail (RID): 3

TDG Special provisions: 59,142

DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28

ADR-Subsidiary hazards: -

ADR-S.P.: 163 367 640D 650

ADR-Transport category (Tunnel restriction code): 2 (D/E)

IATA-Passenger Aircraft: 353

IATA-Subsidiary hazards: -

IATA-Cargo Aircraft: 364

IATA-S.P.: A3 A72 A192

IATA-ERG: 3L

IMDG-EmS: F-E , S-E

IMDG-Subsidiary hazards: -

IMDG-Stowage and handling: Category A

IMDG-Segregation: -

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

xylene [4] is listed in NPRI Part 5

ethylbenzene is listed in NPRI Part 1, Group A

n-butyl acetate is listed in NPRI Part 5

2-methoxy-1-methylethyl acetate is listed in NPRI Part 5

formaldehyde ...% is listed in NPRI Part 5

acetaldehyde; ethanal is listed in NPRI Part 1, Group A

1,4-dioxane is listed in NPRI Part 1, Group A.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] is listed in TSCA Section 8b

xylene [4] is listed in TSCA Section 8b

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR

isobutyl acetate [2] is listed in TSCA Section 8b

n-butyl acetate is listed in TSCA Section 8b

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Propylidynetrimethanol is listed in TSCA Section 8b

Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen-1-amine, (Z) is listed in TSCA Section 8b

Fatty acids, tall-oil, compds. with oleylamine is listed in TSCA Section 8b

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

8a - PAIR, Section 8b, Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

formaldehyde ...% is listed in TSCA Section 8b

acetaldehyde; ethanal is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR

1,4-dioxane is listed in TSCA Section 8b, Section 8a - CAIR.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: formaldehyde ...%.

Section 304 – Hazardous substances: xylene [4], ethylbenzene, isobutyl acetate [2], n-butyl acetate, formaldehyde ...%, acetaldehyde; ethanal, 1,4-dioxane.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene, formaldehyde ...%, acetaldehyde; ethanal, 1,4-dioxane.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

n-butyl acetate - Reportable quantity: 5000 pounds

formaldehyde ...% - Reportable quantity: 100 pounds

acetaldehyde; ethanal - Reportable quantity: 1000 pounds

1,4-dioxane - Reportable quantity: 100 pounds.

Reportable quantity for mixture: 604.4852808 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

n-butyl acetate is listed in CAA Section 111

Propylidynetrimethanol is listed in CAA Section 112(b) - HON

formaldehyde ...% is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON, Section 112(r)

acetaldehyde; ethanal is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON, Section 112(r)

1,4-dioxane is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

isobutyl acetate [2] is listed in CWA Section 311

n-butyl acetate is listed in CWA Section 304, Section 311

formaldehyde ...% is listed in CWA Section 311

acetaldehyde; ethanal is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - Listed as carcinogen

ethylbenzene - Listed as carcinogen

formaldehyde ...% - Listed as carcinogen

acetaldehyde; ethanal - Listed as carcinogen

1,4-dioxane - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

diameter <= 10 µm]
xylene [4]
ethylbenzene
isobutyl acetate [2]
n-butyl acetate
formaldehyde ...%
acetaldehyde; ethanal
1,4-dioxane.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]
xylene [4]
ethylbenzene
isobutyl acetate [2]
n-butyl acetate
formaldehyde ...%
acetaldehyde; ethanal
1,4-dioxane.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]
xylene [4]
ethylbenzene
isobutyl acetate [2]
n-butyl acetate
formaldehyde ...%
acetaldehyde; ethanal
1,4-dioxane.

Volatile Organic compounds - VOCs = 28.61 %
Volatile Organic compounds - VOCs = 386.29 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.23

16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H302 Harmful if swallowed.
H411 Toxic to aquatic life with long lasting effects.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H413 May cause long lasting harmful effects to aquatic life.
H350 May cause cancer.
H341 Suspected of causing genetic defects.
H301 Toxic if swallowed.

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

H311 Toxic in contact with skin.
H331 Toxic if inhaled.
H314 Causes severe skin burns and eye damage.
H224 Extremely flammable liquid and vapour.
H351 Suspected of causing cancer.

Safety Data Sheet dated 6/6/2022, version 2
Sections modified from the previous revision:

2. Hazard identification
3. Composition/Information on ingredients
6. Accidental release measures
7. Handling and storage
8. Exposure controls/personal protection
9. Physical and chemical properties
11. Toxicological information
12. Ecological information
14. Transport information
15. Regulatory information

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.

Safety Data Sheet

LGP501 CHROMOGLOSS Lucido PU bianco - PU White glossy finish

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average