



TIP-ON BLUMOTION for LEGRABOX and MOVENTO combines the advantages of the TIP-ON mechanical opening support system with reliable BLUMOTION dampening for silent and effortless closing – 100% mechanically.

Ablum



































Clear programme

The basis of TIP-ON BLUMOTION is the specially designed LEGRABOX cabinet profile or MOVENTO runner. All other product components are compatible with both pull-out systems. The large number of standard parts form a compact programme that opens up a wide range of possibilities when designing handle-less furniture.





Fittings selection made easy with the online product configurator at www.blum.com/configurator



Well-designed product details

Many of the TIP-ON BLUMOTION components can be used for both LEGRABOX and MOVENTO. This means that TIP-ON BLUMOTION is a suitable solution for any application.

Ablum

TIP-ON BLUMOTION for pull-out systems

It is possible to use a wide range of nominal lengths with the pull-out systems for LEGRABOX and MOVENTO. The pull-outs and drawers impress with their stability and load bearing capacity.

TIP-ON BLUMOTION LEGRABOX cabinet profile

40 and 70 kg Nominal length (NL) 270 to 650 mm



40 and 60 kg Nominal length (NL) 270 to 750 mm




TIP-ON BLUMOTION units and TIP-ON BLUMOTION latch

Adjusted for weight ranges and nominal lengths, the TIP-ON BLUMOTION unit is available in designs of varying strengths. For easy differentiation, each version is a different colour. The latch can be universally used for all TIP-ON BLUMOTION units.



TIP-ON BLUMOTION synchronization

An extensive trigger range is achieved even with a low minimum front gap of 2.5 mm. To extend the trigger range, it is recommended that synchronization should be used for cabinet widths of 400 mm and above.





Shown in the diagram by way of example for height C, nominal length 500 mm with front stabilizer



Order specification







2a + 2b Set containing TIP-ON BLUMOTION unit and TIP-ON BLUMO Can be used for: Nominal length (NL) Unit Part number 270 mm S0 T60L7040 S1 T60L7140 350-650 mm L1 T60L7340 L3 T60L7540 L5

TION latch							
Recommended weight ranges* for an optimum opening and closing function							
< 10 l	kg	20 kg	30 kg	40 kg	50 kg	60 kg	70 kg
≤ 10)						
		> 10–20					
	≤ 2	20					
			5-40				
					25–70)	
	Reco for ar	Recomme for an opti <10 kg ≤10	Recommended weight for an optimum openition of the second	Recommended weight ranges* for an optimum opening and clos <10 kg 20 kg 30 kg ≤10 >10-20 ≤20	Recommended weight ranges* for an optimum opening and closing function <10 kg 20 kg 30 kg 40 kg ≤10 >10-20 ≤20	Recommended weight ranges* for an optimum opening and closing function <10 kg 20 kg 30 kg 40 kg 50 kg ≤10 >10-20 ≤20 5-40	Recommended weight ranges* for an optimum opening and closing function <10 kg 20 kg 30 kg 40 kg 50 kg 60 kg ≤10 >10-20 ≤20

3	TIP-ON BLUMOTION synchronization adapter	
	Symmetrical, in combination with synchronization linkage, two items required per synchronization linkage,	
	for internal cabinet width ≥ 294 mm	T60.000D

4	TIP-ON BLUMOTION round synchronization linkage for cutting to size	
	Recommended with cabinet widths ≥ 400 mm.	
	Suitable for cabinet widths of up to 1400 mm	T60.1125W


Accessories		
	TIP-ON BLUMOTION front gap template	
	Setting the front gap to 2.5 mm	65 5631

* Total weight of the pull-out

TIP-ON BLUMOTION for LEGRABOX




Planning





- TIP-ON BLUMOTION for LEGRABOX uses the same standard installation dimensions as for LEGRABOX. Please refer to the relevant product brochure or catalogue for this information
- The following planning graphics are shown as an example for a drawer with height M



More information on LEGRABOX: www.blum.com/ downloadslegrabox











Assembly

TIP-ON BLUMOTION for LEGRABOX












îblum










Assembly


TIP-ON BLUMOTION for LEGRABOX

Synchronization recommended for cabinet widths of 400 mm and above












TIP-ON BLUMOTION for LEGRABOX

Assembly

ablum










Removal


TIP-ON BLUMOTION for LEGRABOX


pblum°














Order specification

TIP-ON BLUMOTION for MOVENTO



1	TIP-ON BLUMOTION runi	ner MOVENTO le	ft/right
A	Nominal length (NL)	40 kg	60 kg
	270 mm	760H2700M	
	300 mm	760H3000M	
	350 mm	760H3500M	
	400 mm	760H4000M	
	450 mm	760H4500M	766H4500 M
	500 mm	760H5000M	766H5000M
	550 mm	760H5500M	766H5500M
	600 mm	760H6000M	766H6000 M
	650 mm		766H6500M
	700 mm		766H7000 M
	750 mm		766H7500M

2	Left/right locking device	
	Order locking device separately	
	Left	T51.7601
	Right	T51.7601

3a + 3b	Set containing TIP-ON B	LUMOTION unit a	and TIP-ON BLU
	Can be used for:		
To go	Nominal length (NL)	Unit	Part number
	270-300 mm	S0	T60L7040
		S1	T60L7140
	350-750 mm	L1	T60L7340
		L3	T60L7540
		L5	T60L7570

UMO	UMOTION latch							
	Recommended weight ranges* for an optimum opening and closing function							
r	< 10 kg	20 kg	30 kg	40 kg	50 kg	60 kg		
	≤10							
		> 10–20						
	≤:	20						
			5-40					
					25–60			

4	TIP-ON BLUMOTION synchronization adapter	
	Symmetrical, in combination with synchronization linkage, two items required per synchronization linkage,	
	for internal cabinet width ≥ 314 mm	T60.000D

5	TIP-ON BLUMOTION round synchronization linkage for cutting to size	
	Recommended with cabinet widths ≥ 400 mm.	
	Suitable for cabinet widths of up to 1400 mm	T60.1125W


Accessories		
	TIP-ON BLUMOTION front gap template	
	Setting the front gap to 2.5 mm	
		65.5631

* Total weight of the pull-out

TIP-ON BLUMOTION for MOVENTO



Planning



- TIP-ON BLUMOTION for MOVENTO uses the same standard installation dimensions as for MOVENTO. Please refer to the relevant product brochure or catalogue for this information
- The following planning graphics are shown as an example for a drawer




More information on MOVENTO: www.blum.com/runner_movento

Front assembly - do not install bumpers





Bumpers should not be installed for TIP-ON BLUMOTION!

Space requirements in the cabinet



Drawer/inner drawer








- * + 1 mm for assembly of the cabinet profile on the horizontal cabinet side
- ** Limited side adjustment for a drawer side panel thickness of 16 mm, but with full tolerance utilization of the internal width of the drawer.

Planning


TIP-ON BLUMOTION for MOVENTO









îblum










Assembly


TIP-ON BLUMOTION for MOVENTO

Synchronization recommended for cabinet widths of 400 mm and above












TIP-ON BLUMOTION for MOVENTO

Assembly

îblum










Removal


TIP-ON BLUMOTION for MOVENTO


iblum



















Blum in Austria and around the world

The company has seven plants in Vorarlberg, Austria, additional production sites in Poland, the USA and Brazil and 27 subsidiaries/representative offices. Blum supplies more than 120 markets. The Blum Group employs 6.600 people in total, 5.000 of whom work in Vorarlberg.

Global customer benefits

"Whether manufacturer, distributor, fitter or kitchen user
- everybody should personally
enjoy the benefits of Blum products" – that is Blum's philosophy
on global customer benefits.

Innovations

To support customers with innovative fittings solutions and secure long-term success for the company, we need to consistently invest in research and development, in plants and facilities and in employee training. With more than 1200 registered trademarks around the world, Blum is one of Austria's most innovative companies.







Quality

At Blum, the comprehensive concept of quality does not only apply to products. Services and our cooperation with customers and partners should also meet the same quality requirements.

Environment

At Blum, we believe that responsible ecological behaviour has long-term economic benefits. The longevity of products is just one of many important aspects. Other important measures include the use of environmentally friendly processes, the intelligent use of materials and prudent energy management.





DYNAMIC SPACE

Good workflows, optimum use of storage space and high quality of motion are important features of a practical kitchen. Blum's ideas for practical kitchen are designed to bring function, convenience and ergonomics to furniture interiors.



Blum Canada Ltd. 7135 Pacific Circle Mississauga, ON, L5T 2A8

Tel.: 905-670-7920 Fax: 905-670-7929

Long Dist.: 1-800-670-9254 E-mail: info.ca@blum.com



