

## TECHNICAL DATA

PRODUCT	<b>LXA 104</b>
DEFINITION	ADHESION ADDITIVE FOR GLASS

---

### **MAIN FIELD OF USE:**

Liquid additive to be added to transparent and pigmented paints to increase their adhesion on inorganic substrates such as glass.

---

### **CHEMICAL-PHYSICAL PROPERTIES:**

SPECIFIC WEIGHT	910 ± 10 gr. / lt.
-----------------	--------------------

---

### **METHOD OF USE:**

LXA104 should be added at 10% by weight to polyurethane and acrylic paints immediately before their use as the effectiveness of the additive as an adhesion agent decreases in 6-12 hours from incorporation.

LXA104 is an additive, so it does not replace the use of the specific hardener, but must be used in addition to it.

Thoroughly clean the glass surfaces before painting, using alcohol or specific products before application.

Due to the wide variety of glass types on the market, always perform adhesion tests before starting production.

---

### **STORAGE:**

The product, stored in the original cans tightly closed, preferably at a temperature between 10 and 30°C, has a shelf life of 12 months.

---

T.d.s. LXA104 – 2020, November – revision 1

**IMPORTANT:** The information contained in this technical data sheet are based on the average results obtained in our laboratories and is the best experience we have acquired in the most rigorous manner, thorough tests and checks.

**Nuova S.I.V.A.M.** guarantees the consistency of the chemical/physical characteristics of its products within the tolerances indicated above.

The final result is the full responsibility of the user who, before using the product, must check that it meets his requirements in terms of safety, application equipment, support material to paint, and environmental conditions.

The information given herein is based on a temperature of 20°C/68°F and 70% of relative humidity.

**Nuova S.I.V.A.M.** technical and commercial network is at your complete disposal to deal with any questions regarding how to correctly apply and use our products.