

SAFETY DATA SHEET

ULTIMATE CONTACT ADHESIVE 500ml AEROSOL

NON CHLORINATED, HIGH TEMPERATURE

SECTION 1; IDENTIFICATION OF THE SUBSTANCES/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name BONDSEAL ULTIMATE
Product No. BONDSEAL 2091 500ml

1.2. Relevant identified uses of the substances or mixture and uses advised against

Identified uses Spray adhesive

1.3. Details of the supplier of the data sheet

Company name: Chemique Adhesives Inc

3050 Matlock Drive

Kennesaw, GA 30144 USA Tel: +1 990 451 2904 Fax: +1 990 234 4143

Email: sales@chemiqueadhesives.com

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and chemical hazards Extremely Flam. Aerosol - H222

Human health Eye Irrit. 2 – H319

STOT SE 3 – H336 Skin Irrit 2 – H315 Asp Tox 1 – H304

Environmental hazards Aquat Chron 2 – H412

The full text for all Hazard statements are displayed in Section 16.

2.2 Label Elements

Label in Accordance with (EC) No. 1272/2008

Contains Cyclohexane, Acetone, Naphtha petroleum hydrotreated light, <0.1% Benzene, Hexane





| | | • |
|-----------------------------|--------------|---|
| Signal word | Danger | |
| Hazard statements | | |
| | H222 | Extremely flammable aerosol. |
| | H229 | Pressurized container: may burst if heated |
| | H304 | May be fatal if swallowed and enters airways |
| | H315 | Causes skin irritation |
| | H319 | Causes serious eye irritation. |
| | H336 | May cause drowsiness or dizziness. |
| | H412 | Harmful to aquatic life with long lasting effects |
| Precautionary Statements | | |
| | P102 | Keep out of reach of children. |
| | P210 | Keep away from heat/sparks/open flames/hot surfaces, No Smoking |
| | P261 | Avoid breathing vapour/spray. |
| | P281 | Use personal protective equipment as required |
| | P337+313 | If eye irritation persists: Get medical advice/attention. |
| | P270 | Do not eat, drink, or smoke when using this product |
| Supplementary precautionary | statements | |
| | P273 | Avoid release to the environment. |
| | P264 | Wash contaminated skin thoroughly after handling. |
| | P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in |
| | | Position comfortable for breathing. |
| | P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes |
| | | Remove contact lenses, if present and easy to do. Continue |
| | | rinsing |
| | P308+313 | If exposed or concerned: Get medical advice/attention. |
| | P332+313 | If skin irritation occurs: get medical advice/attention |
| | P337+313 | If eye irritation persists: get medical advice/attention |
| | P410+412 | Protect from sunlight. Do not expose to temperatures |
| | | Exceeding 50°C/122°F. |
| | P342+311 | If experiencing respiratory symptoms: Call a POISON CENTRE or Doctor/physician. |
| | P501 | Dispose of contents/container in accordance with local regulations. |
| | | |

Supplement label information

No data available

2.3. Other hazards

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on naked flame or any incandescent material – NO SMOKING.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

ACETONE 15-30%

CAS-No.: 67-64-1 EC No.: 200-662-2 Registration number: 01-2119471330-49

Index No:606-001-00-8

Classification (EC 1272/2008)

Flam. Liq. 2 – H225 STOT SE 3 – H336 Eye irrit. 2 – H319

CYCLOHEXANE 15-30%

CAS- No: 110-82-7 EC No.: 203-806-2

Classification (EC 1272/2008)

Flam Liq 2 - H225

Skin Irrit 2 - H315

STOT SE 3 - H336

Asp Tox 1 – H304

Aquatic Acute 1 – H400

Aquatic Chronic 1 – H410

NAPHTHA, PETROLEUM, HYDROTREATED LIGHT

5<15%

CAS- No: 64742-49-0

Classification (EC 1272/2008)

STOT SE 3 - H336

Asp Tox 1 – H304

Skin Irrit 2 – H315

Aquat Chron 2 – H411

HEXANE 0.5<2%

EC No.: 265-151-9

CAS – No.: 110-54-3 EC No.: 203-777-6

Classification (EC 1272/2008)

Skin Irrit 2 – H315

Repr 2 - H361f

STOT SE 3 – H336

STOT RE 2 - H373

Asp Tox 1 – H304

Aquat Chron 2 – H411

Flam Liq 2 – H225

PETROLEUM GASES LIQUIFIED 20-40%

Classification (EC 1272/2008)

Flam. Gas 1- H220

The full text for all hazard statements are displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately

Skin contact

Wash the skin immediately with soap and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling section 2.2, and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Extinguishing media

Fire can be extinguished using: foam; carbon dioxide; dry powder

5.2 Special hazards arising from the substance or mixture

Unusual fire & Explosion hazards

Aerosol cans may explode in fire.

5.3 Advice for firefighters

Wear self contained breathing apparatus

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Avoid breathing vapours, mist or gas. Wear personal protective equipment (see section 8).

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environment Agency or other regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3 Methods and material for containment and cleaning up

Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth, and place into containers.

6.4 Reference to other sections

Wear protective clothing as described in section 8 of this safety data sheet.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3 Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

| Name | STD | TWA – 8 H | Irs | STEL - 1 | 5 Min | Notes |
|-----------------|-----|-----------|----------|----------|-------|--------------------|
| ACETONE | WEL | 500 ppm | 1210 | 1500 | 3620 | UK EH40 – |
| | | | mg/m3 | ppm | mg/m3 | Workplace Exposure |
| | | | | | | Limits |
| PETROLEUM GASES | WEL | 1000 | 1250 | 1250 | 2180 | UK EH40 – |
| LIQUIFIED | | ppm | mg/m3 | ppm | mg/m3 | Workplace Exposure |
| | | | | | | Limits |
| CYCLOHEXANE | WEL | 200 | 700 | 300 | 1050 | UK EH40 – |
| | | ppm | mg/m3 | ppm | mg/m3 | Workplace Exposure |
| | | | | | | Limits |
| HEXANE | WEL | 20 ppm | 72 mg/m3 | | | |

WEL = Workplace exposure limit.

Derived No Effect Level (DNEL)No data available **Predicted No Effect Concentration**No data available

8.2 Exposure controls

Protective equipment

Engineering measures









Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Chemical splash goggles or face shield. Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU).

Hand protection

Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Nitrile rubber.

Other skin and body protection

Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Wear protective clothing.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| Canister/Aerosol. |
|--------------------|
| No data available |
| Estimated at -17°C |
| No data available |
| No data available |
| |

(j) Upper/lower flammability

Or explosive limits

(k) Vapour pressure

(l) Vapour density

(m) Relative density

No data available

No data available

(n) Water solubility Slightly soluble in water

(o) Partition coefficient

n-octanol/waterNo data available(p) Auto-ignition temperatureNo data available(q) Decomposition temperatureNo data available(r) ViscosityNo data available(s) Explosive propertiesNo data available(t) Oxidising propertiesNo data available

9.2 Other information

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Avoid heat, sparks, and flames, stable under normal conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Avoid heat, flames and other sources or ignition. Avoid contact with: Strong oxidising agents, Strong alkalis and Strong mineral acids.

10.5 Incompatible materials

Materials to avoid

Strong acids, strong oxidising substances and strong alkalis.

10.6 Hazardous decomposition products

No data available

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acetone

Acute Toxicity

LD50 Oral - Rat - >5,800 mg/kg

Inhalation

LD₅₀ Inhalation – Rat – 50,1000 mg/m³

Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritaion - 24 h

(Draize Test)

Eye contact

Eyes - Rabbit

Result: Irritating to eyes - 24 hr

(Draize Test)

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP or EPA classification.

Specific Target Organ Toxicity – Single Exposure

No data available

Chemique Adhesives Inc. REV 4.2 July 2023

Specific Target Organ Toxicity – Repeated Exposure

No data available

Aspiration Hazard

No data available.

Cyclohexane

Acute Toxicity

LD50 Oral – Rat - 12,705 mg/kg LD50 Dermal – Rabit ->2,000 mg/kg

Inhalation

LD₅₀ Inhalation – Rat – 34,000 mg/m³ - 4 h (OECD Test Guideline 403)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritaion - 24 h

(Draize Test)

Eye contact

Eyes - Rabbit

Result: Mild irritation

(Draize Test)

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC classification.

Specific Target Organ Toxicity - Single Exposure

No data available

Specific Target Organ Toxicity - Repeated Exposure

No data available

Aspiration Hazard

No data available.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous to the environment. However, contamination of the aquatic or terrestrial environments should be avoided

12.1 Toxicity

<u>Acetone</u>

Toxicity to fish LC50 – Oncorhynchus mykiss (rainbow trout) – 5.540 mg/l – 96 hr

Toxicity to daphnia and other

Aquatic invertebrates: EC50 – Daphnia magna (Water flea) – 8,800 mg/l – 48 hr

Cyclohexane

Toxicity to fish LC50 – Pimpephalespromelas (Fathead minnow) – 4.53 mg/l – 96 hr

(OECD Test Guideline 203)

Toxicity to daphnia and other

Aquatic invertebrates: EC50 – Daphnia magna (Water flea) – 0.9 mg/l – 48 hr

(OECD Test Guideline 202)

Toxicity to algae EC50 – Pseudokirchneriella subcapitata (Green algae) – 304mg/l – 72 h

(OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability No data available

12.3 Bio accumulative potential

Does not bioaccumulate

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB Assessment

Contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1 UN Number

CEFIC TEC® No

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2 UN proper shipping name

Proper shipping name - AEROSOLS

14.3 Transport hazard class(es)

ADR/RID/ADN class 2.1

ADR/RID/ADN class

ADR Label No

IMDG Class

ICAO Class/division

ICAO Subsidiary risk

Class 2: Gases
2.1 & 6.1

20GSF

Chemique Adhesives Inc. REV 4.2 July 2023

Air Class 2.1
UK Road Class 2.1
Transport labels L.Q.



14.4 Packing group

Not applicable.

14.5 Environmental hazards

Environmentally hazardous substance/marine pollutant.

No.

14.6 Special precautions for user

EMS F-D, S-U
Tunnel restriction code (D)

14.7 transport in bulk according to Annex II of MARPOL73/78 and the IBC code.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Labelling according to Regulation (EC) No 1272/2008

The chemicals (Hazard information and packaging for supply) regulations 2009 (S.I 2009 No. 716). Control of substances hazardous to health.

Approved code of practice.

Guidance notes

Workplace exposure limits EH40.

15.1.1 EU-Regulations

EU-REACH (1907/2006) – Candidate List of Substances of Very High Concern (SVHC) for Authorisation in accordance with Article 59.

This product does not contain candidate substances of very high concern at a concentrations >=0.1% (Regulation (EC) No 1907/2006 (REACH), Article 59.

EU-REACH (1907/2006)-Annex XVII – Substances subject to restrictions.

This product contains one or more substance(s) subject to restriction (Regulation (EC) No 1907/2006 (REACH), Annex XVII

| Chemical Name | CAS No | Restrictions on use |
|---------------|----------|---------------------|
| Cyclohexane | 110-82-7 | 57 |

If supplied in neoprene contact adhesives to general public above 0.1% CAS 110-87-7 must be labelled as per restriction. Must not be supplied to general public in contact adhesive above 0.1% in packages greater than 350gm.

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorisation

This product does not contain substances subject to Authorisation (Regulation (EC) No 1907/2006 (REACH) Annex XIV)

15.1.2 National Regulations

No additional information available.

SECTION 16: OTHER INFORMATION

General information

This product should be used as directed. For further information consult the product data sheet or contact technical services.

Information sources

This safety data sheet was compiled using current safety information supplied by distributor raw materials.

Revision comments

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact AFT Aerosols Ltd.

Hazard statements in full

| H220 | Extremely flammable gas |
|-------|---|
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness |
| H361f | Suspected of damaging fertility |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H411 | Toxic to aquatic life with long lasting effects |

Abbreviations

| Eye Irrit 2 | Eye Irritant Category 2 |
|---------------------|---------------------------------------|
| Skin Irrit 2 | Skin Irritant Category 2 |
| Flam Liq 2 | Flammable liquid Category 2 |
| Flam Gas 1 | Flammable Gas Category 1 |
| Asp Tox 1 | Aspiration Toxicity Category 1 |
| Repr 2 | Reproductive Toxicity Category 2 |
| Aquatic Acute 1 | Acute Aquatic Toxicity Category 1 |
| Aquatic Chronic 1/2 | Chronic Aquatic Toxicity Category 1/2 |
| | |

STOT SE 2/3 Specific Target Organ Toxicity Single Exposure Category 2/3
STOT RE 2 Specific Target Organ Toxicity Repeated Exposure Category 2

ISSUE: REV 4.2

REVISION DATE: JULY 2017
REVIEW DATE: JULY 2018

DISCLAIMER

The Information provided herein, especially recommendations for the usage and the application of this products, is provided in good faith, and no liability on the part of Chemique Adhesives Inc. is stated or implied. No employee of Chemique Adhesives Inc. has the authority to waive or alter in any way the content of this document.

Due to different materials used, as well as to varying working conditions, production techniques, and the requirements of the end users, all of which are beyond our control, we strongly recommend that thorough and extensive trials are carried out in order to test the suitability of our products with regard to the required processes and applications. This should also include an ageing test which should be applied to all substrates used.

It is also the responsibility of the purchaser and end user of this product to ensure that all appropriate actions necessary for the protection of the environment, and for the health and safety of their employees are observed. This datasheet replaces all former versions