

MEDIUM-FAST EVAP THINNER FOR PU

TT5250000

DESCRIPTION

TT5250000 Medium-Fast Evaporation Thinner for Polyurethane is a urethane grade thinner suitable for all urethane products. This product is HAPs FREE and contains esters and ketones.

PRODUCT DATA:

Color:	Wet: Clear Dry: n/a	VOC:	873 g/l or 7.28 lbs/gal
Solids % by Vol.:	00 % (Theoretical)	Lbs. VOC / Lbs. Solids:	n/a
Solids % by Wt.:	00 % (Theoretical)	Lbs. VHAPs / Lbs. Solids:	n/a (65 % by wt.)
Weight / Gal.:	7.28 lb	Flash Point (PMCC):	-7° C / 19° F
Spec. Gravity:	0.87	Frost Sensitivity	No
Viscosity 23°C / 73°F:	#4 Ford: n/a Sec.	Photo chemically Reactive:	Yes
Viscosity 23°C / 73°F:	DIN 4: n/a Sec.	Shelf Life:	2 years (at 15-25° C / 59-77° F)
Theoretical Coverage: n/a			

MIXING / APPLICATION:

Working Temp: >18° C, 65° F substrate, coating and air
Mixing: Add thinner after catalyst (if required). Avoid over mixing which may introduce air into the product.

TESTING: Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.
FOR INDUSTRIAL SHOP APPLICATION: Thoroughly review Safety Data Sheet (SDS) for safety information and cautions prior to using this product. For Regulatory compliance data (i.e. VOC, HAPS, etc.), obtain an Environmental Data Sheet (EDS) prior to using the product. Regulatory documents are available from your local distributor or representative. Please direct any questions or comments to 1-800-524-5979.
NOTE: Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, AcromaPro cannot make any warranties as to the end result.