

MATTING PASTE AC

ZZ5960200

DESCRIPTION:

Matting Paste AC is a solvent based matting paste for AcromaPro Acid Catalyzed products, both Precats and Postcats. Keep the container covered when not in use, as it will quickly dry and form lumps. Product with the matting paste added should always be filtered before use.

PRODUCT DATA:

Color:	Wet: Clear / Hazy Dry: N/A	VOC:	856 g/l or 7.14 lbs/gal
Solids % by Vol.:	6.71 % (Theoretical)	Lbs. VOC / Lbs. Solids:	3.12
Solids % by Wt.:	11.35 % (Theoretical)	Lbs. VHAPs / Lbs. Solids:	0
Weight / Gal.:	8.04 lb	Flash Point (PMCC):	25° C / 77° F
Spec. Gravity:	0.966	Frost Sensitivity	No
Viscosity 23°C / 73°F:	#4 Ford: Thixotropic	Photo chemically Reactive:	No
Viscosity 23°C / 73°F:	DIN 4: Thixotropic	Shelf Life:	1 year (at 15-25° C / 59°-77° F)
Theoretical Coverage: N/A			

MIXING / APPLICATION:

Working Temp:	>18° C, 65° F substrate, coating and air
Hardener:	N/A
Catalyzation:	N/A
Pot Life:	1 Year. (23° C / 73° F)
Mixing:	Add matting paste to product while mixing. Do not exceed 10% by weight addition.
Sealer:	N/A
Reducer:	N/A
Application:	N/A
Surface Prep:	N/A
Use Directions:	Keep container covered when not in use, as it will dry quickly, and form lumps. Product with the matting paste added should always be filtered before use.
App. Equip.:	N/A
Tinting:	N/A

DRYING TIMES TO SAND / STACK / CURE:

Method	Drying Temp.	Drying Time (@ 60 % RH and thickness @ 1 mil dry)
Air Drying	N/A	N/A
*Forced Drying	N/A	N/A

TESTING: Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.

FOR INDUSTRIAL SHOP APPLICATION: Thoroughly review Safety Data Sheet (SDS) for safety information and cautions prior to using this product. For Regulatory compliance data (i.e. VOC, HAPS, etc.), obtain an Environmental Data Sheet (EDS) prior to using the product. Regulatory documents are available from your local distributor or representative. Please direct any questions or comments to 1-800-524-5979.

NOTE: Product Data Sheets are periodically updated to reflect new information relating to the product. It is important that the customer obtain the most recent Product Data Sheet for the product being used. The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, AcromaPro cannot make any warranties as to the end result.