



The new generation of flexible LEDs!

### Milky flexible LED modules for recessed or surface installation

FLEXYLED AT6 is a 24 Vdc flexible linear LED strip developed using a new milky-effect diffusing silicone coating technology that cancels the characteristic spot effect light emitting diodes.

#### ADVANTAGES AND BENEFITS

- Recessed or surface mount installation
- The pre-wired 78 3/4" (2000 mm) double power cable configuration allows the cut part of any of the original modules to be recovered
- High-strength 3M® adhesive base
- Can be cut at 7/8" (22 mm) intervals

#### TECHNICAL SPECS

- Tension: 24 V dc
- Power: 10 W/m
- Color Rendering Index: CRI 90
- Splash proof rating: IP44
- LEDs/m: 276
- Radius minimum: 1" (25 mm)

No.	Watts	Color temperature (K)	Length
15102420012079	20 W	2700 super warm white	78 3/4" (2000 mm)
151024300120118	30 W	2700 super warm white	118 1/8" (3000 mm)
151024600120236	60 W	2700 super warm white	236 1/4" (6000 mm)
15102420012279	20 W	3000 warm white	78 3/4" (2000 mm)
151024300122118	30 W	3000 warm white	118 1/8" (3000 mm)
151024600122236	60 W	3000 warm white	236 1/4" (6000 mm)
15102420012479	20 W	4000 neutral white	78 3/4" (2000 mm)
151024300124118	30 W	4000 neutral white	118 1/8" (3000 mm)
151024600124236	60 W	4000 neutral white	236 1/4" (6000 mm)

Includes fastening hooks and screws for optional surface mount installation.

