

1 Identification

- **Product identifier**

- *Product number* LXC6AA1
- *Trade name:* **CLEAR PRE-CAT SEALER**
- *Application of the substance / the mixture* For professional use

- **Details of the supplier of the safety data sheet**

- *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
- *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
- *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Eye Irritation 2A	H319 Causes serious eye irritation.
Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Single Exposure 3	H336 May cause drowsiness or dizziness.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

- **Label elements**

- *GHS label elements*
The product is classified and labeled according to the Globally Harmonized System (GHS).
- *Hazard pictograms*



GHS02 GHS07 GHS08

- *Signal word* Danger

- *Hazard-determining components of labeling:*

ethyl acetate
xylene
isobutyl acetate
n-butyl acetate

- *Hazard statements*

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

- *Precautionary statements*

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 1)

P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**











3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture: consisting of the following components.

· **Dangerous components:**

141-78-6	ethyl acetate  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	20-24.99%
110-19-0	isobutyl acetate  Flammable Liquids 2, H225  Specific Target Organ Toxicity - Single Exposure 3, H336	15-19.99%
123-86-4	n-butyl acetate  Flammable Liquids 3, H226  Specific Target Organ Toxicity - Single Exposure 3, H336	12.5-15%
67-63-0	propan-2-ol  Flammable Liquids 2, H225  Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	5-9.99%

(Contd. on page 3)

US

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

		(Contd. of page 2)
71-36-3	butan-1-ol ⚠ Flammable Liquids 3, H226 👁 Eye Damage 1, H318 ⚠ Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	1-2.49%
1330-20-7	xylene ⚠ Flammable Liquids 3, H226 ⚠ Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	1-2.49%
100-41-4	ethylbenzene ⚠ Flammable Liquids 2, H225 ⚠ Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Inhalation 4, H332 Aquatic Chronic 3, H412	≥0.1-<0.5%
95-47-6	o-xylene ⚠ Flammable Liquids 3, H226 ⚠ Aspiration Hazard 1, H304 ⚠ Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	<0.5%
78-83-1	2-methylpropan-1-ol ⚠ Flammable Liquids 3, H226 👁 Eye Damage 1, H318 ⚠ Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H335-H336	<0.5%
50-00-0	formaldehyde ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331 ⚠ Germ Cell Mutagenicity 2, H341; Carcinogenicity 1B, H350 👁 Skin Corrosion 1B, H314 ⚠ Sensitization - Skin 1A, H317 Flammable Liquids 4, H227	<0.1%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

personal protective equipment for first aid responders is recommended. (please see section 8)

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

(Contd. on page 4)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; immediately call for medical help.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
For symptoms and effects caused by substances, refer to Section 11.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
Alcohol resistant foam
Alcohol resistant foam, CO, powder, water spray/mist.
 - **For safety reasons unsuitable extinguishing agents:**
Do not use a jet water stream as it may scatter and spread fire.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Carbon monoxide (CO)
- **Advice for firefighters**
Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.
 - **Protective equipment:**
Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to Section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

 · **PAC-1:**

141-78-6 ethyl acetate

1,200 ppm

(Contd. on page 5)

-US

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 4)

110-19-0	isobutyl acetate	450 ppm
123-86-4	n-butyl acetate	5 ppm
67-63-0	propan-2-ol	400 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
71-36-3	butan-1-ol	60 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
78-83-1	2-methylpropan-1-ol	150 ppm

· PAC-2:

141-78-6	ethyl acetate	1,700 ppm
110-19-0	isobutyl acetate	1300* ppm
123-86-4	n-butyl acetate	200 ppm
67-63-0	propan-2-ol	2000* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
71-36-3	butan-1-ol	800 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
78-83-1	2-methylpropan-1-ol	1,300 ppm

· PAC-3:

141-78-6	ethyl acetate	10000** ppm
110-19-0	isobutyl acetate	7500** ppm
123-86-4	n-butyl acetate	3000* ppm
67-63-0	propan-2-ol	12000** ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
71-36-3	butan-1-ol	8000** ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
78-83-1	2-methylpropan-1-ol	8000* ppm

7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Protect against electrostatic charges.

Keep respiratory protective device available.

Use explosion-proof apparatus / fittings and spark-proof tools.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 6)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 5)

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.
· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.
8 Exposure controls/personal protection
· Additional information about design of technical systems: No further data; see item 7.
· Control parameters
· Components with limit values that require monitoring at the workplace:
141-78-6 ethyl acetate

 PEL Long-term value: 1400 mg/m³, 400 ppm

 REL Long-term value: 1400 mg/m³, 400 ppm

TLV Long-term value: 400 ppm

110-19-0 isobutyl acetate

 PEL Long-term value: 700 mg/m³, 150 ppm

 REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: 150 ppm

Long-term value: 50 ppm

123-86-4 n-butyl acetate

 PEL Long-term value: 710 mg/m³, 150 ppm

 REL Short-term value: 950 mg/m³, 200 ppm

 Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 150 ppm

Long-term value: 50 ppm

67-63-0 propan-2-ol

 PEL Long-term value: 980 mg/m³, 400 ppm

 REL Short-term value: 1225 mg/m³, 500 ppm

 Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 400 ppm

Long-term value: 200 ppm

BEI, A4

(Contd. on page 7)

Product number LXC6AA1**Trade name: CLEAR PRE-CAT SEALER**

(Contd. of page 6)

71-36-3 butan-1-olPEL Long-term value: 300 mg/m³, 100 ppmREL Ceiling limit value: 150 mg/m³, 50 ppm
Skin

TLV Long-term value: 20 ppm

1330-20-7 xylenePEL Long-term value: 435 mg/m³, 100 ppmREL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppmTLV Short-term value: (150) ppm
Long-term value: (100) NIC-20 ppm
BEI, A4**100-41-4 ethylbenzene**PEL Long-term value: 435 mg/m³, 100 ppmREL Short-term value: 545 mg/m³, 125 ppm
Long-term value: 435 mg/m³, 100 ppmTLV Long-term value: 20 NIC-20 ppm
BEI, A3, NIC: OTO, BEI, A3**95-47-6 o-xylene**PEL Long-term value: 435 mg/m³, 100 ppmREL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppmTLV Short-term value: (150) ppm
Long-term value: (100) NIC-20 ppm
BEI, A4**78-83-1 2-methylpropan-1-ol**PEL Long-term value: 300 mg/m³, 100 ppmREL Long-term value: 150 mg/m³, 50 ppm

TLV Long-term value: 50 ppm

50-00-0 formaldehydePEL Short-term value: 2 ppm
Long-term value: 0.75 ppm
see 29 CFR 1910.1048(c)REL Long-term value: 0.016 ppm
Ceiling limit value: 0.1* ppm
*15-min; See Pocket Guide App. ATLV Short-term value: 0.3 ppm
Long-term value: 0.1 ppm
DSEN; RSEN, A1**Ingredients with biological limit values:****67-63-0 propan-2-ol**BEI 40 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: Acetone (background, nonspecific)

(Contd. on page 8)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 7)

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

95-47-6 o-xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

· *Additional information:* The lists that were valid during the creation were used as basis.

· **Exposure controls**· *Personal protective equipment:*· *General protective and hygienic measures:*

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.

· *Breathing equipment:*

Short term filter device:



Suitable respiratory protective device recommended.

Filter A

· *Protection of hands:*

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· *Penetration time of glove material*

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 9)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 8)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

- Form: Fluid
- Color: According to product specification
- Odor: Characteristic
- Odor threshold: Not determined.

· pH-value: Mixture is non-polar/aprotic.

· Change in condition

- Melting point/Melting range: Undetermined.
- Boiling point/Boiling range: 77 °C (170.6 °F)

· Flash point: -4 °C (24.8 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 340 °C (644 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

- Lower: 1.1 Vol %
- Upper: 12 Vol %

· Vapor pressure at 20 °C (68 °F): 97 hPa (72.8 mm Hg)

· Density (+/- 0,03) at 20 °C (68 °F): 0.965 g/cm³ (8.053 lbs/gal)

- Relative density: Not determined.
- Vapor density: Not determined.
- Evaporation rate: Not determined.

· Solubility in / Miscibility with

· Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

- Dynamic: Not determined.
- Kinematic at 20 °C (68 °F): 25 s (ISO 6 mm)

· Oxidising properties: N.A.

(Contd. on page 10)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 9)

· Solvent content:		
· VOC content:		65.95 % 636.4 g/l / 5.31 lb/gal
· Solids content:		34.0 %
· Other information (HAPS)		
1330-20-7	xylene	1-2.49%
100-41-4	ethylbenzene	≥0.1-<0.5%
95-47-6	o-xylene	<0.5%
50-00-0	formaldehyde	<0.1%
· Other information		No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
- **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Acids, alkalis and oxidizing agents
- **Hazardous decomposition products:**
in case of possible formation of combustion:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	50,563 mg/kg
Dermal	LD50	90,535 mg/kg (rabbit)
Inhalative	LC50/4 h	905 mg/l (mouse)
141-78-6 ethyl acetate		
Oral	LD50	4,934 mg/kg (rabbit)
Dermal	LD50	20,001 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (mouse)
	LC0	22.6 ppm (mouse)
110-19-0 isobutyl acetate		
Oral	LD50	13,400 mg/kg (mouse)

(Contd. on page 11)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 10)

Dermal	LD50	17,401 mg/kg (rabbit)
Inhalative	LC50/4 h	31 mg/l (mouse)
123-86-4 n-butyl acetate		
Oral	LD50	10,760 mg/kg (mouse)
Dermal	LD50	14,000 mg/kg (rabbit)
Inhalative	LC50/4 h	21.1 mg/l (mouse)
67-63-0 propan-2-ol		
Oral	LD50	4,710 mg/kg (mouse)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	72.6 mg/l (mouse)
71-36-3 butan-1-ol		
Oral	LD50	790 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (mouse)
1330-20-7 xylene		
Oral	LD50.	3,523 mg/kg (mouse)
Dermal	LD50	1,100 mg/kg (rabbit) (ATE value)
	LD50.	12,126 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (mouse) (ATE value)
	LC50/4h.	27.571 mg/l (mouse)
100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (mouse)
Dermal	LD50	15,486 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/l (mouse)
78-83-1 2-methylpropan-1-ol		
Oral	LD50	2,460 mg/kg (mouse)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h.	19.2 mg/l (mouse)
50-00-0 formaldehyde		
Oral	LD50	100 mg/kg (mouse)
Dermal	LD50	270 mg/kg (rabbit)

· **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Irritant

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Oral, Inhalation.

(Contd. on page 12)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 11)

· Carcinogenic categories

Quartz.

No significant exposure to quartz is thought to occur during the use of products in which quartz is bound to other materials, such as resin, and for quantities present in the formula

Ethylbenzene

From IARC MONOGRAPHS VOLUME 77/2000

Human carcinogenicity data

Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.

Evaluation

There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
100-41-4	ethylbenzene	2B
50-00-0	formaldehyde	1
14808-60-7	Quartz (SiO ₂)	1
· NTP (National Toxicology Program)		
50-00-0	formaldehyde	<0.1%
14808-60-7	Quartz (SiO ₂)	<0.1%
· OSHA-Ca (Occupational Safety & Health Administration)		
50-00-0	formaldehyde	<0.1%

12 Ecological information

· Toxicity

· Aquatic toxicity:	
141-78-6 ethyl acetate	
EC50	165 mg/l (daphnia) (48 h)
LC50 (96h)	230 mg/l (Fish)
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h) 25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
123-86-4 n-butyl acetate	
EC50	397 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
67-63-0 propan-2-ol	
EC50	1,001 mg/l (algae) (72 h) 10,000 mg/l (daphnia) (24 h)

(Contd. on page 13)



Safety Data Sheet
acc. to OSHA HCS

Printing date 09/26/2022

Version number 16

Reviewed on 08/19/2022

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 12)

LC50 (96h)	9,640 mg/l (Fish)
1330-20-7 xylene	
EC50	2.2 mg/l (algae)
LC50 48h	1 mg/l (daphnia)
LC50 (96h)	2.6 mg/l (Fish)
100-41-4 ethylbenzene	
EC50	438 mg/l (algae) (72h) 1.8 mg/l (daphnia) (48 h)
LC50 (96h)	12.1 mg/l (Fish)
78-83-1 2-methylpropan-1-ol	
EC50	1,799 mg/l (algae) (72 h) 1,100 mg/l (daphnia) (48 h)
LC50 (96h)	1,430 mg/l (Fish)
64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy	
EC50	4.1 mg/l (algae) (72 h) 20 mg/l (daphnia) (48 h)
LC50 (96h)	20 mg/l (Fish)
50-00-0 formaldehyde	
EC50	4.89 mg/l (algae) (72 h) 5.8 mg/l (daphnia) (48 h)
LC50 (96h)	6.7 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

· **Substances Easily biodegradable**

141-78-6	ethyl acetate	.
110-19-0	isobutyl acetate	.
123-86-4	n-butyl acetate	.
67-63-0	propan-2-ol	.
1330-20-7	xylene	.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects** No further relevant information available.

US

(Contd. on page 14)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 13)

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, IMDG, IATA** UN1263

· **Note** Check viscosity and flash point at section 9

· **UN proper shipping name**

· **DOT** Paint
· **IMDG, IATA** PAINT

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
· **Label** 3
· **Class** 3 Flammable liquids
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids
· **Label** 3

· **Packing group**

· **DOT, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33

· **EMS Number:** F-E, S-E

(Contd. on page 15)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 14)

· <i>Stowage Category</i>	B
· <i>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</i>	Not applicable.
· <i>Transport/Additional information:</i>	
· <i>IMDG</i>	
· <i>Limited quantities (LQ)</i>	5L
· <i>Excepted quantities (EQ)</i>	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· <i>UN "Model Regulation":</i>	UN 1263 PAINT, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture .**
 - *Various regulations*
 - *SARA*

· <i>Section 355 (extremely hazardous substances):</i>		
50-00-0	formaldehyde	<0.1%

· <i>Section 313 (Specific toxic chemical listings) :</i>		
67-63-0	propan-2-ol	5-9.99%
71-36-3	butan-1-ol	1-2.49%
1330-20-7	xylene	1-2.49%
100-41-4	ethylbenzene	≥0.1-<0.5%
95-47-6	o-xylene	<0.5%
50-00-0	formaldehyde	<0.1%
110-82-7	cyclohexane	≥0.025-<0.1%

· <i>TSCA (Toxic Substances Control Act):</i>		
All components have the value ACTIVE.		

· <i>Hazardous Air Pollutants</i>		
1330-20-7	xylene	
100-41-4	ethylbenzene	
95-47-6	o-xylene	
50-00-0	formaldehyde	

· *Proposition 65*

- *Chemicals known to cause cancer:*
Quartz (SiO₂) only in bound form

100-41-4	ethylbenzene	*	≥0.1-<0.5%
50-00-0	formaldehyde	*	<0.1%
14808-60-7	Quartz (SiO ₂)	*	<0.1%

· <i>Chemicals known to cause reproductive toxicity for females:</i>			
None of the ingredients is listed.			

(Contd. on page 16)

Product number LXC6AA1
Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 15)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

71-36-3	butan-1-ol	D	1-2.49%
1330-20-7	xylene	I	1-2.49%
100-41-4	ethylbenzene	D	≥0.1-<0.5%
95-47-6	o-xylene	I	<0.5%
50-00-0	formaldehyde	B1	<0.1%
110-82-7	cyclohexane	I	≥0.025-<0.1%

· **TLV (Threshold Limit Value)**

67-63-0	propan-2-ol	A4
1330-20-7	xylene	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4
50-00-0	formaldehyde	A2
14808-60-7	Quartz (SiO2)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

50-00-0	formaldehyde	<0.1%
14808-60-7	Quartz (SiO2)	<0.1%

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

· **Date of preparation / last revision** 09/26/2022 / 15

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 17)

Product number LXC6AA1

Trade name: CLEAR PRE-CAT SEALER

(Contd. of page 16)

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Acute Toxicity - Oral 4: Acute toxicity – Category 4

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1A: Skin sensitisation – Category 1A

Germ Cell Mutagenicity 2: Germ cell mutagenicity – Category 2

Carcinogenicity 1B: Carcinogenicity – Category 1B

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
and following amendments

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· * **Data compared to the previous version altered.**