

# Integra Adhesives®

## TopSeal

### HYBRID SURFACE SEALANT AND ADHESIVE

Integra Adhesives TopSeal is a premium performance MS Polymer that can be used as an assembly adhesive and a surface sealant. TopSeal comes standard in 6 colors, is food safe, and hardens after cure.



- ✓ 6 standard colors
- ✓ Hybrid sealant and adhesive
- ✓ Excellent gap filling properties
- ✓ Does not yellow and change color over time like silicone
- ✓ High shore hardness making it easy to clean
- ✓ Contains no solvents
- ✓ Easy to clean up leaving no residue
- ✓ Bonds to damp surfaces



White  
(TS290001)



Valenza  
(TS290114)



Ivory  
(TS290082)



Magnolia  
(TS290062)



Fossil Grey  
(TS290017)



Black  
(TS290010)

# TOPSEAL

Hybrid surface sealant and assembly adhesive

## ADVANTAGES

- 6 Standard colors
- Sealant and adhesive
- Excellent gap filling
- Color stable - no yellowing
- Solvent free
- Bonds to damp surfaces

## APPLICATIONS

Indoor use on all surfacing materials

- ✓ Backsplash sealing
- ✓ Backsplash assembly
- ✓ Shower Surrounds
- ✓ Wall panels

## CONTACT

### PHONE

1.888.862.6665

1.919.598.2400

### FAX

1.919.598.2439

### EMAIL & WEB

contact@integra-adhesives.com

www.integra-adhesives.com



## Product Overview

TopSeal is a new color matched adhesive and sealant for backsplashes, upstands and many more. It is the latest generation, high performance toughened polymer technology. TopSeal's excellent bond strength gives instant grip without support. It adheres to a wide range of surfaces – Quartz, Granite, Compact Ceramic and Porcelain. It is color matched to the worktop to give a seamless finish.

TopSeal provides a tough, continuous seam without grooves which is easy to clean and will not wear away like silicone. By its nature it is less likely to harbor viral contamination. It is environmentally friendly, containing no solvents.

## Characteristics

Characteristic	TopSeal
Working Time	5 – 10 minutes
Fixture Time	24 hours (1/16" – 1/8" / 2 – 3mm application)
VOC	353 g/l
Color	Various (15 colors)
Flow (ISO 7390)	<2mm
Elongation	350%
Operating Temperature	41°F – 104°F (+5°C – +40°C)
Temperature Resistance	-40°F – +194°F (-40°C – +90°C)
Shore A Hardness (DIN 53505)	52
Joint Movement	25%
Tensile Strength	290 psi (2 MPa / (N/mm <sup>2</sup> ))
Shelf Life	18 months

\* Use at temperatures below 41°F(5°C) or above 104°F(40°C) may cause incomplete cure, yellowing and poor bonding strength.

## Color Matching

Integra Adhesives is known throughout the industry for excellence in color matching. Our lab combines the latest technology and extensive practical knowledge to produce unrivaled color matches. Customers have access to a large and ever-expanding palette of colors from which to choose. For accurate color matches on a variety of surfaces, visit [www.integra-adhesives.com/color-charts/](http://www.integra-adhesives.com/color-charts/) or download the Integra App from the [Apple App Store](#) or [Google Play Store](#) by searching Integra Adhesives.

## Storage

Store at temperatures between 60° - 80°F (16° - 27°C). Long-term exposure to higher temperatures will reduce shelf life and alter cure properties. Do not freeze. See MFG data on cartridge for expiry information.

## Dispensing / Packaging

Integra Adhesives is a world leader in precoloured cartridge-based adhesives specially designed for the surfacing industry. TopSeal is available in a standard 290ml cartridge, compatible with most caulking/silicone dispensers.

## Shipping Options

Integra Adhesives products are available across North America, Europe and many other parts of world. Please visit [www.integra-adhesives.com](http://www.integra-adhesives.com) to find a distributor near you.

Available at: