


**Product Description**

The DP-300 Concealed Door Straightener/Stiffener is an adjustable threaded rod for reinforcing tall wood doors to resist warping. Ideal for doors visible from both sides that need extra stability and reinforcement. For applications including use in environments with variable humidity levels and doors with a heavy finish on one face, such as laminated or painted doors.

Item no.	Door height	Rod length	▶	Product Features & Benefits
<b>89DP1730</b>	1900 to 2100 mm (74-3/4" to 82-5/8")	1730 mm (68-1/8")	<ul style="list-style-type: none"> <li>Fully concealed within a wood door that is a minimum of 33 mm (1-5/16 in) thick</li> <li>Fabricate the door in two parts : one thicker part (min. 27 mm (1-1/16 in)) with a groove and the second part a decorative skin to cover the hardware</li> <li>Adjustment at one end, typically at the top end of the door</li> <li>Select from 4 sizes for different door height ranges</li> </ul>	
<b>89DP1930</b>	2100 to 2300 mm (82-5/8" to 90-1/2")	1930 mm (76")		
<b>89DP2130</b>	2300 to 2500 mm (90-1/2" to 98-3/8")	2130 mm (83-7/8")		
<b>89DP2330</b>	2500 to 2700 mm (98-3/8" to 106")	2330 mm (91-3/4")		

**Door Straightener/Stiffener**

