



RAMPA Inserts Type SK
with hex socket drive. An unthreaded lead supports for easy assembly.

SK
UNC

CODE	D mm (inch)	L mm (inch)	d thread size	HD	Pilot hole Ø mm (inch)	Weight/ 1.000 kg (lbs)	Steel Zinc Plated
440083210100/1000	8 (0.315)	10 (0.394)	8-32 UNC	4	7,0-7,5	1,9 (4.19)	*
440102412100/1000	10 (0.394)	12 (0.472)	10-24 UNC	5	8,0-8,5	2,8 (6.17)	*
440142012100/1000	12 (0.472)	12 (0.472)	1/4"-20 UNC	6	10,0-10,5	4,8 (10.58)	*
440142020100/500	12 (0.472)	20 (0.787)	1/4"-20 UNC	6	10,0-10,5	7,8 (17.20)	*
4405161818100/500	14 (0.551)	18 (0.709)	5/16"-18 UNC	8	12,0-12,5	8,7 (19.18)	*
4405161830100/1000	14 (0.551)	30 (1.181)	5/16"-18 UNC	8	12,0-12,5	15,0 (33.07)	*
440381620100/1000	18.5 (0.728)	20 (0.787)	3/8"-16 UNC	10	16,0-16,5	19,2 (42.33)	*

All dimensions except d* in mm.