

DESCRIPTION

UB-F3557 is the right choice when you need a high performance double-sided clear foam tape for those demanding jobs. It has a high-performance acrylic adhesive engineered for permanent mounting and bonding to metal, glass and plastics including rough, textured or painted surfaces. This tape is designed to be so strong that it is often used as an alternative to traditional fasteners and it's clear, making it almost invisible and giving you a nice clean look. UB-F3557 also offers outstanding resistance to heat, cold and extreme weather fluctuations.

APPLICATIONS

- Use to attach a variety of automotive exterior trim parts
- Use to attach automotive side body mouldings, claddings, roof ditch mouldings, wheel flares, and tailgate appliqués
- Use to mount muntin/SDL bars on wooden, metal and vinyl doors
- Use indoor and outdoors as a fastener replacement when hanging or mounting translucent or transparent materials (i.e. acrylic, plexiglass) and signage

FEATURES & BENEFITS

- Good shock absorption properties
- Excellent temperature resistance
- Highly flexible making it easy to stick to curved surfaces
- Excellent for use on high surface energy (HSE) surfaces (i.e., metal, glass)
- Strong enough to support a heavier load than the typical double sided tape
- Easy removable liner
- Adheres well on hard to stick-to plastics

COLOR

- Clear

PRODUCT CONSTRUCTION

Backing	Acrylic foam
Adhesive	Acrylic
Liner	Red PE

TECHNICAL DATA

Total Thickness	40 mils
Tensile	> 20 lbs./in.
Adhesion	> 80 oz./in.
Elongation	> 700%
Application Temperature	70°F to 97°F (21°C to 36°C)
Service Temperature	-40°F to 248°F (-40°C to 120°C)
Water Absorption: % by Weight	< 5%

STORAGE & USAGE CONDITIONS

**Store tape in its original packaging away from direct sunlight and in a cool and dry area.
For optimum performance, tape should be used within 12 months of date of shipment.
Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.**

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.