

# MINIMALIST RECESSED LED LIGHT

## LD 8112 24V Black Profile



### POWER SUPPLY INSTALLATION: PLUG-IN

- Lowered Beam Angle
- Glare-free light
- Black anodized aluminum profile
- Thermoplastic end caps
- Black cover
- 0.16in (4mm) 3000K or 4000K LED strip
- Dimmable (depending on the driver)
- Push-fit installation
- Protection Class III

#### Installation with VARIO Power Conductor System

##### Standard Version:

- VARIO track on the left side
- Cable outlet left
- Beam angle inside the closet/cabinet

##### Caution!

##### VARIO track on the right side:

- Light must be rotated
- Beam angle outside the closet/cabinet (see sketches)


### LD 8112 Cable outlet left/Standard version




Qty.	Art. No.	Light Color	Wattage	Length inch (mm)	Cable Length inch (mm)	Suits shelves inch (mm)
	811209512290	3000K	1W	3.74 (95)	5.91 (150)	12 – --
	811212012290	3000K	2W	4.72 (120)	7.87 (200)	13 – 17
	811224512290	3000K	3,9W	9.65 (245)	9.84 (250)	18 – 23
	811239512290	3000K	6,8W	15.55 (395)	9.84 (250)	24 – 29
	811254512290	3000K	9,6W	21.45 (545)	9.84 (250)	30 – 35
	811269512290	3000K	12,5W	27.36 (695)	9.84 (250)	36 – --
	811209512490	4000K	1W	3.74 (95)	5.91 (150)	12 – --
	811212012490	4000K	2W	4.72 (120)	7.87 (200)	13 – 17
	811224512490	4000K	3,9W	9.65 (245)	9.84 (250)	18 – 23
	811239512490	4000K	6,8W	15.55 (395)	9.84 (250)	24 – 29
	811254512490	4000K	9,6W	21.45 (545)	9.84 (250)	30 – 35
	811269512490	4000K	12,5W	27.36 (695)	9.84 (250)	36 – --

### DIMENSIONS


Cross section




Milling dimension



A. **Standard installation**  
with beam angle inside the closet/cabinet, cable outlet left.



B. Installation with beam angle outside the closet/cabinet, cable outlet right.



### LD 8112 BLACK



View into the profile without end cap.



Light with black cover and end cap.



Explore the many control options for the X-Driver system: [www.richelieu.com](http://www.richelieu.com).