

General-Duty to Medium-Duty Casters Roulettes pour usage général à modéré

Rubber I Caoutchouc I



F25091



F25095





F25752

FEATURES AND APPLICATIONS

- Combines strength, durability, and savings
- Rubber wheel combines a soft rubber tread with hard rubber core for quiet movement and cushioned ride
- Recommended for general warehouse and factory applications; use on concrete, asphalt, carpet, wood
- Corrosion-resistant zinc finish

CARACTÉRISTIQUES ET APPLICATIONS

- Allie solidité, durabilité et économie
- Roue de caoutchouc combinant bande de roulement douce et jante en caoutchouc dur pour stabilité de mouvement et roulement coussiné
- Recommandées pour utilisations générales d'usine et d'entrepôt, sur béton, asphalte, tapis, bois
- Fini de zinc résistant à la corrosion

| No. | TYPE | A | | B | C | D | E x F | |
|---|---------------------------------|---|---|------------------------------------|--------------------------------|--|--------------------------------------|--------------------|
| | |  |  | TREAD WIDTH LARGEUR DE BANDE | TOTAL HEIGHT HAUTEUR TOTALE | OFFSET DISTANCE DISTANCE DE DÉPORT | PLATE SIZE DIMENSION DE PLAQUE | WEIGHT POIDS |
| GENERAL-DUTY FORK / CHAPE POUR USAGE GÉNÉRAL | | | | | | | | |
| F25082 | Swivel / Pivot | 2" / 50 mm | 125 lb / 57 kg | 29/32" / 23 mm | 2-7/16" / 62 mm | 25/32" / 20 mm | 1-7/8" × 2-9/16" 48 × 65 mm | 0.41 lb 0.19 kg |
| F25086 | Swivel + brake Pivot + frein | 2" / 50 mm | 125 lb / 57 kg | 29/32" / 23 mm | 2-7/16" / 62 mm | 25/32" / 20 mm | 1-7/8" × 2-9/16" 48 × 65 mm | 0.44 lb 0.2 kg |
| F25748 | Rigid / Fixe | 2" / 50 mm | 125 lb / 57 kg | 29/32" / 23 mm | 2-7/16" / 62 mm | | 1-1/2" × 2-11/16" 38 × 68 mm | 0.3 lb 0.13 kg |
| F25083 | Swivel / Pivot | 2-1/2" / 63 mm | 176 lb / 80 kg | 1-3/32" / 27 mm | 3-7/32" / 82 mm | 29/32" / 23 mm | 2-3/4" × 3-27/32" 70 × 98 mm | 0.9 lb 0.41 kg |
| F25160 | Swivel + brake Pivot + frein | 2-1/2" / 63 mm | 176 lb / 80 kg | 1-3/32" / 27 mm | 3-7/32" / 82 mm | 29/32" / 23 mm | 2-3/4" × 3-27/32" 70 × 98 mm | 0.98 lb 0.44 kg |
| F25749 | Rigid / Fixe | 2-1/2" / 63 mm | 176 lb / 80 kg | 1-3/32" / 27 mm | 3-7/32" / 82 mm | | 2-3/16" × 4-7/16" 56 × 113 mm | 0.72 lb 0.33 kg |
| F25091 | Swivel / Pivot | 3" / 75 mm | 209 lb / 95 kg | 1-9/32" / 32.5 mm | 3-13/16" / 96.5 mm | 1-3/16" / 30 mm | 3-1/8" × 4-1/8" 79.5 × 105 mm | 1.23 lb 0.56 kg |
| F25095 | Swivel + brake Pivot + frein | 3" / 75 mm | 209 lb / 95 kg | 1-9/32" / 32.5 mm | 3-13/16" / 96.5 mm | 1-3/16" / 30 mm | 3-1/8" × 4-1/8" 79.5 × 105 mm | 1.35 lb 0.61 kg |
| F25752 | Rigid / Fixe | 3" / 75 mm | 209 lb / 95 kg | 1-9/32" / 32.5 mm | 3-13/16" / 96.5 mm | | 2-7/16" × 4-7/8" 62 × 124 mm | 1.08 lb 0.49 kg |
| MEDIUM-DUTY FORK / CHAPE POUR USAGE MODÉRÉ | | | | | | | | |
| F25413 | Swivel / Pivot | 4" / 102 mm | 246 lb / 112 kg | 1-1/4" / 32 mm | 5" / 127 mm | 1-1/2" / 38 mm | 2-17/32" × 3-21/32" 64 × 93 mm | 1.88 lb 0.85 kg |
| F25415 | Swivel + brake Pivot + frein | 4" / 102 mm | 246 lb / 112 kg | 1-1/4" / 32 mm | 5" / 127 mm | 1-1/2" / 38 mm | 2-17/32" × 3-21/32" 64 × 93 mm | 1.99 lb 0.9 kg |
| F27280 | Rigid / Fixe | 4" / 102 mm | 246 lb / 112 kg | 1-1/4" / 32 mm | 5" / 127 mm | | 2-3/8" × 3-5/8" 60 × 92 mm | 1.32 lb 0.6 kg |
| F25533 | Swivel / Pivot | 5" / 125 mm | 297 lb / 135 kg | 1-1/4" / 32 mm | 6-1/8" / 156 mm | 1-3/8" / 35 mm | 2-3/8" × 3-5/8" 60 × 92 mm | 2.62 lb 1.19 kg |
| F25426 | Swivel + brake Pivot + frein | 5" / 125 mm | 297 lb / 135 kg | 1-1/4" / 32 mm | 6-1/8" / 156 mm | 1-3/8" / 35 mm | 2-3/8" × 3-5/8" 60 × 92 mm | 2.91 lb 1.32 kg |
| F27281 | Rigid / Fixe | 5" / 125 mm | 297 lb / 135 kg | 1-1/4" / 32 mm | 6-1/8" / 155.5 mm | | 2-3/8" × 3-5/8" 60 × 92 mm | 1.89 lb 0.86 kg |

See / Voir : page 36