

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

## SECTION 1: IDENTIFICATION

**1.1 Product identifier:** BI1019T.  
White post-cat 10° / Blanc post-cat 10°

**Other means of identification:**

Non-applicable

**1.2 Recommended use of the chemical and restrictions on use:**

Relevant uses: Product for varnishing wood. For industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Initial supplier identifier:**

RICHELIEU HARDWARE LTD.

Importateur - Distributeur / Importer -Distributor : Richelieu Hardware ltd. 7900 Bld. Henri-Bourassa Ouest H4S 1V4 Ville St-Laurent - QUEBEC-QC - CANADA

www.richelieu.com info@richelieu.com - - Fabriqué à / Made in: European Union, Industrias Químicas KUPSA S.L., - Carretera Logroño-Pamplona km 2,3, Oyón, ES-01320

Phone: +34 945 622 225 - Fax: +34 945 62 22 31

Canada : Quincaillerie Richelieu ltée - Richelieu Hardware ltd, 7900 Henri-Bourassa Blvd West, Montreal, QC, H4S 1V4. Tel : 1-800-361-6000

U.S.A. : Richelieu America Ltd., 7021 Sterling Ponds Blvd, Sterling Heights, MI 48312-5809 U.S. Tel: 1-800-619-5446

**1.4 Emergency phone number:** +34 945 622 225

## SECTION 2: HAZARD IDENTIFICATION

**2.1 Classification of the substance or mixture:**

**WHMIS 2015:**

Classification of this product has been carried out in accordance with Part 2 of Hazardous Products Regulations (SOR/2015-17)

Asp. Tox. 1: Aspiration hazard, Category 1, H304

Carc. 2: Carcinogenicity, Category 2, H351

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 2: Flammable liquids, Category 2, H225

Repr. 2: Reproductive toxicity, Category 2, H361

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**WHMIS 2015:**

Danger



**Hazard statements:**

- CONTINUED ON NEXT PAGE -



## SECTION 2: HAZARD IDENTIFICATION (continued)

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Carc. 2: H351 - Suspected of causing cancer.  
Eye Dam. 1: H318 - Causes serious eye damage.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1A: H317 - May cause an allergic skin reaction.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

### Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P370+P378: In case of fire: Use ABC powder extinguisher to put it out.  
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

### Substances that contribute to the classification

Reaction mass of ethylbenzene and m-xylene and p-xylene ; N-butyl acetate; 2-methylpropan-1-ol; propan-2-ol

### 2.3 Health and physical hazards not otherwise classified (HHNOC - PHNOC):

Non-applicable

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances:










Non-applicable

### 3.2 Mixtures:

**Chemical description:** Mixture composed of additives, aggregates, pigments and resins in solvents

### Components:

In accordance with Schedule I of the Hazardous Products Regulations (SOR/2015-17), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Non-applicable	<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b> Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	 10 - <30 %
CAS: 123-86-4	<b>N-butyl acetate</b> Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	 5 - <10 %
CAS: 78-83-1	<b>2-methylpropan-1-ol</b> Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	 5 - <10 %
CAS: 67-63-0	<b>propan-2-ol</b> Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	 5 - <10 %
CAS: Non-applicable	<b>Reaction mass of ethylbenzene and xylene</b> Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	 1 - <5 %
CAS: 141-78-6	<b>Ethyl acetate</b> Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	 1 - <5 %
CAS: 108-88-3	<b>Toluene</b> Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	 1 - <5 %
CAS: 67-64-1	<b>acetone</b> Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	 1 - <5 %
CAS: 79-20-9	<b>methyl acetate</b> Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	 1 - <5 %

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

Identification	Chemical name/Classification	Concentration
CAS: 85711-46-2	<b>Fatty acids, C14-18 and C16-18-unsatd., maleated</b> Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	<1 %
CAS: 100-41-4	<b>Ethylbenzene</b> Acute Tox. 4: H332; Carc. 2: H351; Flam. Liq. 2: H225 - Danger	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**Other information:**

Identification	Specific concentration limit
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	% (w/w) >=10: STOT RE 2 - H373

**SECTION 4: FIRST-AID MEASURES**

**4.1 Description of necessary measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Non-applicable

**SECTION 5: FIRE-FIGHTING MEASURES**

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

- CONTINUED ON NEXT PAGE -



## SECTION 5: FIRE-FIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

See section 8.

### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### 6.3 Methods and materials for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

#### B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

#### C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in fixed places that comply with the necessary security conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to containers of small amounts. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

#### D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

### SECTION 7: HANDLING AND STORAGE (continued)

**A.- Technical measures for storage**

Minimum Temp.: 5 °C

Maximum Temp.: 40 °C

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

British Columbia - Occupational Health and Safety Regulation section 5.48:

Identification	Occupational exposure limits		
	TLV-TWA	TLV-STEL	
N-butyl acetate CAS: 123-86-4	20 ppm		
2-methylpropan-1-ol CAS: 78-83-1	50 ppm		
propan-2-ol CAS: 67-63-0	200 ppm	400 ppm	
Ethyl acetate CAS: 141-78-6	150 ppm		
Toluene CAS: 108-88-3	20 ppm		
acetone CAS: 67-64-1	250 ppm	500 ppm	
methyl acetate CAS: 79-20-9	200 ppm	250 ppm	
Ethylbenzene CAS: 100-41-4	20 ppm		

ALBERTA - Occupational Health and Safety Code:

Identification	Occupational exposure limits		
	8-hour	15-minute	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	100 ppm	434 mg/m <sup>3</sup>	651 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4	150 ppm	713 mg/m <sup>3</sup>	950 mg/m <sup>3</sup>
2-methylpropan-1-ol CAS: 78-83-1	50 ppm	152 mg/m <sup>3</sup>	
propan-2-ol CAS: 67-63-0	200 ppm	492 mg/m <sup>3</sup>	984 mg/m <sup>3</sup>
Ethyl acetate CAS: 141-78-6	400 ppm	1440 mg/m <sup>3</sup>	
Toluene CAS: 108-88-3	50 ppm	188 mg/m <sup>3</sup>	
acetone CAS: 67-64-1	500 ppm	1200 mg/m <sup>3</sup>	1800 mg/m <sup>3</sup>
methyl acetate CAS: 79-20-9	200 ppm	606 mg/m <sup>3</sup>	757 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4	100 ppm	434 mg/m <sup>3</sup>	543 mg/m <sup>3</sup>

**8.2 Appropriate engineering controls:**

A.- Individual protection measures, such as personal protective equipment

- CONTINUED ON NEXT PAGE -




**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**


In accordance with the order of importance to control professional exposure it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



**D.- Ocular and facial protection**

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Bodily protection**

Pictogram	PPE	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds (VOC) according to Canadian Environmental Protection Act, 1999:**

Volatile organic compounds:	42.73 % weight
V.O.C. density at 20 °C:	482.44 kg/m <sup>3</sup> (482.44 g/L)

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Not available
Color:	Characteristic
Odor:	Not available
Odour threshold:	Non-applicable *

#### Volatility:

Boiling point at atmospheric pressure:	103 °C
Vapour pressure at 20 °C:	4854 Pa
Vapour pressure at 50 °C:	20461.92 Pa (20.46 kPa)
Evaporation rate at 20 °C:	Non-applicable *

#### Product description:

Density at 20 °C:	1089.9 kg/m <sup>3</sup>
Relative density at 20 °C:	1.09
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20.5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

#### Flammability:

Flash Point:	16 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	315 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

#### Explosive (Solid):

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

#### Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

### 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
<b>Other safety characteristics:</b>	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### Other information:

Avoid strong acids

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

#### A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

#### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- CONTINUED ON NEXT PAGE -



**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
2-methylpropan-1-ol CAS: 78-83-1	3350 mg/kg	2460 mg/kg	Rat
		24.6 mg/L (4 h)	Rabbit
			Rat
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	2100 mg/kg	1100 mg/kg	Rat
		11 mg/L (4 h) (ATEi)	Rat
methyl acetate CAS: 79-20-9	6482 mg/kg	18684 mg/kg	Rat
		75 mg/L (4 h)	Guinean pig
			Rabbit
acetone CAS: 67-64-1	5800 mg/kg	7426 mg/kg	Rat
		76 mg/L (4 h)	Rabbit
			Rat
propan-2-ol CAS: 67-63-0	5280 mg/kg	12800 mg/kg	Rat
		72.6 mg/L (4 h)	Rat
			Rat
Toluene CAS: 108-88-3	5580 mg/kg	12124 mg/kg	Rat
		28.1 mg/L (4 h)	Rat
			Rat
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	2100 mg/kg	1100 mg/kg	Rat
		11 mg/L (4 h)	Rat
			Rat

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23.4 mg/L (4 h)	Rat
Ethyl acetate CAS: 141-78-6	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	
Fatty acids, C14-18 and C16-18-unsatd., maleated CAS: 85711-46-2	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Ethylbenzene CAS: 100-41-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17.2 mg/L (4 h)	Rat

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	35861.74 mg/kg (Calculation method)	0 %
Dermal	7127.84 mg/kg (Calculation method)	0 %
Inhalation	71.28 mg/L (4 h) (Calculation method)	0 %

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Ecotoxicity (aquatic and terrestrial, where available):**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	LC50	EC50		
N-butyl acetate CAS: 123-86-4	LC50	Non-applicable		
	EC50	Non-applicable		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methylpropan-1-ol CAS: 78-83-1	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
propan-2-ol CAS: 67-63-0	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration	Species	Genus
Ethyl acetate CAS: 141-78-6	LC50 230 mg/L (96 h)	Pimephales promelas	Fish
	EC50 717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Toluene CAS: 108-88-3	LC50 5.5 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50 3.78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50 Non-applicable		
acetone CAS: 67-64-1	LC50 5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50 8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50 3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
methyl acetate CAS: 79-20-9	LC50 320 mg/L (96 h)	Pimephales promelas	Fish
	EC50 1026.7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 120 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethylbenzene CAS: 100-41-4	LC50 42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50 75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 63 mg/L (3 h)	Chlorella vulgaris	Algae

**Chronic toxicity:**

Identification	Concentration	Species	Genus
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	NOEC 1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1.17 mg/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate CAS: 123-86-4	NOEC Non-applicable		
	NOEC 23.2 mg/L	Daphnia magna	Crustacean
2-methylpropan-1-ol CAS: 78-83-1	NOEC Non-applicable		
	NOEC 20 mg/L	Daphnia magna	Crustacean
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	NOEC 1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1.17 mg/L	Ceriodaphnia dubia	Crustacean
Ethyl acetate CAS: 141-78-6	NOEC 9.65 mg/L	Pimephales promelas	Fish
	NOEC 2.4 mg/L	Daphnia magna	Crustacean
acetone CAS: 67-64-1	NOEC Non-applicable		
	NOEC 2212 mg/L	Daphnia magna	Crustacean
Ethylbenzene CAS: 100-41-4	NOEC Non-applicable		
	NOEC 0.96 mg/L	Ceriodaphnia dubia	Crustacean

**12.2 Persistence and degradability:**

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Degradability		Biodegradability	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
N-butyl acetate CAS: 123-86-4	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	5 days
	BOD5/COD	Non-applicable	% Biodegradable	84 %
2-methylpropan-1-ol CAS: 78-83-1	BOD5	0.4 g O2/g	Concentration	100 mg/L
	COD	2.41 g O2/g	Period	14 days
	BOD5/COD	0.17	% Biodegradable	90 %
propan-2-ol CAS: 67-63-0	BOD5	1.19 g O2/g	Concentration	100 mg/L
	COD	2.23 g O2/g	Period	14 days
	BOD5/COD	0.53	% Biodegradable	86 %
Ethyl acetate CAS: 141-78-6	BOD5	1.36 g O2/g	Concentration	100 mg/L
	COD	1.69 g O2/g	Period	14 days
	BOD5/COD	0.8	% Biodegradable	83 %
Toluene CAS: 108-88-3	BOD5	2.5 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
acetone CAS: 67-64-1	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	96 %
methyl acetate CAS: 79-20-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	92 %
Ethylbenzene CAS: 100-41-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	BCF	9
	Pow Log	2.77
	Potential	Low

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Bioaccumulation potential	
N-butyl acetate CAS: 123-86-4	BCF	4
	Pow Log	1.78
	Potential	Low
2-methylpropan-1-ol CAS: 78-83-1	BCF	3
	Pow Log	0.76
	Potential	Low
propan-2-ol CAS: 67-63-0	BCF	3
	Pow Log	0.05
	Potential	Low
Reaction mass of ethylbenzene and xylene CAS: Non-applicable	BCF	9
	Pow Log	2.77
	Potential	Low
Ethyl acetate CAS: 141-78-6	BCF	30
	Pow Log	0.73
	Potential	Moderate
Toluene CAS: 108-88-3	BCF	90
	Pow Log	2.73
	Potential	Moderate
acetone CAS: 67-64-1	BCF	1
	Pow Log	-0.24
	Potential	Low
methyl acetate CAS: 79-20-9	BCF	0.8
	Pow Log	0.18
	Potential	Low
Ethylbenzene CAS: 100-41-4	BCF	1
	Pow Log	3.15
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable	Koc	202	Henry	524.86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Absorption/desorption		Volatility	
N-butyl acetate CAS: 123-86-4	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2.478E-2 N/m (25 °C)	Moist soil	Non-applicable
2-methylpropan-1-ol CAS: 78-83-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2.378E-2 N/m (25 °C)	Moist soil	Non-applicable
propan-2-ol CAS: 67-63-0	Koc	1.5	Henry	8.207E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.24E-2 N/m (25 °C)	Moist soil	Yes
Ethyl acetate CAS: 141-78-6	Koc	59	Henry	13.58 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.324E-2 N/m (25 °C)	Moist soil	Yes
Toluene CAS: 108-88-3	Koc	178	Henry	672.8 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.793E-2 N/m (25 °C)	Moist soil	Yes
acetone CAS: 67-64-1	Koc	1	Henry	2.93 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.304E-2 N/m (25 °C)	Moist soil	Yes
methyl acetate CAS: 79-20-9	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2.454E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene CAS: 100-41-4	Koc	520	Henry	798.44 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.859E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

**Regulations related to waste management:**

Legislation related to waste management:

Canadian Environmental Protection Act, 1999

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to Transportation of Dangerous Goods Regulations including Amendment SOR/2017-100

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number:** UN1263  
**14.2 United Nations proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** II  
**14.5 Environmental hazard:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 39-18:



- 14.1 UN number:** UN1263  
**14.2 United Nations proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** II  
**14.5 Marine pollutant:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Special regulations: 367, 163  
 EmS Codes: F-E, S-E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
 Segregation group: Non-applicable  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2021:



- 14.1 UN number:** UN1263  
**14.2 United Nations proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** II  
**14.5 Environmental hazard:** No  
**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

- 15.1 Safety, health and environmental regulations specific for the product in question:**

- CONTINUED ON NEXT PAGE -

**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

### SECTION 15: REGULATORY INFORMATION (continued)

Domestic Substances List (DSL): Reaction mass of ethylbenzene and m-xylene and p-xylene ; N-butyl acetate ; 2-methylpropan-1-ol ; propan-2-ol ; Ethyl acetate ; Toluene ; acetone ; methyl acetate ; Ethylbenzene  
Non-Domestic Substances List (NDSL): Fatty acids, C14-18 and C16-18-unsatd., maleated

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Other legislation:**

Canadian Environmental Protection Act, 1999

### SECTION 16: OTHER INFORMATION

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Part 4 and Schedule I of the Hazardous Products Regulations (SOR/2015-17)

**Texts of the legislative phrases mentioned in section 2:**

H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H317: May cause an allergic skin reaction.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H351: Suspected of causing cancer.

H361: Suspected of damaging fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

H304: May be fatal if swallowed and enters airways.

H225: Highly flammable liquid and vapour.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**WHMIS 2015:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 2: H351 - Suspected of causing cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://whmis.org/>

**Abbreviations and acronyms:**

- CONTINUED ON NEXT PAGE -



**BI1019T.**  
**White post-cat 10° / Blanc post-cat 10°**



Printing: 2021-11-11

Date of compilation: 2021-02-22

Revised: 2021-09-29

Version: 7 (Replaced 6)

**SECTION 16: OTHER INFORMATION (continued)**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
CL50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

END OF SAFETY DATA SHEET