

LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Safety Data Sheet dated 1/25/2019, version 1

1. Identification

GHS Product identifier

Mixture identification:

Trade name: VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Other means of identification

Trade code: LAW100

Recommended use and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Resin for varnish

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-514-832-4010

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

The product is not classified as dangerous according to WHMIS 2015.

GHS label elements, including precautionary statements

The product is not classified as dangerous according to WHMIS 2015.

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

LAW100/1

Page n. 1 of 7



LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Qty	Name	Ident. Number		Classification
720 ppm	formaldehyde%	CAS: EC: REACH No.:	605-001-00-5 50-00-0 200-001-8 01-2119488953- 20	 ♣ A.6/1B Carc. 1B H350 ♠ A.5/2 Muta. 2 H341 ♠ A.1/3/Oral Acute Tox. 3 H301 ♠ A.1/3/Dermal Acute Tox. 3 H311 ♠ A.1/3/Inhal Acute Tox. 3 H331 ♠ A.2/1B Skin Corr. 1B H314 ♠ A.4.2/1 Skin Sens. 1 H317
90 ppm	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS: EC: REACH No.:	613-088-00-6 2634-33-5 220-120-9 01-2120761540- 60	 ♠ A.2/2 Skin Irrit. 2 H315 ♠ A.4.2/1 Skin Sens. 1 H317 ♠ A.3/1 Eye Dam. 1 H318 ♠ CAN-HAE/A1 Aquatic Acute 1 H400 ♠ A.1/4/Oral Acute Tox. 4 H302
9 ppm	mixture of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220- 239-6] (3:1) (CAS 26172-55- 4 + CAS 2682-20-4)		613-167-00-5 55965-84-9	 A.2/1B Skin Corr. 1B H314 1 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Inhal Acute Tox. 3 H331

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

LAW100/1

Page n. 2 of 7



LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

formaldehyde ...% - CAS: 50-00-0

ACGIH - TWA(8h): 0.1 ppm - STEL: 0.3 ppm - Notes: DSEN, RSEN, A1 - URT and eye irr, URT cancer mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9

TLV TWA - 0,05 mg/m3 TLV STEL - 0,23 mg/m3

DNEL Exposure Limit Values

formaldehyde ...% - CAS: 50-00-0

Worker Industry: 9 mg/m3 - Worker Professional: 9 mg/m3 - Consumer: 3.2 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 0.5 mg/m3 - Worker Professional: 0.5 mg/m3 - Consumer: 0.1 mg/m3 - Exposure: Human

Inhalation - Frequency: Long Term, local effects

Worker Industry: 1 mg/m3 - Worker Professional: 1 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 240 mg/kg - Worker Professional: 240 mg/kg - Consumer: 102 mg/kg - Exposure: Human Dermal

- Frequency: Long Term, systemic effects

Consumer: 4.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Target: Fresh Water - Value: 0.47 mg/l Target: Marine water - Value: 0.47 mg/l

Target: Freshwater sediments - Value: 2.44 mg/kg Target: Marine water sediments - Value: 2.44 mg/kg

Target: Microorganisms in sewage treatments - Value: 0.19 mg/l

Target: Soil (agricultural) - Value: 0.21 mg/kg

Appropriate engineering controls

None

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable gloves type:(EN374)

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour: opalescent fluid Odour: typical

LAW100/1

Page n. 3 of 7



LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Odour threshold: N.D. pH: 7.5 N.D. °C Melting point / freezing point: > 100 °C Initial boiling point and boiling range: N.A. Evaporation rate: N.D. Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.D. N.D. (20 °C) Vapour pressure: Vapour density: Relative density: 1.000 - 1.010 Solubility in water: miscible Solubility in oil: N.D. Partition coefficient (n-octanol/water): N.D. N.D. °C Auto-ignition temperature: N.D. °C Decomposition temperature: Viscosity: N.D.

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

d) respiratory or skin sensitisation

Not classified

No data available for the product

e) germ cell mutagenicity Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

Not classified

No data available for the product

h) STOT-single exposure

Not classified

No data available for the product

i) STOT-repeated exposure

Not classified

No data available for the product

j) aspiration hazard

Not classified

No data available for the product



LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

```
Toxicological information of the main substances found in the product:
                formaldehyde ...% - CAS: 50-00-0
                a) acute toxicity:
                        Test: LD50 - Route: Oral - Species: Rat > 100 mg/kg
                        Test: LC50 - Route: Inhalation - Species: Rat = 588 mg/m3 - Duration: 4h
                        Test: LC50 - Route: Skin - Species: Rabbit = 270 mg/l
                1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
                a) acute toxicity
                        Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg
                        Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg
                mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6]
                (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
                a) acute toxicity:
                        Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h
                        Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg
        Substance(s) listed on the NTP report on Carcinogens:
                formaldehyde ...%
        Substance(s) listed on the IARC Monographs:
                formaldehyde ...% - Group 1.
        Substance(s) listed as OSHA Carcinogen(s):
               formaldehyde ...%
        Substance(s) listed as NIOSH Carcinogen(s):
               formaldehyde ...%.
12. Ecological information
        Ecotoxicity
                Adopt good working practices, so that the product is not released into the environment.
        VEICOLO Uniformante per tinte acqua - Clear binder for WB stain
                Not classified for environmental hazards
                No data available for the product
       formaldehyde ...% - CAS: 50-00-0
                a) Aquatic acute toxicity:
                        Endpoint: LC50 - Species: Fish = 6.7 mg/l - Duration h: 96
                        Endpoint: EC50 - Species: Daphnia = 5.8 mg/l - Duration h: 48
                        Endpoint: EC50 - Species: Algae > 3.48 mg/l - Duration h: 72
        1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
                a) Aquatic acute toxicity:
                        Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96
                        Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48
                        Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72
                b) Aquatic chronic toxicity:
                        Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d
                        Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d
        mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)
        (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
                a) Aquatic acute toxicity:
                        Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72
                        Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48
```

Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEĆ - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201 Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211

Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210

Persistence and degradability

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5

Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B

Bioaccumulative potential

Mobility in soil

N.A.

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

LAW100/1



LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

formaldehyde ...% is listed in NPRI Part 5.

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

formaldehyde ...% is listed in TSCA Section 8b

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: formaldehyde ...%.

Section 304 – Hazardous substances: formaldehyde ...%.

Section 313 – Toxic chemical list: formaldehyde ...%.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: formaldehyde ...% - Reportable quantity: 100 pounds.

Reportable quantity for mixture: 138888.8889 pounds.

CAA - Clean Air Act

CAA listed substances:

formaldehyde ...% is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON, Section 112(r).

CWA - Clean Water Act

CWA listed substances:

formaldehyde ...% is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

formaldehyde ...% - Listed as carcinogen.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

formaldehyde ...%.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

formaldehyde ...%.

Pennsylvania Right to know

LAW100/1



LAW100 VEICOLO Uniformante per tinte acqua - Clear binder for WB stain

Substance(s) listed under Pennsylvania Right to know: formaldehyde ...%.

 $\label{eq:volatile} \begin{tabular}{ll} Volatile Organic compounds - VOCs = 0.07 \% \\ Volatile Organic compounds - VOCs = 0.73 g/l \\ Volatile CMR substances = 0.07 \% \\ Organic Carbon - C = 0.00 \\ \end{tabular}$

16. Other information

Full text of phrases referred to in Section 3:

H350 May cause cancer.

H341 Suspected of causing genetic defects.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H302 Harmful if swallowed.

H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet dated 1/25/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average