

**RICHELIEU HARDWARE LTD.**

7900 Henri-Bourassa Ouest  
St-Laurent, Quebec-QC, H4S 1V4 (CANADA)  
☎ +1 450 664 0163 www.richelieu.com  
E-mail: info@richelieu.com

**Clear sealer pre-cat**Reference: **LF2001T****Product description**

Clear sealer pre-catalysed.

**Components**

Reducer: DN2000M 15% - 25%

*Do not use other thinners and reducers than DN2000M.*

**Physical-chemical characteristics**

Density:	0.940 g/cm <sup>3</sup> ±0.010 at 20°C
Solid (% by weight):	27 %
Viscosity	150 sec ± 15 ISO 6 at 20°C

**Application systems**

The product can be applied by brush and spraying gun after adjustment of the viscosity, being the suitable quantity to apply 90-150 gr/m<sup>2</sup> per coat.

**Drying system**

Air drying. Very fast drying, easy sanding and good hiding properties.

**Usage field**

Primer for furniture and frames in general. Brush or spray gun application on a wide range of solid wood or veneers.

Dilute with DN2000M to get the suitable application viscosity. Recoatable with pre-catalysed or post-catalysed coatings.

**Storing and packaging.**

Product must be stored away from electrical and heat sources. Don't smoke in the storage area. To avoid product leaking, once opened one package it will have to be carefully closed again and kept always in vertical position.

- *Maximum storing-time:* 18 months in original packaging,
- *Available packages:* 20 litres.

**Observations**

Always shake the product before use and make a first trial application if the product has been in stock for a long time since production.