

Safety Data Sheet



LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Safety Data Sheet dated 5/17/2018, version 1

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Other means of identification:

Trade code: LFE423

Recommended use of the chemical and restrictions on use

Recommended use:

Industrial and professional uses (SU3 - SU22)

Varnish for wood

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-860-529-7704

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel:+1-860-529-7704

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

- ⚠ Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.
- ⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.
- ⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Label elements

Hazard pictograms:



Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash ... Thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor/... if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see ... On this label).
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P363 Wash contaminated clothing before reuse.
 P370+P378 In case of fire, use alcohol resistant foam, dry chemical, CO2, water spray. Do not use water jet.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

Additional classification information

NFPA rating:



HMIS rating:

HEALTH	/ 2
FLAMMABILITY	3
PHYSICAL HAZARD	1
PERSONAL PROTECTION	B

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Qty	Name	Ident. Number	Classification
>= 20% - < 25%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.10/1 Asp. Tox. 1 H304 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.7/2 Unst. Expl. ⚠ A.8/3 STOT SE 3 H336 ⚠ A.9/2 STOT RE 2 H373
>= 15% - < 20%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 10% - < 12.5%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.8/3 STOT SE 3 H336
>= 7% - < 10%	butanone; ethyl methyl ketone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH No.: 01-2119457290-43	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.3/2A Eye Irrit. 2A H319 ⚠ A.8/3 STOT SE 3 H336
>= 3% - < 5%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/2A Eye Irrit. 2A H319 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304
>= 1% - < 3%	ethyl acetate	Index number: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH No.: 01-2119475103-46	<ul style="list-style-type: none"> ⚠ A.3/2A Eye Irrit. 2A H319 ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.8/3 STOT SE 3 H336
>= 1% - < 3%	2-methylpropan-1-ol; iso-butanol	Index number: 603-108-00-1 CAS: 78-83-1 EC: 201-148-0 REACH No.: 01-2119484609-23	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.3/1 Eye Dam. 1 H318 ⚠ A.8/3 STOT SE 3 H336
>= 0.5% - < 1%	methyl methacrylate; methyl 2-methylprop-2-enoate	Index number: 607-035-00-6 CAS: 80-62-6 EC: 201-297-1 REACH No.: 01-2119452498-28	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.4.2/1 Skin Sens. 1 H317
>= 0.3% - < 0.5%	Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67	Index number: 607-176-00-3 EC: 400-830-7 REACH No.: 01-0000015075-76	<ul style="list-style-type: none"> ⚠ A.4.2/1 Skin Sens. 1 H317 ⚠ US-HAE/C2 Aquatic Chronic 2 H411
>= 0.1% - < 0.3%	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	EC: 915-687-0 REACH No.: 01-2119491304-40	<ul style="list-style-type: none"> ⚠ A.4.2/1 Skin Sens. 1 H317 ⚠ US-HAE/A1 Aquatic Acute 1 H400 ⚠ US-HAE/C1 Aquatic Chronic 1 H410
>= 0.1% - < 0.3%	2-hydroxyethyl methacrylate	Index number: 607-124-00-X CAS: 868-77-9 EC: 212-782-2	<ul style="list-style-type: none"> ⚠ A.3/2A Eye Irrit. 2A H319 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.4.2/1 Skin Sens. 1 H317

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

		REACH No.: 01-2119490169-29	
--	--	-----------------------------	--

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do NOT induce vomiting.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

- In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

- In case of fire, use alcohol resistant foam, dry chemical, CO₂, water spray. Do not use water jet.

Unsuitable extinguishing media:

- None in particular.

Specific hazards arising from the chemical

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

- Use suitable breathing apparatus .
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

- Wear personal protection equipment.
- Remove all sources of ignition.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.
- Provide adequate ventilation.
- Remove persons to safety.
- Use appropriate respiratory protection.
- See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

- Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

- Avoid contact with skin and eyes, inhalation of vapours and mists.
- Exercise the greatest care when handling or opening the container.
- Do not use on extensive surface areas in premises where there are occupants.
- Don't use empty container before they have been cleaned.
- Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
- Contaminated clothing should be changed before entering eating areas.
- Do not eat or drink while working.
- See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

- Always keep in a well ventilated place.
- Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Avoid accumulating electrostatic charge.
 Keep away from food, drink and feed.
 Incompatible materials:
 None in particular.
 Instructions as regards storage premises:
 Cool and adequately ventilated.
 Safety electric system.
 Storage temperature:
 Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

toluene - CAS: 108-88-3
 EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

n-butyl acetate - CAS: 123-86-4
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

isobutyl acetate [2] - CAS: 110-19-0
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

butanone; ethyl methyl ketone - CAS: 78-93-3
 EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm
 ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

xylene [4] - CAS: 1330-20-7
 EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethyl acetate - CAS: 141-78-6
 ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr
 EU - TWA(8h): 734 mg/m³, 200 ppm - STEL: 1468 mg/m³, 400 ppm

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
 ACGIH - TWA(8h): 50 ppm - Notes: Skin and eye irr

methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6
 EU - TWA(8h): 50 ppm - STEL: 100 ppm
 ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: DSEN, A4 - URT and eye irr, body weight eff, pulm edema

DNEL Exposure Limit Values

toluene - CAS: 108-88-3
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

n-butyl acetate - CAS: 123-86-4
 Worker Industry: 960 mg/m³ - Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 960 mg/m³ - Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
 Worker Industry: 480 mg/m³ - Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 480 mg/m³ - Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

isobutyl acetate [2] - CAS: 110-19-0
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 300 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

butanone; ethyl methyl ketone - CAS: 78-93-3
 Worker Industry: 1161 mg/kg - Worker Professional: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 106 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7
 Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

- Frequency: Long Term, systemic effects
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- ethyl acetate - CAS: 141-78-6
Worker Industry: 1468 mg/m³ - Worker Professional: 1468 mg/m³ - Consumer: 734 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Industry: 1468 mg/m³ - Worker Professional: 1468 mg/m³ - Consumer: 734 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Industry: 63 mg/kg - Worker Professional: 63 mg/kg - Consumer: 37 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 734 mg/m³ - Worker Professional: 734 mg/m³ - Consumer: 367 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 734 mg/m³ - Worker Professional: 734 mg/m³ - Consumer: 367 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 4.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- 2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
Worker Industry: 310 mg/m³ - Worker Professional: 310 mg/m³ - Consumer: 55 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
- Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67 - Index number: 607-176-00-3
Worker Industry: 0.398 mg/m³ - Worker Professional: 0.398 mg/m³ - Consumer: 0.099 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 0.25 mg/kg - Worker Professional: 0.25 mg/kg - Consumer: 0.025 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 0.025 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Worker Industry: 3.53 mg/m³ - Worker Professional: 3.53 mg/m³ - Consumer: 0.87 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 2 mg/kg - Worker Professional: 2 mg/kg - Consumer: 1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 0.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- PNEC Exposure Limit Values**
- toluene - CAS: 108-88-3
Target: Fresh Water - Value: 0.68 mg/l
Target: Marine water - Value: 0.68 mg/l
Target: Intermittent emission - Value: 0.68 mg/l
Target: Freshwater sediments - Value: 16.39 mg/kg
Target: Marine water sediments - Value: 16.39 mg/kg
Target: Microorganisms in sewage treatments - Value: 13.61 mg/l
Target: Soil (agricultural) - Value: 2.89 mg/kg
- n-butyl acetate - CAS: 123-86-4
Target: Fresh Water - Value: 0.18 mg/l
Target: Marine water - Value: 0.018 mg/l
Target: Intermittent emission - Value: 0.36 mg/l
Target: Freshwater sediments - Value: 0.98 mg/kg
Target: Marine water sediments - Value: 0.098 mg/kg
Target: Microorganisms in sewage treatments - Value: 35.6 mg/l
Target: Soil (agricultural) - Value: 0.09 mg/kg
- isobutyl acetate [2] - CAS: 110-19-0
Target: Fresh Water - Value: 0.17 mg/l
Target: Marine water - Value: 0.017 mg/l
Target: Intermittent emission - Value: 0.34 mg/l
Target: Microorganisms in sewage treatments - Value: 200 mg/l
Target: Freshwater sediments - Value: 0.877 mg/kg
Target: Marine water sediments - Value: 0.0877 mg/kg
Target: Soil (agricultural) - Value: 0.0755 mg/kg
- butanone; ethyl methyl ketone - CAS: 78-93-3
Target: Fresh Water - Value: 55.8 mg/l
Target: Intermittent emission - Value: 55.8 mg/l
Target: Microorganisms in sewage treatments - Value: 709 mg/l
Target: Freshwater sediments - Value: 284.7 mg/kg
Target: Marine water sediments - Value: 284.7 mg/kg
Target: Soil (agricultural) - Value: 22.5 mg/kg
Target: Food chain - Value: 1000 mg/kg
- xylene [4] - CAS: 1330-20-7
Target: Fresh Water - Value: 0.32 mg/l
Target: Marine water - Value: 0.32 mg/l
Target: Intermittent emission - Value: 0.32 mg/l
Target: Freshwater sediments - Value: 12.46 mg/kg
Target: Marine water sediments - Value: 12.46 mg/kg
Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Target: Soil (agricultural) - Value: 2.31 mg/kg
 ethyl acetate - CAS: 141-78-6
 Target: Fresh Water - Value: 0.24 mg/l
 Target: Marine water - Value: 0.024 mg/l
 Target: Intermittent emission - Value: 1.65 mg/l
 Target: Microorganisms in sewage treatments - Value: 650 mg/l
 Target: Freshwater sediments - Value: 1.15 mg/kg
 Target: Marine water sediments - Value: 0.115 mg/kg
 Target: Soil (agricultural) - Value: 0.148 mg/kg
 Target: Food chain - Value: 200 mg/kg
 2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
 Target: Fresh Water - Value: 0.4 mg/l
 Target: Marine water - Value: 0.04 mg/l
 Target: Freshwater sediments - Value: 1.52 mg/kg
 Target: Marine water sediments - Value: 0.152 mg/kg
 Target: Intermittent emission - Value: 11 mg/l
 Target: Microorganisms in sewage treatments - Value: 10 mg/l
 Target: Soil (agricultural) - Value: 0.06 mg/kg
 Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67 - Index number: 607-176-00-3
 Target: Fresh Water - Value: 0.023 mg/l
 Target: Marine water - Value: 0.00023 mg/l
 Target: Freshwater sediments - Value: 7.26 mg/l
 Target: Marine water sediments - Value: 0.726 mg/l
 Target: Intermittent emission - Value: 0.023 mg/l
 Target: Microorganisms in sewage treatments - Value: 100 mg/l
 Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
 Target: Fresh Water - Value: 0.0022 mg/l
 Target: Marine water - Value: 0.00022 mg/l
 Target: Intermittent emission - Value: 0.009 mg/l
 Target: Marine water sediments - Value: 0.11 mg/kg
 Target: Soil (agricultural) - Value: 0.21 mg/kg
 Target: Microorganisms in sewage treatments - Value: 1 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Eye glasses with side protection. (EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)

Respiratory protection:

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 79 °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	6.7% - 1.3% Vol. (Toluene)
Vapour density:	> 1
Flash point:	< 0 °C
Evaporation rate:	N.D.
Vapour pressure:	N.D. (20 °C)
Relative density:	0.930 - 0.950
Solubility in water:	partial
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
Miscibility:	N.D.
Fat Solubility:	N.D.
Conductivity:	N.D.

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Substance Groups relevant properties N.A.

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

d) respiratory or skin sensitisation

The product is classified: Skin Sens. 1 H317

e) germ cell mutagenicity

Not classified

No data available for the product

f) carcinogenicity

Not classified

No data available for the product

g) reproductive toxicity

The product is classified: Repr. 2 H361

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

The product is classified: STOT RE 2 H373

j) aspiration hazard

Not classified

No data available for the product

Toxicological information of the main substances found in the product:

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5580 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 28.1 mg/l - Duration: 4h - Source: OECD 403

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 - Notes: 24h

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10760 mg/kg - Source: OECD 423

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OECD 403

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401

Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403

Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

butanone; ethyl methyl ketone - CAS: 78-93-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2193 mg/kg - Source: OECD 423

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat = 23.5 mg/l - Duration: 8h

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg
 Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h
 Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

ethyl acetate - CAS: 141-78-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4934 mg/kg - Source: OCSE 401
 Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2830 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat > 24.6 mg/l - Duration: 4h

methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
 Test: LC50 - Route: Inhalation - Species: Rat > 29.8 mg/l - Duration: 4h

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
 Test: LD50 - Route: Skin - Species: Rabbit > 3000 mg/kg

toluene - CAS: 108-88-3

Effects following acute exposure:

At 200 ppm: mild but definite decrease in co-ordination and in reaction time, fatigue, confusion, paraesthesia of the skin; the fatigue lasted over a number of hours together with mild insomnia.

At 400 ppm: worsening of symptoms and mental confusion.

n-butyl acetate - CAS: 123-86-4

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.

butanone; ethyl methyl ketone - CAS: 78-93-3

High exposure can cause drowsiness, migraine, narcosis and dizziness.

The extended contact and/or repeated with skin can cause dermatitis.

Environmental concentrations more than 200 ppm result irritating for eyes and respiratory tract.

xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

ethyl acetate - CAS: 141-78-6

The product is extremely volatile and provokes for inhalation, irritation to respiratory tracts. Acute exposition can cause depression of central nervous system with effects such as drowsiness, reflex loss, narcosis.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

toluene - Group 3

xylene [4] - Group 3

methyl methacrylate; methyl 2-methylprop-2-enoate - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Not classified for environmental hazards

No data available for the product

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 134 mg/l - Duration h: 3
 Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48
 Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

- Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72
 Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d
 Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d
- n-butyl acetate - CAS: 123-86-4
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203
 Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72
- isobutyl acetate [2] - CAS: 110-19-0
- a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Algae = 397 mg/l - Duration h: 72 - Notes: OCSE 201
 Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202
 Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)
- butanone; ethyl methyl ketone - CAS: 78-93-3
- a) Aquatic acute toxicity:
 Endpoint: EC50 - Species: Daphnia = 308 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae = 2029 mg/l - Duration h: 96
 Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96
- xylene [4] - CAS: 1330-20-7
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Algae = 4.3 mg/l - Duration h: 72
 Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d
 Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d
- ethyl acetate - CAS: 141-78-6
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Algae > 100 mg/l - Duration h: 72
 Endpoint: EC50 - Species: Daphnia = 165 mg/l - Duration h: 48
 Endpoint: LC50 - Species: Fish = 230 mg/l - Duration h: 96
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Daphnia = 2.4 mg/l - Notes: 21d
- methyl methacrylate; methyl 2-methylprop-2-enoate - CAS: 80-62-6
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 191 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Daphnia = 69 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae > 110 mg/l - Duration h: 72
- Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67 - Index number: 607-176-00-3
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 2.8 mg/l - Duration h: 96
 Endpoint: EC50 - Species: Daphnia = 4 mg/l - Duration h: 48
 Endpoint: EC50 - Species: Algae = 9 mg/l - Duration h: 72
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Daphnia = 0.23 mg/l - Notes: 21 day
 Endpoint: NOEC - Species: Fish = 1.2 mg/l - Duration h: 96
- Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
- a) Aquatic acute toxicity:
 Endpoint: LC50 - Species: Fish = 0.9 mg/l - Duration h: 72
 Endpoint: EC50 - Species: Daphnia = 1.68 mg/l - Duration h: 72
- b) Aquatic chronic toxicity:
 Endpoint: NOEC - Species: Daphnia = 1 mg/l - Notes: 21 day
 Endpoint: NOEC - Species: Algae = 0.22 mg/l - Duration h: 72
- Persistence and degradability
- toluene - CAS: 108-88-3
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- n-butyl acetate - CAS: 123-86-4
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- isobutyl acetate [2] - CAS: 110-19-0
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- butanone; ethyl methyl ketone - CAS: 78-93-3
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- xylene [4] - CAS: 1330-20-7
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- 2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
 Biodegradability: Readily biodegradable - Test: N.A. - Duration h: N.A. - %: N.A. - Notes: N.A.
- Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

Biodegradability: Non-readily biodegradable - Test: Biochemical oxygen demand - Duration h: 28 days - %: 38 -
Notes: OECD 301F

Bioaccumulative potential
N.A.
Mobility in soil
N.A.
Other adverse effects
None

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number
ADR-UN Number: 1263
DOT number: UN1263
IATA-UN Number: 1263
IMDG-UN Number: 1263

UN proper shipping name
ADR-Shipping Name: PAINT
DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
ADR-Technical Name: Paint
IATA-Shipping Name: PAINT
IATA-Technical name: Paint
IMDG-Shipping Name: PAINT
IMDG-Shipping name: Paint

Transport hazard class(es)
ADR-Class: 3
DOT Hazard Class: 3
ADR - Hazard identification number: 33
IATA-Class: 3
IATA-Label: 3
IMDG-Class: 3
IMDG-Class: 3

Packing group
ADR-Packing Group: II
DOT Packing group: II
IATA-Packing group: II
IMDG-Packing group: II

Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
N.A.

Special precautions
Rail (RID): 3
DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28
ADR-Subsidiary risks: -
ADR-S.P.: 163 367 640D 650
ADR-Transport category (Tunnel restriction code): 2 (D/E)
IATA-Passenger Aircraft: 353
IATA-Subsidiary risks: -
IATA-Cargo Aircraft: 364
IATA-S.P.: A3 A72 A192
IATA-ERG: 3L
IMDG-EmS: F-E , S-E
IMDG-Subsidiary risks: -
IMDG-Stowage and handling: Category A

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

IMDG-Segregation: -

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

List of substances included in the TSCA inventory: toluene, n-butyl acetate, isobutyl acetate [2], butanone; ethyl methyl ketone, xylene [4], ethyl acetate, 2-methylpropan-1-ol; iso-butanol, methyl methacrylate; methyl 2-methylprop-2-enoate, 2-hydroxyethyl methacrylate.

List of substances not included in the TSCA inventory: Hydroxyphenyl-benzotriazole derivatives EC No. 400-830-67, Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

TSCA listed substances:

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

n-butyl acetate is listed in TSCA Section 8b

isobutyl acetate [2] is listed in TSCA Section 8b

butanone; ethyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR

xylene [4] is listed in TSCA Section 8b

ethyl acetate is listed in TSCA Section 8b

2-methylpropan-1-ol; iso-butanol is listed in TSCA Section 8b, Section 8d HSDR

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in TSCA Section 8b, Section 8d HSDR

2-hydroxyethyl methacrylate is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: toluene, n-butyl acetate, isobutyl acetate [2], butanone; ethyl methyl ketone, xylene [4], ethyl acetate, 2-methylpropan-1-ol; iso-butanol, methyl methacrylate; methyl 2-methylprop-2-enoate.

Section 313 – Toxic chemical list: toluene, xylene [4], methyl methacrylate; methyl 2-methylprop-2-enoate.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: toluene - Reportable quantity: 1000 pounds

n-butyl acetate - Reportable quantity: 5000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

butanone; ethyl methyl ketone - Reportable quantity: 5000 pounds

xylene [4] - Reportable quantity: 100 pounds

ethyl acetate - Reportable quantity: 5000 pounds

2-methylpropan-1-ol; iso-butanol - Reportable quantity: 5000 pounds

methyl methacrylate; methyl 2-methylprop-2-enoate - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 2237.386732 pounds.

CAA - Clean Air Act

CAA listed substances:

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

n-butyl acetate is listed in CAA Section 111

isobutyl acetate [2] is listed in CAA Section 111

butanone; ethyl methyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethyl acetate is listed in CAA Section 111

2-methylpropan-1-ol; iso-butanol is listed in CAA Section 111

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

n-butyl acetate is listed in CWA Section 304, Section 311

isobutyl acetate [2] is listed in CWA Section 311

xylene [4] is listed in CWA Section 304, Section 311

ethyl acetate is listed in CWA Section 304

methyl methacrylate; methyl 2-methylprop-2-enoate is listed in CWA Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

toluene

n-butyl acetate

isobutyl acetate [2]

butanone; ethyl methyl ketone

xylene [4]

ethyl acetate

2-methylpropan-1-ol; iso-butanol

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

methyl methacrylate; methyl 2-methylprop-2-enoate.
New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
toluene
n-butyl acetate
isobutyl acetate [2]
butanone; ethyl methyl ketone
xylene [4]
ethyl acetate
2-methylpropan-1-ol; iso-butanol
methyl methacrylate; methyl 2-methylprop-2-enoate.
Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
toluene
n-butyl acetate
isobutyl acetate [2]
butanone; ethyl methyl ketone
xylene [4]
ethyl acetate
2-methylpropan-1-ol; iso-butanol
methyl methacrylate; methyl 2-methylprop-2-enoate.

Volatile Organic compounds - VOCs = 69.99 %
Volatile Organic compounds - VOCs = 664.91 g/l
Volatile CMR substances = 0.00 %
Organic Carbon - C = 0.51

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet dated 5/17/2018, version 1
Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.
This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.

Safety Data Sheet

LFE423 SIVOSAT 35 Finitura acrilica trasp. - Clear Acrylic top coat

NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average