



## LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

Safety Data Sheet dated 12/12/2018, version 1

### 1. Identification

GHS Product identifier  
Mixture identification:  
Trade name: CHROMOLACK 80 Finitura PU bianca - PU White top coat  
Other means of identification  
Trade code: LFP400

Recommended use and restrictions on use  
Recommended use:  
Industrial and professional uses (SU3 - SU22)  
Varnish for wood






Supplier's details  
Company:  
NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1  
Importer:  
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.  
7900 Henri-Bourassa Blvd. W.  
Montreal, Quebec, Canada, H4S 1V4  
Tel :+1-514-832-4010  
Emergency phone number for Canada: Canutec (613) 996-6666  
Distributor:  
Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.  
7900 Henri-Bourassa Blvd. W.  
Montreal, Quebec, Canada, H4S 1V4  
Tel :+1-514-832-4010  
Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:  
msds@sivam.it

Emergency phone number  
NUOVA S.I.V.A.M. SpA - Tel. +39 02 90304.1 (Monday - Friday 8.00 - 15.00)  
Poison Centre - Ospedale di Niguarda - Milan - Tel. +39 02 66101029 (24 h)

### 2. Hazard identification

Classification of the hazardous product

-  Danger, Flam. Liq. 2, Highly flammable liquid and vapour.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, Eye Irrit. 2A, Causes serious eye irritation.
-  Warning, STOT SE 3, May cause respiratory irritation.
-  Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

GHS label elements, including precautionary statements  
Hazard pictograms:



Danger  
Hazard statements:  
H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash ... Thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of water/...  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 Call a POISON CENTER/ doctor/if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P321 Specific treatment (see ... On this label).  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P370+P378 In case of fire: Use ... to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.

#### Special provisions

None

#### Other hazards

None

#### Ingredient(s) with unknown acute toxicity

None.

### 3. Composition/Information on ingredients

#### Substances

N.A.

#### Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 15% - < 40%	Titanium Dioxide	CAS: 13463-67-7 EC: 236-675-5 REACH No.: 01-2119489379-17	The product is not classified as dangerous according to WHMIS 2015.
>= 10% - < 30%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> <li>⚠ B.6/3 Flam. Liq. 3 H226</li> <li>⚠ A.1/4/Dermal Acute Tox. 4 H312</li> <li>⚠ A.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ A.2/2 Skin Irrit. 2 H315</li> <li>⚠ A.8/3 STOT SE 3 H335</li> <li>⚠ A.9/2 STOT RE 2 H373</li> <li>⚠ A.10/1 Asp. Tox. 1 H304</li> </ul>
>= 1% - < 5%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	<ul style="list-style-type: none"> <li>⚠ B.6/2 Flam. Liq. 2 H225</li> <li>CAN-HAE/C3 Aquatic Chronic 3 H412</li> <li>⚠ A.1/4/Inhal Acute Tox. 4 H332</li> <li>⚠ A.9/2 STOT RE 2 H373</li> <li>⚠ A.10/1 Asp. Tox. 1 H304</li> </ul>
>= 1% - < 5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-2119485493-29	<ul style="list-style-type: none"> <li>⚠ B.6/3 Flam. Liq. 3 H226</li> <li>⚠ A.8/3 STOT SE 3 H336</li> </ul>
>= 1% - < 5%	4-methylpentan-2-one; isobutyl methyl ketone	Index number: 606-004-00-4 CAS: 108-10-1 EC: 203-550-1 REACH No.: 01-2119473980-30	<ul style="list-style-type: none"> <li>⚠ B.6/2 Flam. Liq. 2 H225</li> <li>⚠ A.8/3 STOT SE 3 H335</li> <li>⚠ A.1/4/Inhal Acute Tox. 4 H332</li> </ul>

The actual concentration of the components listed above is withheld as a trade secret.

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

#### 4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

#### 5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties:

N.D. in volume

Oxidizing properties:

N.D.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

---

#### 7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

None in particular.  
 Instructions as regards storage premises:  
 Cool and adequately ventilated.  
 Safety electric system.  
 Storage temperature:  
 Store at ambient temperature.

#### 8. Exposure controls/personal protection

##### Control parameters

Titanium Dioxide - CAS: 13463-67-7  
 ACGIH - TWA(8h): 10 mg/m<sup>3</sup> - Notes: A4 - LRT irr

xylene [4] - CAS: 1330-20-7  
 EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin  
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

ethylbenzene - CAS: 100-41-4  
 EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin  
 ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

n-butyl acetate - CAS: 123-86-4  
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 EU - TWA(8h): 83 mg/m<sup>3</sup>, 20 ppm - STEL: 208 mg/m<sup>3</sup>, 50 ppm  
 ACGIH - TWA(8h): 20 ppm - STEL: 75 ppm - Notes: A3, BEI - URT irr, dizziness, headache

##### DNEL Exposure Limit Values

Titanium Dioxide - CAS: 13463-67-7  
 Worker Industry: 10 mg/m<sup>3</sup> - Worker Professional: 10 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
 Consumer: 700 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7  
 Worker Industry: 289 mg/m<sup>3</sup> - Worker Professional: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

ethylbenzene - CAS: 100-41-4  
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects  
 Worker Industry: 77 mg/m<sup>3</sup> - Worker Professional: 77 mg/m<sup>3</sup> - Consumer: 15 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

n-butyl acetate - CAS: 123-86-4  
 Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 960 mg/m<sup>3</sup> - Worker Professional: 960 mg/m<sup>3</sup> - Consumer: 859.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects  
 Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 480 mg/m<sup>3</sup> - Worker Professional: 480 mg/m<sup>3</sup> - Consumer: 102.34 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Worker Industry: 83 mg/m<sup>3</sup> - Worker Professional: 83 mg/m<sup>3</sup> - Consumer: 14.7 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects  
 Worker Industry: 208 mg/m<sup>3</sup> - Worker Professional: 208 mg/m<sup>3</sup> - Consumer: 115.2 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects  
 Worker Industry: 83 mg/m<sup>3</sup> - Worker Professional: 83 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, local effects  
 Worker Industry: 208 mg/m<sup>3</sup> - Worker Professional: 208 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects  
 Worker Industry: 11.8 mg/kg - Worker Professional: 11.8 mg/kg - Consumer: 4.2 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

##### PNEC Exposure Limit Values

Titanium Dioxide - CAS: 13463-67-7  
 Target: Fresh Water - Value: 0.184 mg/l  
 Target: Marine water - Value: 0.0184 mg/l  
 Target: Intermittent emission - Value: 0.61 mg/l  
 Target: Freshwater sediments - Value: 1000 mg/kg  
 Target: Marine water sediments - Value: 100 mg/kg  
 Target: Microorganisms in sewage treatments - Value: 100 mg/l

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

	Target: Soil (agricultural) - Value: 100 mg/kg
	Target: Food chain - Value: 1667 mg/kg
xylene [4] - CAS: 1330-20-7	
	Target: Fresh Water - Value: 0.327 mg/l
	Target: Marine water - Value: 0.327 mg/l
	Target: Intermittent emission - Value: 0.327 mg/l
	Target: Freshwater sediments - Value: 12.46 mg/kg
	Target: Marine water sediments - Value: 12.46 mg/kg
	Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
	Target: Soil (agricultural) - Value: 2.31 mg/kg
ethylbenzene - CAS: 100-41-4	
	Target: Fresh Water - Value: 0.1 mg/l
	Target: Marine water - Value: 0.01 mg/l
	Target: Freshwater sediments - Value: 13.7 mg/kg
	Target: Soil (agricultural) - Value: 2.68 mg/kg
	Target: Intermittent emission - Value: 0.1 mg/l
	Target: Microorganisms in sewage treatments - Value: 9.6 mg/l
n-butyl acetate - CAS: 123-86-4	
	Target: Fresh Water - Value: 0.18 mg/l
	Target: Marine water - Value: 0.018 mg/l
	Target: Intermittent emission - Value: 0.36 mg/l
	Target: Freshwater sediments - Value: 0.98 mg/kg
	Target: Marine water sediments - Value: 0.098 mg/kg
	Target: Microorganisms in sewage treatments - Value: 35.6 mg/l
	Target: Soil (agricultural) - Value: 0.09 mg/kg
4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1	
	Target: Fresh Water - Value: 0.6 mg/l
	Target: Marine water - Value: 0.06 mg/l
	Target: Freshwater sediments - Value: 8.27 mg/kg
	Target: Marine water sediments - Value: 0.83 mg/kg
	Target: Microorganisms in sewage treatments - Value: 27.5 mg/l
	Target: Soil (agricultural) - Value: 1.3 mg/kg
Biological Exposure Index	
xylene [4] - CAS: 1330-20-7	
	Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn
ethylbenzene - CAS: 100-41-4	
	Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and acid fenilgliossalico - Sampling Period: End of turn; End of working week
Appropriate engineering controls	
	None
Individual protection measures, such as personal protective equipment (PPE)	
Eye protection:	
	Eye glasses with side protection. (EN166)
Protection for skin:	
	Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
Protection for hands:	
	Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. (EN374)
Respiratory protection:	
	Use respiratory protection where ventilation is insufficient or exposure is prolonged.
	Use adequate protective respiratory equipment.
Thermal Hazards:	
	None

## 9. Physical and chemical properties

Appearance and colour:	white fluid
Odour:	typical
Odour threshold:	N.D.
pH:	N.A.
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Flash point:	< 23 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.0% - 0.9% Vol. (Xylene)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	1.340 - 1.360
Solubility in water:	N.D.
Solubility in oil:	partial

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

---

#### 10. Stability and reactivity

Reactivity	It may generate dangerous reactions (See subsections below)
Chemical stability	It may generate dangerous reactions (See subsections below)
Possibility of hazardous reactions	It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.
Conditions to avoid	Avoid accumulating electrostatic charge.
Incompatible materials	Avoid contact with combustible materials. The product could catch fire.
Hazardous decomposition products	None.

---

#### 11. Toxicological information

Information on toxicological effects	
Toxicological information of the product:	
CHROMOLACK 80 Finitura PU bianca - PU White top coat	
a) acute toxicity	Not classified No data available for the product
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2 H315
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2A H319
d) respiratory or skin sensitisation	Not classified No data available for the product
e) germ cell mutagenicity	Not classified No data available for the product
f) carcinogenicity	Not classified No data available for the product
g) reproductive toxicity	Not classified No data available for the product
h) STOT-single exposure	The product is classified: STOT SE 3 H335
i) STOT-repeated exposure	The product is classified: STOT RE 2 H373
j) aspiration hazard	Not classified No data available for the product
Toxicological information of the main substances found in the product:	
Titanium Dioxide - CAS: 13463-67-7	
a) acute toxicity:	Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425 Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 3.5 mg/l - Duration: 4h
xylene [4] - CAS: 1330-20-7	
a) acute toxicity:	Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg Test: LD50 - Route: Oral - Species: Mouse = 5627 mg/kg Test: LC50 - Route: Inhalation - Species: Rat = 6700 Ppm - Duration: 4h Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
ethylbenzene - CAS: 100-41-4	
a) acute toxicity:	Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg Test: LD50 - Route: Inhalation - Species: Rat = 17.6 mg/l - Duration: 1h
i) STOT-repeated exposure:	Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity
n-butyl acetate - CAS: 123-86-4	

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

- a) acute toxicity:  
 Test: LD50 - Route: Oral - Species: Rat > 10760 mg/kg - Source: OECD 423  
 Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OECD 403  
 Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg - Source: OECD 402
- 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
- a) acute toxicity:  
 Test: LC50 - Route: Inhalation Vapour - Species: Rat > 2000 Ppm - Duration: 4h - Source: OCSE 403  
 Test: LD50 - Route: Oral - Species: Rat = 2080 mg/kg - Source: OCSE 401  
 Test: LD50 - Route: Skin - Species: Rabbit > 20 ml/kg - Source: OCSE 402
- xylene [4] - CAS: 1330-20-7  
 Observations on human subjects.  
 Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.
- n-butyl acetate - CAS: 123-86-4  
 The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.  
 Symptoms of illness at 500 ppm. Serious toxic effects at 2.000 ppm for 60 min.
- 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Product is harmful if inhaled.  
 Repeated exposure can cause irritation to respiratory tract, skin dryness, cough, cephalic nausea, dizziness and vomiting. Symptoms of chronic exposure are neurological, gastro-intestinal and respiratory.

Substance(s) listed on the NTP report on Carcinogens:  
 None.

Substance(s) listed on the IARC Monographs:  
 Titanium Dioxide - Group 2B  
 xylene [4] - Group 3  
 ethylbenzene - Group 2B  
 4-methylpentan-2-one; isobutyl methyl ketone - Group 2B.

Substance(s) listed as OSHA Carcinogen(s):  
 None.

Substance(s) listed as NIOSH Carcinogen(s):  
 Titanium Dioxide.

## 12. Ecological information

### Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CHROMOLACK 80 Finitura PU bianca - PU White top coat

Not classified for environmental hazards

No data available for the product

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day

Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 674 mg/l - Duration h: 72

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia > 200 mg/l - Duration h: 48 - Notes: OECD 202

Endpoint: LC50 - Species: Fish > 179 mg/l - Duration h: 96 - Notes: OECD 203

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae > 146 mg/l - Notes: 7 days

Endpoint: NOEC - Species: Daphnia = 30 mg/l - Notes: 21 days

Persistence and degradability



## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

xylene [4] - CAS: 1330-20-7  
 Biodegradability: Readily biodegradable  
 ethylbenzene - CAS: 100-41-4  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80  
 n-butyl acetate - CAS: 123-86-4  
 Biodegradability: Readily biodegradable  
 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1  
 Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83 - Notes: OECD 301F

Bioaccumulative potential  
 N.A.  
 Mobility in soil  
 N.A.  
 Other adverse effects  
 None

### 13. Disposal considerations

Safe handling and methods for disposal  
 Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

### 14. Transport information



UN number  
 TDG number: UN1263  
 ADR-UN Number: 1263  
 DOT number: UN1263  
 IATA-UN Number: 1263  
 IMDG-UN Number: 1263  
 UN proper shipping name  
 TDG-Shipping Name: PAINT  
 ADR-Shipping Name: PAINT  
 DOT-Shipping Name: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound  
 ADR-Technical Name: Paint  
 IATA-Shipping Name: PAINT  
 IATA-Technical name: Paint  
 IMDG-Shipping Name: PAINT  
 IMDG-Shipping name: Paint  
 Transport hazard class(es)  
 TDG Class: 3  
 ADR-Class: 3  
 DOT Hazard Class: 3  
 ADR - Hazard identification number: 33  
 IATA-Class: 3  
 IATA-Label: 3  
 IMDG-Class: 3  
 Packing group  
 TDG Packing group: II  
 ADR-Packing Group: II  
 DOT Packing group: II  
 IATA-Packing group: II  
 IMDG-Packing group: II  
 Environmental hazards  
 ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No  
 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)  
 N.A.  
 Special precautions in connection with transport or conveyance  
 Rail (RID): 3  
 TDG Special provisions: 59,142  
 DOT Special provisions: 149, 367, 383, B52, B131, IB2, T4, TP1, TP8, TP28  
 ADR-Subsidiary risks: -



## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

ADR-S.P.:	163 367 640D 650
ADR-Transport category (Tunnel restriction code):	2 (D/E)
IATA-Passenger Aircraft:	353
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	364
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

#### 15. Regulatory information

- Safety, health and environmental regulations specific for the product in question  
 This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.
- NPRI - National Pollutant Release Inventory  
 Substance(s) listed under NPRI:  
 None.
- DSL inventory - Domestic substances list  
 no substances listed
- NDSL inventory - Not Domestic substances list  
 no substances listed
- TSCA inventory  
 All the components are listed on the TSCA inventory.
- TSCA listed substances:  
 Titanium Dioxide is listed in TSCA Section 8b  
 xylene [4] is listed in TSCA Section 8b  
 ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR  
 n-butyl acetate is listed in TSCA Section 8b  
 4-methylpentan-2-one; isobutyl methyl ketone is listed in TSCA Section 8b, Section 8d HSDR.
- USA - Federal regulations
- SARA - Superfund Amendments and Reauthorization Act  
 Section 302 – Extremely Hazardous Substances: no substances listed.  
 Section 304 – Hazardous substances: xylene [4], ethylbenzene, n-butyl acetate, 4-methylpentan-2-one; isobutyl methyl ketone.  
 Section 313 – Toxic chemical list: xylene [4], ethylbenzene, 4-methylpentan-2-one; isobutyl methyl ketone.
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds  
 ethylbenzene - Reportable quantity: 1000 pounds  
 n-butyl acetate - Reportable quantity: 5000 pounds  
 4-methylpentan-2-one; isobutyl methyl ketone - Reportable quantity: 5000 pounds.  
 Reportable quantity for mixture: 441.1923665 pounds.
- CAA - Clean Air Act  
 CAA listed substances:  
 xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON  
 ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON  
 n-butyl acetate is listed in CAA Section 111  
 4-methylpentan-2-one; isobutyl methyl ketone is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.
- CWA - Clean Water Act  
 CWA listed substances:  
 xylene [4] is listed in CWA Section 304, Section 311  
 ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants  
 n-butyl acetate is listed in CWA Section 304, Section 311  
 4-methylpentan-2-one; isobutyl methyl ketone is listed in CWA Section 304.
- USA - State specific regulations
- California Proposition 65  
 Substance(s) listed under California Proposition 65:  
 Titanium Dioxide - Listed as carcinogen  
 ethylbenzene - Listed as carcinogen  
 4-methylpentan-2-one; isobutyl methyl ketone - Listed as carcinogen and reproductive toxicant.
- Massachusetts Right to know  
 Substance(s) listed under Massachusetts Right to know:  
 Titanium Dioxide  
 xylene [4]  
 ethylbenzene  
 n-butyl acetate

## Safety Data Sheet

### LFP400 CHROMOLACK 80 Finitura PU bianca - PU White top coat

4-methylpentan-2-one; isobutyl methyl ketone.  
 New Jersey Right to know  
 Substance(s) listed under New Jersey Right to know:  
 Titanium Dioxide  
 xylene [4]  
 ethylbenzene  
 n-butyl acetate  
 4-methylpentan-2-one; isobutyl methyl ketone.  
 Pennsylvania Right to know  
 Substance(s) listed under Pennsylvania Right to know:  
 Titanium Dioxide  
 xylene [4]  
 ethylbenzene  
 n-butyl acetate  
 4-methylpentan-2-one; isobutyl methyl ketone.

Volatile Organic compounds - VOCs = 35.74 %  
 Volatile Organic compounds - VOCs = 486.10 g/l  
 Volatile CMR substances = 0.01 %  
 Organic Carbon - C = 0.30

#### 16. Other information

Full text of phrases referred to in Section 3:  
 H226 Flammable liquid and vapour.  
 H312 Harmful in contact with skin.  
 H332 Harmful if inhaled.  
 H315 Causes skin irritation.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.  
 H225 Highly flammable liquid and vapour.  
 H412 Harmful to aquatic life with long lasting effects.  
 H336 May cause drowsiness or dizziness.

Safety Data Sheet dated 12/12/2018, version 1  
 Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.  
 This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average