

Safety Data Sheet



LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

Safety Data Sheet dated 6/1/2023, version 2

1. Identification

GHS Product identifier

Mixture identification:

Trade name: CHROMOLACK 20 Finitura PU bianca - PU White top coat

Other means of identification

Trade code: LFP406

Recommended use and restrictions on use

Recommended use:

IS- Industrial use

PW - Professional use

Varnish for wood

Supplier's details

Company:

NUOVA S.I.V.A.M. SpA - Via Monviso, 10 - 20008 BAREGGIO (MI) - Tel. +39 02-903041

Importer:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Distributor:

Quincaillerie Richelieu Ltée/Richelieu Hardware Ltd.

7900 Henri-Bourassa Blvd. W.

Montreal, Quebec, Canada, H4S 1V4

Tel :+1-800-361-6000

Emergency phone number for Canada: Canutec (613) 996-6666

Competent person responsible for the safety data sheet:

msds@sivam.it

Emergency phone number

NUOVA S.I.V.A.M. SpA - Tel. +39 02- 903041 (Monday - Friday 8.00 - 15.00)

Poison Centre - Ospedale di Niguarda Ca' Granda - Milan - Tel. +39 02-66101029 (24 h)

2. Hazard identification

Classification of the hazardous product

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, Skin Irrit. 2, Causes skin irritation.

⚠ Warning, Eye Irrit. 2A, Causes serious eye irritation.

⚠ Warning, Repr. 2, Suspected of damaging fertility or the unborn child.

⚠ Warning, STOT SE 3, May cause respiratory irritation.

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

GHS label elements, including precautionary statements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

H319 Causes serious eye irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof [electrical/ventilating/lighting/...] equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash ... Thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water/...
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/ doctor/if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see ... On this label).
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use ... to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special provisions

None

Other hazards

None

Ingredient(s) with unknown acute toxicity

None.

3. Composition/Information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

Qty	Name	Ident. Number	Classification
>= 15% - < 40%	titanium dioxide; [in powder form containing 1 % or more of particles with	Index number: 022-006-00-2	The product is not classified as dangerous according to WHMIS 2015.

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

	aerodynamic diameter ≤ 10 µm]	CAS: 13463-67-7 EC: 236-675-5 REACH No.: 01-2119489379-17	
>= 10% - < 30%	xylene [4]	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 CAN-HAE/C3 Aquatic Chronic 3 H412 ⚠ A.1/4/Dermal Acute Tox. 4 H312 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.8/3 STOT SE 3 H335 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304
>= 1% - < 5%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.1/4/Inhal Acute Tox. 4 H332 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.10/1 Asp. Tox. 1 H304 CAN-HAE/C3 Aquatic Chronic 3 H412
>= 1% - < 5%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.8/3 STOT SE 3 H336
>= 0.5% - < 1.5%	isobutyl acetate [2]	Index number: 607-026-00-7 CAS: 110-19-0 EC: 203-745-1 REACH No.: 01-2119488971-22	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.8/3 STOT SE 3 H336
>= 0.1% - < 1%	toluene	Index number: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 REACH No.: 01-2119471310-51	<ul style="list-style-type: none"> ⚠ B.6/2 Flam. Liq. 2 H225 ⚠ A.7/2 Repr. 2 H361 ⚠ A.10/1 Asp. Tox. 1 H304 ⚠ A.9/2 STOT RE 2 H373 ⚠ A.2/2 Skin Irrit. 2 H315 ⚠ A.8/3 STOT SE 3 H336
>= 0.1% - < 1%	Propylidyntrimethanol	CAS: 77-99-6 EC: 201-074-9 REACH No.: 01-2119486799-10	<ul style="list-style-type: none"> ⚠ A.7/2 Repr. 2 H361
22 ppm	octamethylcyclotetrasiloxane (D4)	Index number: 014-018-00-1 CAS: 556-67-2 EC: 209-136-7	<ul style="list-style-type: none"> ⚠ B.6/3 Flam. Liq. 3 H226 ⚠ A.7/2 Repr. 2 H361 CAN-HAE/C4 Aquatic Chronic 4 H413

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

		REACH No.: 01-2119529238-36	
22 ppm	Decamethylcyclopentasiloxane (D5)	CAS: 541-02-6 EC: 208-764-9 REACH No.: 01-2119511367-43	The product is not classified as dangerous according to WHMIS 2015.
5 ppm	Dodecamethylcyclohexasiloxane (D6)	CAS: 540-97-6 EC: 208-762-8 REACH No.: 01-2119517435-42	The product is not classified as dangerous according to WHMIS 2015.

The actual concentration of the components listed above is withheld as a trade secret.

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.D. in volume

Oxidizing properties: N.D.

Special protective equipment and precautions for fire-fighters

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. Exposure controls/personal protection

Control parameters

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

ACGIH - TWA(8h): 0.2 mg/m³ - Notes: Nanoscale particles; (R); A3 - LRT irr, pneumoconiosis

ACGIH - TWA(8h): 2.5 mg/m³ - Notes: Finescale particles; (R); A3 - LRT irr, pneumoconiosis

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

- ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: Skin
 TLV TWA - 275 mg/m³ - 50 ppm
 TLV STEL - 550 mg/m³ - 100 ppm
- isobutyl acetate [2] - CAS: 110-19-0
 ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr
 EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm
- toluene - CAS: 108-88-3
 EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 20 ppm - Notes: OTO; A4; BEI - CNS, visual & hearing impair; female repro system eff; pregnancy loss
- octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 ACGIH - TWA(8h): 123 mg/m³, 10 ppm
- Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 ACGIH - TWA(8h): 10 ppm
- DNEL Exposure Limit Values**
- titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7
 Worker Industry: 3.3 mg/m³ - Worker Professional: 3.3 mg/m³ - Exposure: Human
 Inhalation - Frequency: Long Term, systemic effects
- xylene [4] - CAS: 1330-20-7
 Worker Industry: 289 mg/m³ - Worker Professional: 289 mg/m³ - Consumer: 174 mg/m³
 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Consumer: 108 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- ethylbenzene - CAS: 100-41-4
 Worker Industry: 180 mg/kg - Worker Professional: 180 mg/kg - Exposure: Human
 Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 77 mg/m³ - Worker Professional: 77 mg/m³ - Consumer: 15 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 Worker Industry: 796 mg/kg - Worker Professional: 796 mg/kg - Consumer: 320 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 275 mg/m³ - Worker Professional: 275 mg/m³ - Consumer: 33 mg/m³ -
 Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 550 mg/m³ - Worker Professional: 550 mg/m³ - Exposure: Human
 Inhalation - Frequency: Short Term, local effects
 Consumer: 36 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- isobutyl acetate [2] - CAS: 110-19-0
 Worker Industry: 300 mg/m³ - Worker Professional: 300 mg/m³ - Consumer: 35.7 mg/m³
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Worker Industry: 600 mg/m³ - Worker Professional: 600 mg/m³ - Consumer: 300 mg/m³
 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
 Worker Industry: 10 mg/kg - Worker Professional: 10 mg/kg - Consumer: 5 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- toluene - CAS: 108-88-3
 Worker Industry: 384 mg/kg - Worker Professional: 384 mg/kg - Consumer: 226 mg/kg -
 Exposure: Human Dermal - Frequency: Long Term, systemic effects
 Worker Industry: 192 mg/m³ - Worker Professional: 192 mg/m³ - Consumer: 56.5 mg/m³
 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 Consumer: 8.13 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

effects

Propylidynetrimethanol - CAS: 77-99-6

Worker Industry: 3.3 mg/m³ - Worker Professional: 3.3 mg/m³ - Consumer: 0.58 mg/m³ -
Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 0.94 mg/kg - Worker Professional: 0.94 mg/kg - Consumer: 0.34 mg/kg -
Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 0.34 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Worker Industry: 73 mg/m³ - Worker Professional: 73 mg/m³ - Consumer: 13 mg/m³ -
Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 73 mg/kg - Worker Professional: 73 mg/kg - Consumer: 13 mg/kg -
Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Worker Industry: 24.2 mg/m³ - Worker Professional: 24.2 mg/m³ - Consumer: 4.3 mg/m³ -
Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Industry: 97.3 mg/m³ - Worker Professional: 97.3 mg/m³ - Consumer: 17.3
mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Worker Industry: 6.1 mg/m³ - Worker Professional: 6.1 mg/m³ - Consumer: 1.5 mg/m³ -
Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 11 mg/m³ - Worker Professional: 11 mg/m³ - Consumer: 2.7 mg/m³ -
Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.7 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects

PNEC Exposure Limit Values

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter
≤ 10 μm] - CAS: 13463-67-7

Target: Fresh Water - Value: 0.184 mg/l

Target: Marine water - Value: 0.0184 mg/l

Target: Intermittent emission - Value: 0.61 mg/l

Target: Freshwater sediments - Value: 1000 mg/kg

Target: Marine water sediments - Value: 100 mg/kg

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Soil (agricultural) - Value: 100 mg/kg

Target: Food chain - Value: 1667 mg/kg

xylylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Intermittent emission - Value: 0.327 mg/l

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

ethylbenzene - CAS: 100-41-4

Target: Fresh Water - Value: 0.1 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Freshwater sediments - Value: 13.7 mg/kg

Target: Marine water sediments - Value: 1.37 mg/kg

Target: Intermittent emission - Value: 0.1 mg/l

Target: Microorganisms in sewage treatments - Value: 9.6 mg/l

Target: Soil (agricultural) - Value: 2.68 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/l

Target: Marine water - Value: 0.0635 mg/l

Target: Intermittent emission - Value: 6.35 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

- Target: Freshwater sediments - Value: 3.29 mg/kg
- Target: Marine water sediments - Value: 0.329 mg/kg
- Target: Soil (agricultural) - Value: 0.29 mg/kg
- isobutyl acetate [2] - CAS: 110-19-0
 - Target: Fresh Water - Value: 0.17 mg/l
 - Target: Marine water - Value: 0.017 mg/l
 - Target: Intermittent emission - Value: 0.34 mg/l
 - Target: Microorganisms in sewage treatments - Value: 200 mg/l
 - Target: Freshwater sediments - Value: 0.877 mg/kg
 - Target: Marine water sediments - Value: 0.0877 mg/kg
 - Target: Soil (agricultural) - Value: 0.0755 mg/kg
- toluene - CAS: 108-88-3
 - Target: Fresh Water - Value: 0.074 mg/l
 - Target: Marine water - Value: 0.0074 mg/l
 - Target: Freshwater sediments - Value: 1.78 mg/kg
 - Target: Marine water sediments - Value: 0.178 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 0.84 mg/l
 - Target: Soil (agricultural) - Value: 0.313 mg/kg
- octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2
 - Target: Fresh Water - Value: 0.0015 mg/l
 - Target: Marine water - Value: 0.00015 mg/l
 - Target: Freshwater sediments - Value: 3 mg/kg
 - Target: Marine water sediments - Value: 0.3 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 10 mg/kg
 - Target: Soil (agricultural) - Value: 0.54 mg/kg
 - Target: Food chain - Value: 41 mg/kg
- Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6
 - Target: Fresh Water - Value: 0.0012 mg/kg
 - Target: Marine water - Value: 0.00012 mg/kg
 - Target: Freshwater sediments - Value: 11 mg/kg
 - Target: Marine water sediments - Value: 1.1 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 10 mg/l
 - Target: Soil (agricultural) - Value: 2.54 mg/kg
- Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6
 - Target: Freshwater sediments - Value: 13 mg/kg
 - Target: Marine water sediments - Value: 1.3 mg/kg
 - Target: Microorganisms in sewage treatments - Value: 1 mg/kg
 - Target: Soil (agricultural) - Value: 3.77 mg/kg
- Biological Exposure Index
 - xylylene [4] - CAS: 1330-20-7
 - Value: 1.5 g/g - medium: Urine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn
 - ethylbenzene - CAS: 100-41-4
 - Value: 0.15 g/g - medium: Urine - Biological Indicator: Sum of mandelic acid in urine and acid fenilgliossalico - Sampling Period: End of turn; End of working week
 - toluene - CAS: 108-88-3
 - Value: 0.02 mg/L - medium: Blood - Biological Indicator: Toluene in blood - Sampling Period: End of turn; End of working week
- Appropriate engineering controls
 - None
- Individual protection measures, such as personal protective equipment (PPE)
 - Eye protection:
 - Eye glasses with side protection. (EN166)
 - Protection for skin:
 - Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
 - Protection for hands:
 - Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

(EN374)

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Use adequate protective respiratory equipment.

Thermal Hazards:

None

9. Physical and chemical properties

Appearance and colour:	Liquid, White
Odour:	typical
Odour threshold:	N.D.
pH:	Not Relevant
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling range:	> 110 °C
Flash point:	> 23 °C
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	7.0% - 0.9% Vol. (Xylene)
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	1.320 - 1.340
Solubility in water:	partial
Solubility in oil:	partial
Partition coefficient (n-octanol/water):	N.D.
Auto-ignition temperature:	> 300 °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.

10. Stability and reactivity

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

CHROMOLACK 20 Finitura PU bianca - PU White top coat

a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2A H319

d) respiratory or skin sensitisation

Not classified

No data available for the product

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

- e) germ cell mutagenicity
Not classified
No data available for the product
- f) carcinogenicity
Not classified
No data available for the product
- g) reproductive toxicity
The product is classified: Repr. 2 H361
- h) STOT-single exposure
The product is classified: STOT SE 3 H335
- i) STOT-repeated exposure
The product is classified: STOT RE 2 H373
- j) aspiration hazard
Not classified
No data available for the product

Toxicological information of the main substances found in the product:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 425

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation Dust - Species: Rat > 3.5 mg/l - Duration: 4h

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 6.7 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit = 1100 mg/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat = 17.2 mg/l - Duration: 1h

i) STOT-repeated exposure:

Test: NOAEC - Route: Inhalation - Species: Rat = 0.5 mg/l - Notes: Ototoxicity

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.5 mg/l - Duration: 4h

isobutyl acetate [2] - CAS: 110-19-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 13.4 g/kg - Source: OCSE 401

Test: LD50 - Route: Oral - Species: Rabbit = 4.76 g/kg

Test: LC50 - Route: Inhalation - Species: Rat > 23.4 mg/l - Duration: 4h - Source: OCSE 403

Test: LD50 - Route: Skin - Species: Rabbit > 17.4 g/kg - Source: OCSE 402

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 25.7 mg/l - Duration: 4h - Source: OECD 403

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit = 500 mg/kg - Source: OECD 404 -

Notes: 24h

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 36 mg/l - Duration: 4h

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

Test: LD50 - Route: Skin - Species: Rabbit = 2.5 ml/kg
xylene [4] - CAS: 1330-20-7

Observations on human subjects.

Effects following acute exposure: dermatitis, eczema, irritation to the eyes and to the respiratory tract, dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - Group 2B

xylene [4] - Group 3

ethylbenzene - Group 2B

toluene - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm].

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

CHROMOLACK 20 Finitura PU bianca - PU White top coat

The product is classified: Aquatic Chronic 3 - H412

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72 - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: OECD TG 202

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56d

Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Notes: 21d

ethylbenzene - CAS: 100-41-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1.8 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 3.6 mg/l - Duration h: 96

Endpoint: LC50 - Species: Fish = 4.2 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.96 mg/l - Notes: 7 day

Endpoint: NOEC - Species: Algae = 3.4 mg/l - Duration h: 96

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96 - Notes: OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: LC50 - Species: Daphnia = 408 mg/l - Duration h: 48

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Notes: 14d OECD 204

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Notes: 21d OECD 211

isobutyl acetate [2] - CAS: 110-19-0

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 370 mg/l - Duration h: 72 - Notes: OCSE 201

Endpoint: EC50 - Species: Daphnia = 24.6 mg/l - Duration h: 48 - Notes: OCSE 202

Endpoint: LC50 - Species: Fish = 16.6 mg/l - Duration h: 96 - Notes: OCSE 203

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 23.2 mg/l - Notes: OCSE 201 (21d)

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

toluene - CAS: 108-88-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 12.5 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 3.78 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 5.5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 10 mg/l - Duration h: 72

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7d

Endpoint: NOEC - Species: Fish = 1.39 mg/l - Notes: 40d

Persistence and degradability

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable

ethylbenzene - CAS: 100-41-4

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 70-80

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Readily biodegradable - Duration h: 28 days - %: 83 - Notes: OECD 301F

isobutyl acetate [2] - CAS: 110-19-0

Biodegradability: Readily biodegradable

toluene - CAS: 108-88-3

Biodegradability: Readily biodegradable

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 3.7 - Notes: OECD 310

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 0 - Notes: OECD 310

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Biodegradability: Non-readily biodegradable - Duration h: 28 days - %: 4.47 - Notes: OECD 310

Bioaccumulative potential

octamethylcyclotetrasiloxane (D4) - CAS: 556-67-2

Bioaccumulation: Bioaccumulative

Decamethylcyclopentasiloxane (D5) - CAS: 541-02-6

Bioaccumulation: Bioaccumulative

Dodecamethylcyclohexasiloxane (D6) - CAS: 540-97-6

Bioaccumulation: Bioaccumulative

Mobility in soil

N.A.

Other adverse effects

None

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information



UN number

TDG number:

UN1263

ADR-UN Number:

1263

LFP406/2

Page n. 12 of 16

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

DOT number:	UN1263
IATA-UN Number:	1263
IMDG-UN Number:	1263
UN proper shipping name	
TDG-Shipping Name:	PAINT
ADR-Shipping Name:	PAINT
DOT-Shipping Name:	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base or Paint related material including paint thinning, drying, removing, or reducing compound
IATA-Shipping Name:	PAINT
IMDG-Shipping Name:	PAINT
Transport hazard class(es)	
TDG Class:	3
ADR-Class:	3
DOT Hazard Class:	3
ADR - Hazard identification number:	30
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
TDG Packing group:	III
ADR-Packing Group:	III
DOT Packing group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
	N.A.
Special precautions in connection with transport or conveyance	
Rail (RID):	3
TDG Special provisions:	59,142
DOT Special provisions:	367, B1, B52, B131, IB3, T2, TP1, TP29
ADR-Subsidiary hazards:	-
ADR-S.P.:	163 367 650
ADR-Transport category (Tunnel restriction code):	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) - WHMIS 2015.

NPRI - National Pollutant Release Inventory

Substance(s) listed under NPRI:

xylene [4] is listed in NPRI Part 5

ethylbenzene is listed in NPRI Part 1, Group A

2-methoxy-1-methylethyl acetate is listed in NPRI Part 5

toluene is listed in NPRI Part 5.

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

DSL inventory - Domestic substances list

All the components are listed in the DSL..

NDSL inventory - Not Domestic substances list

no substances listed

TSCA inventory

All the components are listed on the TSCA inventory.

TSCA listed substances:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] is listed in TSCA Section 8b

xylene [4] is listed in TSCA Section 8b

ethylbenzene is listed in TSCA Section 8b, Section 8d HSDR

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

isobutyl acetate [2] is listed in TSCA Section 8b

toluene is listed in TSCA Section 8b, Section 8d HSDR, Section 8a - CAIR

Propylidynetrimethanol is listed in TSCA Section 8b

octamethylcyclotetrasiloxane (D4) is listed in TSCA Section 12b, Section 4 Test, Section 8a - PAIR, Section 8b, Section 8d HSDR

Decamethylcyclopentasiloxane (D5) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

Dodecamethylcyclohexasiloxane (D6) is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR.

USA - Federal regulations

SARA - Superfund Amendments and Reauthorization Act

Section 302 – Extremely Hazardous Substances: no substances listed.

Section 304 – Hazardous substances: xylene [4], ethylbenzene, isobutyl acetate [2], toluene.

Section 313 – Toxic chemical list: xylene [4], ethylbenzene, toluene.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: xylene [4] - Reportable quantity: 100 pounds

ethylbenzene - Reportable quantity: 1000 pounds

isobutyl acetate [2] - Reportable quantity: 5000 pounds

toluene - Reportable quantity: 1000 pounds.

Reportable quantity for mixture: 437.3438846 pounds.

CAA - Clean Air Act

CAA listed substances:

xylene [4] is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

ethylbenzene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

isobutyl acetate [2] is listed in CAA Section 111

toluene is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON

Propylidynetrimethanol is listed in CAA Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

xylene [4] is listed in CWA Section 304, Section 311

ethylbenzene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants

isobutyl acetate [2] is listed in CWA Section 311

toluene is listed in CWA Section 304, Section 307, Section 311, CWA Priority Pollutants.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - Listed as carcinogen

ethylbenzene - Listed as carcinogen

toluene - Listed as reproductive toxicant.

Massachusetts Right to know

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

Substance(s) listed under Massachusetts Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
xylene [4]
ethylbenzene
isobutyl acetate [2]
toluene.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
xylene [4]
ethylbenzene
isobutyl acetate [2]
toluene.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
xylene [4]
ethylbenzene
isobutyl acetate [2]
toluene.

Volatile Organic compounds - VOCs = 34.25 %
Volatile Organic compounds - VOCs = 458.97 g/l
Volatile CMR substances = 0.01 %
Organic Carbon - C = 0.29

16. Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H413 May cause long lasting harmful effects to aquatic life.

Safety Data Sheet dated 6/1/2023, version 2
Sections modified from the previous revision:

3. Composition/Information on ingredients
8. Exposure controls/personal protection
9. Physical and chemical properties
11. Toxicological information
12. Ecological information
15. Regulatory information

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information

Safety Data Sheet

LFP406 CHROMOLACK 20 Finitura PU bianca - PU White top coat

relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average