

RICHELIEU HARDWARE LTD.

7900 Henri-Bourassa Ouest
St-Laurent, Quebec-QC, H4S 1V4 (CANADA)
☎ +1 450 664 0163 www.richelieu.com
E-mail: info@richelieu.com

Reference: **LI1015T**

Product description

White pre-catalysed primer, high solids, fast drying, and easy sanding.

Components

Reducer: DN2000M 10% - 20%

Do not use other thinners and reducers than DN2000M.

Physical-chemical characteristics

Density:	1.280 g/cm ³ ±0.010 at 20°C
Solid (% by weight):	58%
Viscosity	70" ± 4 Ford 4 at 20°C

Application systems

Application method is by spraying-gun, recommended coat thickness 120 to 150 gr/m².

Drying system

Very fast drying, in general at room temperature avoiding airflow in the drying area.

Usage field

White primer for lacquering processes. Application on MDF, chipboard and veneers. It can be employed as a primer or as a multilayer coating. Recoatable with pre-catalysed or post-catalysed coatings.

Storing and packaging.

Product must be stored away from electrical and heat sources. Don't smoke in the storage area. To avoid product leaking, once opened one package it will have to be carefully closed again and kept always in vertical position.

- *Maximum storing-time:* 18 months in original packaging,
- *Available packages:* 20 litres.

Remarks.

Follow the instructions on the package label and take care of precautions for storing and handling, according to those indicated on the Safety Data Sheet.