

LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior

Safety Data Sheet dated 7/3/2019, version 1

1. Identification	
GHS Product identifier	
Mixture identification:	
Trade name:	IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior
Other means of identification	
Trade code:	LWM051
Recommended use and restrictions on use	
Recommended use:	
Industrial and professional uses (SU3	- SU22)
Varnish for wood	
Supplier's details	
Company:	
	10 - 20010 BAREGGIO (MI) - Tel. +39 02 90304.1
Importer:	analysiana I dal
Quincaillerie Richelieu Ltée/Richelieu H 7900 Henri-Bourassa Blvd. W.	ardware Ltd.
Montreal, Quebec, Canada, H4S 1V4	
Tel +1-514-832-4010	
Emergency phone number for Canada:	Caputec (613) 006-6666
Distributor:	Canales (015) 330-0000
Quincaillerie Richelieu Ltée/Richelieu H	ardware I td
7900 Henri-Bourassa Blvd, W.	
Montreal, Quebec, Canada, H4S 1V4	
Tel :+1-514-832-4010	
Emergency phone number for Canada:	Canutec (613) 996-6666
Competent person responsible for the safety da	
msds@sivam.it	
Emergency phone number	
	0304.1 (Monday - Friday 8.00 - 15.00)
Poison Centre - Ospedale di Niguarda -	Milan - Tel. +39 02 66101029 (24 h)
	· · · · · · · · · · · · · · · · · · ·

2. Hazard identification

Classification of the hazardous product The product is not classified as dangerous according to WHMIS 2015.

GHS label elements, including precautionary statements The product is not classified as dangerous according to WHMIS 2015. Hazard pictograms: None Hazard statements: None Precautionary statements: None Special provisions None Other hazards None Ingredient(s) with unknown acute toxicity None.

3. Composition/Information on ingredients

Substances

N.A. Mixtures

Hazardous components within the meaning of WHMIS 2015 and related classification:

LWM051/1 Page n. 1 of 8



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior

Qty	Name	Ident. Number		Classification
>= 0.1% - < 1%	ammonia%	Index number: CAS: EC: REACH No.:	007-001-01-2 1336-21-6 215-647-6 01-2119982985- 14	 A.2/1B Skin Corr. 1B H314 A.8/3 STOT SE 3 H335 CAN-HAE/A1 Aquatic Acute 1 H400
5 ppm	mixture of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220- 239-6] (3:1) (CAS 26172-55- 4 + CAS 2682-20-4)	Index number: CAS:	613-167-00-5 55965-84-9	 A.2/1B Skin Corr. 1B H314 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410 A.1/3/Oral Acute Tox. 3 H301 A.1/3/Inhal Acute Tox. 3 H331
2 ppm	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	Index number: CAS: EC: REACH No.:	613-088-00-6 2634-33-5 220-120-9 01-2120761540- 60	 A.2/2 Skin Irrit. 2 H315 A.4.2/1 Skin Sens. 1 H317 A.3/1 Eye Dam. 1 H318 CAN-HAE/A1 Aquatic Acute 1 H400 A.1/4/Oral Acute Tox. 4 H302
349 ppb	2-metil-2H-isotiazol-3-one	CAS: EC: REACH No.:	2682-20-4 220-239-6 01-2120764690- 50	 A.1/2/Inhal Acute Tox. 2 H330 A.1/3/Dermal Acute Tox. 3 H311 A.1/3/Oral Acute Tox. 3 H301 A.2/1B Skin Corr. 1B H314 A.4.2/1A Skin Sens. 1A H317 CAN-HAE/A1 Aquatic Acute 1 H400 CAN-HAE/C1 Aquatic Chronic 1 H410

The actual concentration of the components listed above is withheld as a trade secret.

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact: Wash with plenty of water and soap.

- In case of eyes contact:
 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of Ingestion:
- Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY. In case of Inhalation:
- Remove casualty to fresh air and keep warm and at rest.
- Most important symptoms/effects, acute and delayed
 - None

Indication of immediate medical attention and special treatment needed, if necessary Treatment:

None

5. Fire-fighting measures

Suitable and unsuitable extinguish	ing media
Suitable extinguishing media:	-
Water.	
Carbon dioxide (CO2).	
Unsuitable extinguishing media:	
None in particular.	
Specific hazards arising from the I	nazardous product
Do not inhale explosion ar	nd combustion gases.
Burning produces heavy s	moke.
Hazardous combustion products:	
None	
Explosive properties:	N.D. in volume
Oxidizing properties:	N.D.

LWM051/1

Page n. 2 of 8



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal

interior

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove persons to safety. See protective measures under point 7 and 8. Methods and material for containment and cleaning up Wash with plenty of water.

7. Handling and storage

Precautions for safe handling Avoid contact with skin and eyes, inhalation of vapours and mists. Do not use on extensive surface areas in premises where there are occupants. Do not eat or drink while working. See also section 8 for recommended protective equipment. Conditions for safe storage, including any incompatibilities Keep away from food, drink and feed. Incompatible materials: None in particular. Instructions as regards storage premises: Adequately ventilated premises. Storage temperature: Store at ambient temperature.

8. Exposure controls/personal protection Control parameters ammonia ...% - CAS: 1336-21-6 ACGIH - TWA: 18 mg/m3, 25 ppm - STEL: 27 mg/m3, 35 ppm mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 TLV TWA - 0,05 mg/m3 TLV STEL - 0,23 mg/m3 **DNEL Exposure Limit Values** ammonia ...% - CAS: 1336-21-6 Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects Worker Industry: 6.8 mg/kg - Worker Professional: 6.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Industry: 47.6 mg/m3 - Worker Professional: 47.6 mg/m3 - Consumer: 23.8 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Industry: 36 mg/m3 - Worker Professional: 36 mg/m3 - Exposure: Human Inhalation - Frequency: Short Term, local effects Worker Industry: 14 mg/m3 - Worker Professional: 14 mg/m3 - Consumer: 2.8 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects Consumer: 6.8 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects **PNEC Exposure Limit Values** ammonia ...% - CAS: 1336-21-6 Target: Fresh Water - Value: 0.0011 mg/l Target: Marine water - Value: 0.0011 mg/l Target: Intermittent emission - Value: 0.0068 mg/l Appropriate engineering controls None Individual protection measures, such as personal protective equipment (PPE) Eye protection: Eye glasses with side protection. (EN166) Protection for skin: No special precaution must be adopted for normal use. Protection for hands:

LWM051/1 Page n. 3 of 8



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior

Suitable gloves type:(EN374) Respiratory protection: Not needed for normal use. Thermal Hazards: None

9. Physical and chemical properties

· ·	
Appearance and colour:	opalescent fluid
Odour:	typical
Odour threshold:	N.D.
pH:	8.5
Melting point / freezing point:	N.D. °C
Initial boiling point and boiling	range: > 100 °C
Flash point:	N.A.
Evaporation rate:	N.D.
Solid/gas flammability:	N.A.
Upper/lower flammability or ex	plosive limits: N.D.
Vapour pressure:	N.D. (20 °C)
Vapour density:	> 1
Relative density:	1.010 - 1.030
Solubility in water:	miscible
Solubility in oil:	partial
Partition coefficient (n-octanol/	/water): N.D.
Auto-ignition temperature:	N.D. °C
Decomposition temperature:	N.D. °C
Viscosity:	N.D.
•	

10. Stability and reactivity

Reactivity

Stable under normal conditions Chemical stability Stable under normal conditions

Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), nitrides, and powerful reducing agents.

It may catch fire on contact with oxidising mineral acids, elementary metals (alkalis and alkaline earth), nitrides, organic peroxides and hydroperoxides, oxidising agents, and reducing agents.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular. Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the product:

IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior a) acute toxicity

Not classified

No data available for the product

b) skin corrosion/irritation

Not classified

No data available for the product

c) serious eye damage/irritation

Not classified

No data available for the product

- d) respiratory or skin sensitisation
 - Not classified
 - No data available for the product
- e) germ cell mutagenicity Not classified
- No data available for the product
- f) carcinogenicity
 - Not classified

LWM051/1 Page n. 4 of 8



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior

No data available for the product g) reproductive toxicity Not classified No data available for the product h) STOT-single exposure Not classified No data available for the product i) STOT-repeated exposure Not classified No data available for the product j) aspiration hazard Not classified No data available for the product Toxicological information of the main substances found in the product: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat = 0.31 mg/l - Duration: 4h Test: LC50 - Route: Oral - Species: Rat = 53 mg/kg 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 670 mg/kg Test: LD50 - Route: Skin - Species: Rat = 4115 mg/kg 2-metil-2H-isotiazol-3-one - CAS: 2682-20-4 a) acute toxicity Test: LD50 - Route: Oral - Species: Rat = 285 mg/kg Substance(s) listed on the NTP report on Carcinogens: None. Substance(s) listed on the IARC Monographs: None. Substance(s) listed as OSHA Carcinogen(s): None Substance(s) listed as NIOSH Carcinogen(s):

12. Ecological information

None

```
Ecotoxicity
                 Adopt good working practices, so that the product is not released into the environment.
        IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior
                 Not classified for environmental hazards
                 No data available for the product
        ammonia ...% - CAS: 1336-21-6
                 a) Aquatic acute toxicity:
                          Endpoint: EC50 - Species: Daphnia = 24 mg/l - Duration h: 48
                          Endpoint: LC50 - Species: Fish = 0.53 mg/l - Duration h: 96
                 b) Aquatic chronic toxicity:
                          Endpoint: NOEC - Species: Daphnia = 0.79 mg/l - Duration h: 96
Endpoint: NOEC - Species: Fish = 0.022 mg/l - Notes: 73d
        mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)
         (CAS 26172-55-4 + CAS 2682-20-4) - CAS: 55965-84-9
                 a) Aquatic acute toxicity:
                          Endpoint: EC50 - Species: Algae = 0.018 mg/l - Duration h: 72
                          Endpoint: EC50 - Species: Daphnia = 0.126 mg/l - Duration h: 48
                          Endpoint: LC50 - Species: Fish = 0.188 mg/l - Duration h: 96
                 b) Aquatic chronic toxicity:
                          Endpoint: NOEC - Species: Algae = 0.0012 mg/l - Duration h: 72 - Notes: OECD 201
                          Endpoint: NOEC - Species: Daphnia = 0.004 mg/l - Notes: 21d - OECD 211
                          Endpoint: NOEC - Species: Fish = 0.098 mg/l - Notes: 28d - OECD 210
         1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5
                 a) Aquatic acute toxicity:
                          Endpoint: LC50 - Species: Fish = 2.18 mg/l - Duration h: 96
                          Endpoint: EC50 - Species: Daphnia = 2.94 mg/l - Duration h: 48
                          Endpoint: EC50 - Species: Algae = 0.11 mg/l - Duration h: 72
                 b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia = 1.2 mg/l - Notes: 21 d
Endpoint: NOEC - Species: Fish = 0.21 mg/l - Notes: 28 d
LWM051/1
```



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal

interior

2-metil-2H-isotiazol-3-one - CAS: 2682-20-4 a) Aquatic acute toxicity: Endpoint: LC50 - Species: Fish = 0.3 mg/l - Duration h: 96 Endpoint: EC50 - Species: Daphnia = 0.93 mg/l - Duration h: 48 Persistence and degradability 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one - CAS: 2634-33-5 Biodegradability: Readily biodegradable - Test: CO2 production - Duration h: 28 days - %: 100 - Notes: OECD 301B Bioaccumulative potential N.A. Mobility in soil N.A. Other adverse effects None

13. Disposal considerations

Safe handling and methods for disposal Recover if possible. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number Not classified as dangerous in the meaning of transport regulations. UN proper shipping name N.A. Transport hazard class(es) N.A. Packing group N.A Environmental hazards ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code) N.A Special precautions in connection with transport or conveyance N.A.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

- This Safety Data Sheet has been prepared according to the Hazardous Products Regulations (HPR) WHMIS 2015.
 - NPRI National Pollutant Release Inventory Substance(s) listed under NPRI:

None.

- DSL inventory Domestic substances list
- All the components are listed in the DSL.
- NDSL inventory Not Domestic substances list
- no substances listed
- TSCA inventory
 - All the components are listed on the TSCA inventory.

TSCA listed substances:

- ammonia ...% is listed in TSCA Section 8b
- mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (CAS 26172-55-4 + CAS 2682-20-4) is listed in TSCA Section 12b, Section 8b
 - 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one is listed in TSCA Section 8b
 - 2-metil-2H-isotiazol-3-one is listed in TSCA Section 12b, Section 8b.

USA - Federal regulations

- SARA Superfund Amendments and Reauthorization Act
 - Section 302 Extremely Hazardous Substances: no substances listed.
 - Section 304 Hazardous substances: ammonia ...%.
 - Section 313 Toxic chemical list: ammonia ...%.
 - CERCLA Comprehensive Environmental Response, Compensation, and Liability Act
 - Substance(s) listed under CERCLA: ammonia ...% Reportable quantity: 1000 pounds. Reportable quantity for mixture: 693481.276 pounds.

LWM051/1

Page n. 6 of 8



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal interior

CAA - Clean Air Act CAA listed substances: None. CWA - Clean Water Act CWA listed substances: ammonia ...% is listed in CWA Section 311.

USA - State specific regulations California Proposition 65 Substance(s) listed under California Proposition 65: None. Massachusetts Right to know Substance(s) listed under Massachusetts Right to know: ammonia ...%. New Jersey Right to know Substance(s) listed under New Jersey Right to know: ammonia ...%. Pennsylvania Right to know Substance(s) listed under Pennsylvania Right to know: ammonia ...%.

Volatile Organic compounds - VOCs = 3.84 % Volatile Organic compounds - VOCs = 39.54 g/l Volatile CMR substances = 0.00 % Organic Carbon - C = 0.02

16. Other information

Full text of phrases referred to in Section 3:

- H314 Causes severe skin burns and eye damage.
 - H335 May cause respiratory irritation.
 - H400 Very toxic to aquatic life.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H301 Toxic if swallowed.
 - H311 Toxic in contact with skin.
 - H331 Toxic if inhaled.
 - H315 Causes skin irritation.
 - H302 Harmful if swallowed.
 - H330 Fatal if inhaled.

Safety Data Sheet dated 7/3/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: CAS:	European Agreement concerning the International Carriage of Dangerous Goods by Road. Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health

LWM051/1

Page n. 7 of 8



LWM051 IDROFIX 50 Polivalente acqua interno - Clear WB self-seal

interior

NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average